

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流+25°C (uA)	漏电流+85°C (uA)	损耗角正切 -55°C 120Hz(%)	损耗角正切 +25°C 120Hz(%)	损耗角正切 +85°C 120Hz(%)
<b>300 Volt 额定电压 +85°C时</b>										
0.22	CA11C-300V0.22uF(*)A	T11C0A224(*)300(**)	(*)	300V0.22uF	A	3.3	33	110	12	18
0.33	CA11C-300V0.33uF(*)A	T11C0A334(*)300(**)	(*)	300V0.33uF	A	4.95	49.5	110	12	18
0.47	CA11C-300V0.47uF(*)B	T11C0B474(*)300(**)	(*)	300V0.47uF	B	7.05	70.5	110	12	18
0.68	CA11C-300V0.68uF(*)B	T11C0B684(*)300(**)	(*)	300V0.68uF	B	10.2	102	110	12	18
1	CA11C-300V1uF(*)B	T11C0B105(*)300(**)	(*)	300V1uF	B	15	150	110	12	18
1.5	CA11C-300V1.5uF(*)B	T11C0B155(*)300(**)	(*)	300V1.5uF	B	22.5	225	110	12	18
2.2	CA11C-300V2.2uF(*)C	T11C0C225(*)300(**)	(*)	300V2.2uF	C	33	330	110	12	18
3.3	CA11C-300V3.3uF(*)C	T11C0C335(*)300(**)	(*)	300V3.3uF	C	49.5	495	110	12	18
4.7	CA11C-300V4.7uF(*)C	T11C0C475(*)300(**)	(*)	300V4.7uF	C	70.5	705	110	12	18
6.8	CA11C-300V6.8uF(*)D	T11C0D685(*)300(**)	(*)	300V6.8uF	D	102	1020	110	12	18
10	CA11C-300V10uF(*)E	T11C0E106(*)300(**)	(*)	300V10uF	E	150	1500	110	12	18
<b>400 Volt 额定电压 +85°C时</b>										
0.47	CA11C-400V0.47uF(*)B	T11C0B474(*)400(**)	(*)	400V0.47uF	B	9.4	94	110	12	18
0.68	CA11C-400V0.68uF(*)B	T11C0B684(*)400(**)	(*)	400V0.68uF	B	13.6	136	110	12	18
1	CA11C-400V1uF(*)B	T11C0B105(*)400(**)	(*)	400V1uF	B	20	200	110	12	18
1.5	CA11C-400V1.5uF(*)C	T11C0C155(*)400(**)	(*)	400V1.5uF	C	30	300	110	12	18
2.2	CA11C-400V2.2uF(*)C	T11C0C225(*)400(**)	(*)	400V2.2uF	C	44	440	110	12	18
3.3	CA11C-400V3.3uF(*)C	T11C0C335(*)400(**)	(*)	400V3.3uF	C	66	660	110	12	18
4.7	CA11C-400V4.7uF(*)D	T11C0D475(*)400(**)	(*)	400V4.7uF	D	94	940	110	12	18
<b>450 Volt 额定电压 +85°C时</b>										
0.47	CA11C-450V0.47uF(*)B	T11C0B474(*)450(**)	(*)	450V0.47uF	B	10.575	105.75	110	12	18
0.68	CA11C-450V0.68uF(*)B	T11C0B684(*)450(**)	(*)	450V0.68uF	B	15.3	153	110	12	18
1	CA11C-450V1uF(*)B	T11C0B105(*)450(**)	(*)	450V1uF	B	22.5	225	110	12	18
1.5	CA11C-450V1.5uF(*)C	T11C0C155(*)450(**)	(*)	450V1.5uF	C	33.75	337.5	110	12	18
2.2	CA11C-450V2.2uF(*)C	T11C0C225(*)450(**)	(*)	450V2.2uF	C	49.5	495	110	12	18
3.3	CA11C-450V3.3uF(*)D	T11C0D335(*)450(**)	(*)	450V3.3uF	D	74.25	742.5	110	12	18
4.7	CA11C-450V4.7uF(*)D	T11C0D475(*)450(**)	(*)	450V4.7uF	D	105.75	1057.5	110	12	18

(\*): 电容量允许偏差: ±10%, ±20%  
 如电压、容量、电容量允许偏差等有特殊要求, 请与上海聚电联系。