

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25°C(uA)	漏电流 +85°C(uA)	漏电流 +125°C(uA)	损耗角正切 +25°C 120Hz(%)	损耗角正切 +85°C 120Hz(%)	损耗角正切 +125°C 120Hz(%)	ESR AT -55°C 100Hz
10 Volt 额定电压 +85°C时 (6.3 Volt 额定电压 +125°C时)												
3300	CA32-10V3300uF(*)A	T3200A338(*)010(**)	(*)	10V3300uF	A	33.00	264.00	264.00	45	45	45	11
4700	CA32-10V4700uF(*)A	T3200A478(*)010(**)	(*)	10V4700uF	A	47.00	376.00	376.00	40	40	40	10
6800	CA32-10V6800uF(*)B	T3200B688(*)010(**)	(*)	10V6800uF	B	68.00	544.00	544.00	40	40	40	10
8200	CA32-10V8200uF(*)B	T3200B828(*)010(**)	(*)	10V8200uF	B	82.00	656.00	656.00	40	40	40	10
10000	CA32-10V10000uF(*)C	T3200C109(*)010(**)	(*)	10V10000uF	C	100.00	800.00	800.00	40	40	40	10
15000	CA32-10V15000uF(*)C	T3200C159(*)010(**)	(*)	10V15000uF	C	150.00	1200.00	1200.00	45	45	45	9
22000	CA32-10V22000uF(*)D	T3200D229(*)010(**)	(*)	10V22000uF	D	220.00	1760.00	1760.00	55	55	55	9
33000	CA32-10V33000uF(*)D	T3200D339(*)010(**)	(*)	10V33000uF	D	330.00	2640.00	2640.00	55	55	55	8
16 Volt 额定电压 +85°C时 (10 Volt 额定电压 +125°C时)												
2200	CA32-16V2200uF(*)A	T3200A228(*)016(**)	(*)	16V2200uF	A	35.20	281.60	281.60	40	40	40	12
3300	CA32-16V3300uF(*)A	T3200A338(*)016(**)	(*)	16V3300uF	A	52.80	422.40	422.40	35	35	35	10
4700	CA32-16V4700uF(*)B	T3200B478(*)016(**)	(*)	16V4700uF	B	75.20	601.60	601.60	40	40	40	10
6800	CA32-16V6800uF(*)B	T3200B688(*)016(**)	(*)	16V6800uF	B	108.80	870.40	870.40	35	35	35	10
8200	CA32-16V8200uF(*)C	T3200C828(*)016(**)	(*)	16V8200uF	C	131.20	1049.60	1049.60	40	40	40	10
10000	CA32-16V10000uF(*)C	T3200C109(*)016(**)	(*)	16V10000uF	C	160.00	1280.00	1280.00	45	45	45	9
15000	CA32-16V15000uF(*)D	T3200D159(*)016(**)	(*)	16V15000uF	D	240.00	1920.00	1920.00	55	55	55	9
22000	CA32-16V22000uF(*)D	T3200D229(*)016(**)	(*)	16V22000uF	D	352.00	2816.00	2816.00	55	55	55	9
25 Volt 额定电压 +85°C时 (16 Volt 额定电压 +125°C时)												
1500	CA32-25V1500uF(*)A	T3200A158(*)025(**)	(*)	25V1500uF	A	37.50	300.00	300.00	45	45	45	18
2200	CA32-25V2200uF(*)A	T3200A228(*)025(**)	(*)	25V2200uF	A	55.00	440.00	440.00	35	35	35	15
3300	CA32-25V3300uF(*)B	T3200B338(*)025(**)	(*)	25V3300uF	B	82.50	660.00	660.00	35	35	35	13
4700	CA32-25V4700uF(*)B	T3200B478(*)025(**)	(*)	25V4700uF	B	117.50	940.00	940.00	35	35	35	10
6800	CA32-25V6800uF(*)C	T3200C688(*)025(**)	(*)	25V6800uF	C	170.00	1360.00	1360.00	35	35	35	10
8200	CA32-25V8200uF(*)C	T3200C828(*)025(**)	(*)	25V8200uF	C	205.00	1640.00	1640.00	40	40	40	10
10000	CA32-25V10000uF(*)D	T3200D109(*)025(**)	(*)	25V10000uF	D	250.00	2000.00	2000.00	55	55	55	10
15000	CA32-25V15000uF(*)D	T3200D159(*)025(**)	(*)	25V15000uF	D	375.00	3000.00	3000.00	55	55	55	9
40 Volt 额定电压 +85°C时 (25 Volt 额定电压 +125°C时)												
1000	CA32-40V1000uF(*)A	T3200A108(*)040(**)	(*)	40V1000uF	A	40.00	320.00	320.00	40	40	40	12
1500	CA32-40V1500uF(*)A	T3200A158(*)040(**)	(*)	40V1500uF	A	60.00	480.00	480.00	30	30	30	11
2200	CA32-40V2200uF(*)B	T3200B228(*)040(**)	(*)	40V2200uF	B	88.00	704.00	704.00	30	30	30	8
3300	CA32-40V3300uF(*)C	T3200C338(*)040(**)	(*)	40V3300uF	C	132.00	1056.00	1056.00	30	30	30	8
4700	CA32-40V4700uF(*)C	T3200C478(*)040(**)	(*)	40V4700uF	C	188.00	1504.00	1504.00	30	30	30	8
6800	CA32-40V6800uF(*)D	T3200D688(*)040(**)	(*)	40V6800uF	D	272.00	2176.00	2176.00	55	55	55	7
10000	CA32-40V10000uF(*)D	T3200D109(*)040(**)	(*)	40V10000uF	D	400.00	3200.00	3200.00	55	55	55	7
63 Volt 额定电压 +85°C时 (40 Volt 额定电压 +125°C时)												
680	CA32-63V680uF(*)A	T3200A687(*)063(**)	(*)	63V680uF	A	42.84	342.72	342.72	30	30	30	22
1000	CA32-63V1000uF(*)A	T3200A108(*)063(**)	(*)	63V1000uF	A	63.00	504.00	504.00	30	30	30	18
1500	CA32-63V1500uF(*)B	T3200B158(*)063(**)	(*)	63V1500uF	B	94.50	756.00	756.00	30	30	30	12
2200	CA32-63V2200uF(*)C	T3200C228(*)063(**)	(*)	63V2200uF	C	138.60	1108.80	1108.80	30	30	30	10
3300	CA32-63V3300uF(*)C	T3200C338(*)063(**)	(*)	63V3300uF	C	207.90	1663.20	1663.20	30	30	30	10
4700	CA32-63V4700uF(*)D	T3200D478(*)063(**)	(*)	63V4700uF	D	296.10	2368.80	2368.80	55	55	55	9
6800	CA32-63V6800uF(*)D	T3200D688(*)063(**)	(*)	63V6800uF	D	428.40	3427.20	3427.20	55	55	55	9
75 Volt 额定电压 +85°C时 (50 Volt 额定电压 +125°C时)												
470	CA32-75V470uF(*)A	T3200A477(*)075(**)	(*)	75V470uF	A	35.25	282.00	282.00	25	25	25	20
680	CA32-75V680uF(*)A	T3200A687(*)075(**)	(*)	75V680uF	A	51.00	408.00	408.00	25	25	25	15
1000	CA32-75V1000uF(*)B	T3200B108(*)075(**)	(*)	75V1000uF	B	75.00	600.00	600.00	25	25	25	25
1500	CA32-75V1500uF(*)B	T3200B158(*)075(**)	(*)	75V1500uF	B	112.50	900.00	900.00	30	30	30	20
2200	CA32-75V2200uF(*)C	T3200C228(*)075(**)	(*)	75V2200uF	C	165.00	1320.00	1320.00	30	30	30	20
3300	CA32-75V3300uF(*)D	T3200D338(*)075(**)	(*)	75V3300uF	D	247.50	1980.00	1980.00	35	35	35	18
4700	CA32-75V4700uF(*)D	T3200D478(*)075(**)	(*)	75V4700uF	D	352.50	2820.00	2820.00	35	35	35	15
100 Volt 额定电压 +85°C时 (63 Volt 额定电压 +125°C时)												
330	CA32-100V330uF(*)A	T3200A337(*)100(**)	(*)	100V330uF	A	33.00	264.00	264.00	20	20	20	20
470	CA32-100V470uF(*)A	T3200A477(*)100(**)	(*)	100V470uF	A	47.00	376.00	376.00	20	20	20	15
680	CA32-100V680uF(*)B	T3200B687(*)100(**)	(*)	100V680uF	B	68.00	544.00	544.00	20	20	20	15
1000	CA32-100V1000uF(*)B	T3200B108(*)100(**)	(*)	100V1000uF	B	100.00	800.00	800.00	20	20	20	12
1500	CA32-100V1500uF(*)C	T3200C158(*)100(**)	(*)	100V1500uF	C	150.00	1200.00	1200.00	20	20	20	11
2200	CA32-100V2200uF(*)C	T3200C228(*)100(**)	(*)	100V2200uF	C	220.00	1760.00	1760.00	20	20	20	8
3300	CA32-100V3300uF(*)D	T3200D338(*)100(**)	(*)	100V3300uF	D	330.00	2640.00	2640.00	30	30	30	8
125 Volt 额定电压 +85°C时 (75 Volt 额定电压 +125°C时)												
220	CA32-125V220uF(*)A	T3200A227(*)125(**)	(*)	125V220uF	A	27.50	220.00	220.00	20	20	20	28
330	CA32-125V330uF(*)B	T3200B337(*)125(**)	(*)	125V330uF	B	41.25	330.00	330.00	15	15	15	19
470	CA32-125V470uF(*)B	T3200B477(*)125(**)	(*)	125V470uF	B	58.75	470.00	470.00	20	20	20	12
680	CA32-125V680uF(*)C	T3200C687(*)125(**)	(*)	125V680uF	C	85.00	680.00	680.00	15	15	15	12
1000	CA32-125V1000uF(*)C	T3200C108(*)125(**)	(*)	125V1000uF	C	125.00	1000.00	1000.00	20	20	20	12
1500	CA32-125V1500uF(*)D	T3200D158(*)125(**)	(*)	125V1500uF	D	187.50	1500.00	1500.00	30	30	30	11

(*) : 电容量允许偏差: ±10%, ±20%

如电压、容量、电容量允许偏差等有特殊要求, 请与上海聚电联系。