

容量 (μF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(μA)	漏电流 +85℃(μA)	漏电流 +125℃(μA)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)	ESR AT -55℃ 100Hz
150 Volt 额定电压 +85℃时 (95 Volt 额定电压 +125℃时)												
68	CA33A-150V68μF(*)E	T33A0E686(*)150(**)	(*)	150V68μF	E	10.20	81.60	81.60	35	35	35	55
100	CA33A-150V100μF(*)E	T33A0E107(*)150(**)	(*)	150V100μF	E	15.00	120.00	120.00	20	20	20	55
150	CA33A-150V150μF(*)F	T33A0F157(*)150(**)	(*)	150V150μF	F	22.50	180.00	180.00	30	30	30	50
220	CA33A-150V220μF(*)F	T33A0F227(*)150(**)	(*)	150V220μF	F	33.00	264.00	264.00	35	35	35	50
330	CA33A-150V330μF(*)G	T33A0G337(*)150(**)	(*)	150V330μF	G	49.50	396.00	396.00	35	35	35	35
470	CA33A-150V470μF(*)H	T33A0H477(*)150(**)	(*)	150V470μF	H	70.50	564.00	564.00	40	40	40	35
200 Volt 额定电压 +85℃时 (130 Volt 额定电压 +125℃时)												
3.3	CA33A-200V3.3μF(*)A	T33A0A335(*)200(**)	(*)	200V3.3μF	A	0.66	5.28	5.28	15	15	15	700
4.7	CA33A-200V4.7μF(*)B	T33A0B475(*)200(**)	(*)	200V4.7μF	B	0.94	7.52	7.52	18	18	18	500
6.8	CA33A-200V6.8μF(*)C	T33A0C685(*)200(**)	(*)	200V6.8μF	C	1.36	10.88	10.88	18	18	18	350
10	CA33A-200V10μF(*)C	T33A0C106(*)200(**)	(*)	200V10μF	C	2.00	16.00	16.00	20	20	20	260
15	CA33A-200V15μF(*)C	T33A0C156(*)200(**)	(*)	200V15μF	C	3.00	24.00	24.00	25	25	25	175
22	CA33A-200V22μF(*)D	T33A0D226(*)200(**)	(*)	200V22μF	D	4.40	35.20	35.20	25	25	25	140
33	CA33A-200V33μF(*)E	T33A0E336(*)200(**)	(*)	200V33μF	E	6.60	52.80	52.80	25	25	25	90
47	CA33A-200V47μF(*)E	T33A0E476(*)200(**)	(*)	200V47μF	E	9.40	75.20	75.20	30	30	30	80
68	CA33A-200V68μF(*)F	T33A0F686(*)200(**)	(*)	200V68μF	F	13.60	108.80	108.80	35	35	35	60
100	CA33A-200V100μF(*)F	T33A0F107(*)200(**)	(*)	200V100μF	F	20.00	160.00	160.00	40	40	40	60
150	CA33A-200V150μF(*)G	T33A0G157(*)200(**)	(*)	200V150μF	G	30.00	240.00	240.00	40	40	40	50
220	CA33A-200V220μF(*)H	T33A0H227(*)200(**)	(*)	200V220μF	H	44.00	352.00	352.00	40	40	40	45
250 Volt 额定电压 +85℃时 (160 Volt 额定电压 +125℃时)												
2.2	CA33A-250V2.2μF(*)A	T33A0A225(*)250(**)	(*)	250V2.2μF	A	0.55	4.40	4.40	14	14	14	1100
3.3	CA33A-250V3.3μF(*)B	T33A0B335(*)250(**)	(*)	250V3.3μF	B	0.83	6.60	6.60	15	15	15	700
4.7	CA33A-250V4.7μF(*)C	T33A0C475(*)250(**)	(*)	250V4.7μF	C	1.18	9.40	9.40	18	18	18	500
6.8	CA33A-250V6.8μF(*)C	T33A0C685(*)250(**)	(*)	250V6.8μF	C	1.70	13.60	13.60	18	18	18	350
10	CA33A-250V10μF(*)C	T33A0C106(*)250(**)	(*)	250V10μF	C	2.50	20.00	20.00	20	20	20	260
15	CA33A-250V15μF(*)D	T33A0D156(*)250(**)	(*)	250V15μF	D	3.75	30.00	30.00	25	25	25	175
22	CA33A-250V22μF(*)D	T33A0D226(*)250(**)	(*)	250V22μF	D	5.50	44.00	44.00	25	25	25	140
33	CA33A-250V33μF(*)E	T33A0E336(*)250(**)	(*)	250V33μF	E	8.25	66.00	66.00	25	25	25	90
47	CA33A-250V47μF(*)E	T33A0E476(*)250(**)	(*)	250V47μF	E	11.75	94.00	94.00	30	30	30	80
68	CA33A-250V68μF(*)F	T33A0F686(*)250(**)	(*)	250V68μF	F	17.00	136.00	136.00	35	35	35	60
100	CA33A-250V100μF(*)G	T33A0G107(*)250(**)	(*)	250V100μF	G	25.00	200.00	200.00	40	40	40	60
150	CA33A-250V150μF(*)H	T33A0H157(*)250(**)	(*)	250V150μF	H	37.50	300.00	300.00	45	45	45	50
300 Volt 额定电压 +85℃时 (190 Volt 额定电压 +125℃时)												
1.5	CA33A-300V1.5μF(*)A	T33A0A155(*)300(**)	(*)	300V1.5μF	A	0.45	3.60	3.60	8	8	8	1400
2.2	CA33A-300V2.2μF(*)B	T33A0B225(*)300(**)	(*)	300V2.2μF	B	0.66	5.28	5.28	14	14	14	1100
3.3	CA33A-300V3.3μF(*)C	T33A0C335(*)300(**)	(*)	300V3.3μF	C	0.99	7.92	7.92	15	15	15	700
4.7	CA33A-300V4.7μF(*)C	T33A0C475(*)300(**)	(*)	300V4.7μF	C	1.41	11.28	11.28	18	18	18	500
6.8	CA33A-300V6.8μF(*)C	T33A0C685(*)300(**)	(*)	300V6.8μF	C	2.04	16.32	16.32	20	20	20	350
10	CA33A-300V10μF(*)D	T33A0D106(*)300(**)	(*)	300V10μF	D	3.00	24.00	24.00	20	20	20	260
15	CA33A-300V15μF(*)D	T33A0D156(*)300(**)	(*)	300V15μF	D	4.50	36.00	36.00	25	25	25	175
22	CA33A-300V22μF(*)E	T33A0E226(*)300(**)	(*)	300V22μF	E	6.60	52.80	52.80	25	25	25	140
33	CA33A-300V33μF(*)E	T33A0E336(*)300(**)	(*)	300V33μF	E	9.90	79.20	79.20	25	25	25	90
47	CA33A-300V47μF(*)F	T33A0F476(*)300(**)	(*)	300V47μF	F	14.10	112.80	112.80	30	30	30	80
68	CA33A-300V68μF(*)G	T33A0G686(*)300(**)	(*)	300V68μF	G	20.40	163.20	163.20	35	35	35	60
100	CA33A-300V100μF(*)H	T33A0H107(*)300(**)	(*)	300V100μF	H	30.00	240.00	240.00	40	40	40	60
400 Volt 额定电压 +85℃时 (280 Volt 额定电压 +125℃时)												
1	CA33A-400V1μF(*)A	T33A0A105(*)400(**)	(*)	400V1μF	A	0.40	3.20	3.20	9	9	9	1800
1.5	CA33A-400V1.5μF(*)B	T33A0B155(*)400(**)	(*)	400V1.5μF	B	0.60	4.80	4.80	9	9	9	1400
2.2	CA33A-400V2.2μF(*)B	T33A0B225(*)400(**)	(*)	400V2.2μF	B	0.88	7.04	7.04	14	14	14	1100
3.3	CA33A-400V3.3μF(*)C	T33A0C335(*)400(**)	(*)	400V3.3μF	C	1.32	10.56	10.56	15	15	15	700
4.7	CA33A-400V4.7μF(*)C	T33A0C475(*)400(**)	(*)	400V4.7μF	C	1.88	15.04	15.04	18	18	18	500
6.8	CA33A-400V6.8μF(*)D	T33A0D685(*)400(**)	(*)	400V6.8μF	D	2.72	21.76	21.76	20	20	20	350
10	CA33A-400V10μF(*)D	T33A0D106(*)400(**)	(*)	400V10μF	D	4.00	32.00	32.00	20	20	20	260
15	CA33A-400V15μF(*)E	T33A0E156(*)400(**)	(*)	400V15μF	E	6.00	48.00	48.00	25	25	25	175
22	CA33A-400V22μF(*)F	T33A0F226(*)400(**)	(*)	400V22μF	F	8.80	70.40	70.40	25	25	25	140
33	CA33A-400V33μF(*)F	T33A0F336(*)400(**)	(*)	400V33μF	F	13.20	105.60	105.60	25	25	25	90
47	CA33A-400V47μF(*)G	T33A0G476(*)400(**)	(*)	400V47μF	G	18.80	150.40	150.40	35	35	35	80
68	CA33A-400V68μF(*)H	T33A0H686(*)400(**)	(*)	400V68μF	H	27.20	217.60	217.60	40	40	40	60
500 Volt 额定电压 +85℃时 (320 Volt 额定电压 +125℃时)												
3.3	CA33A-500V3.3μF(*)C	T33A0C335(*)500(**)	(*)	500V3.3μF	C	1.65	13.20	13.20	18	18	18	700
4.7	CA33A-500V4.7μF(*)C	T33A0C475(*)500(**)	(*)	500V4.7μF	C	2.35	18.80	18.80	18	18	18	500
6.8	CA33A-500V6.8μF(*)D	T33A0D685(*)500(**)	(*)	500V6.8μF	D	3.40	27.20	27.20	20	20	20	350
10	CA33A-500V10μF(*)E	T33A0E106(*)500(**)	(*)	500V10μF	E	5.00	40.00	40.00	25	25	25	260
15	CA33A-500V15μF(*)F	T33A0F156(*)500(**)	(*)	500V15μF	F	7.50	60.00	60.00	25	25	25	175
22	CA33A-500V22μF(*)G	T33A0G226(*)500(**)	(*)	500V22μF	G	11.00	88.00	88.00	25	25	25	140
33	CA33A-500V33μF(*)H	T33A0H336(*)500(**)	(*)	500V33μF	H	16.50	132.00	132.00	40	40	40	90
600 Volt 额定电压 +85℃时 (390 Volt 额定电压 +125℃时)												
1.5	CA33A-600V1.5μF(*)C	T33A0C155(*)600(**)	(*)	600V1.5μF	C	0.90	7.20	7.20	8	8	8	1400



CA33A 系列

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	漏电流 +125℃(uA)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)	ESR AT -55℃ 100Hz
2.2	CA33A-600V2.2uF(*)D	T33A0D225(*)600(**)	(*)	600V2.2uF	D	1.32	10.56	10.56	13	13	13	1100
3.3	CA33A-600V3.3uF(*)D	T33A0D335(*)600(**)	(*)	600V3.3uF	D	1.98	15.84	15.84	15	15	15	700
4.7	CA33A-600V4.7uF(*)E	T33A0E475(*)600(**)	(*)	600V4.7uF	E	2.82	22.56	22.56	18	18	18	500
6.8	CA33A-600V6.8uF(*)F	T33A0F685(*)600(**)	(*)	600V6.8uF	F	4.08	32.64	32.64	20	20	20	350
10	CA33A-600V10uF(*)G	T33A0G106(*)600(**)	(*)	600V10uF	G	6.00	48.00	48.00	25	25	25	260
15	CA33A-600V15uF(*)H	T33A0H156(*)600(**)	(*)	600V15uF	H	9.00	72.00	72.00	30	30	30	175

(*)：电容量允许偏差：±10%，±20%
如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。