



容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25°C (uA)	漏电流 +85°C (uA)	漏电流 +125°C (uA)	损耗角正切 +25°C 120Hz(%)	损耗角正切 +85°C 120Hz(%)	损耗角正切 +125°C 120Hz(%)	ESR
33	CA35-63V33uF(*)C	T3500C336(*)063(**)	(*)	63V33uF	C	1.7	12.5	12.5	8	8	8	85
47	CA35-63V47uF(*)D	T3500D476(*)063(**)	(*)	63V47uF	D	2.4	17.8	17.8	10	10	10	70
68	CA35-63V68uF(*)E	T3500E686(*)063(**)	(*)	63V68uF	E	3.4	25.7	25.7	10	10	10	55
100	CA35-63V100uF(*)F	T3500F107(*)063(**)	(*)	63V100uF	F	5.0	37.8	37.8	12	12	12	50
150	CA35-63V150uF(*)F	T3500F157(*)063(**)	(*)	63V150uF	F	7.6	56.7	56.7	15	15	15	40
<b>100 Volt 额定电压 +85°C时 ( 63 Volt 额定电压 +125°C时 )</b>												
1.5	CA35-100V1.5uF(*)A	T3500A155(*)100(**)	(*)	100V1.5uF	A	1	6	6	5	5	5	1400
2.2	CA35-100V2.2uF(*)A	T3500A225(*)100(**)	(*)	100V2.2uF	A	1	6	6	5	5	5	1100
3.3	CA35-100V3.3uF(*)A	T3500A335(*)100(**)	(*)	100V3.3uF	A	1	6	6	6	6	6	700
4.7	CA35-100V4.7uF(*)A	T3500A475(*)100(**)	(*)	100V4.7uF	A	1	6	6	6	6	6	500
6.8	CA35-100V6.8uF(*)B	T3500B685(*)100(**)	(*)	100V6.8uF	B	1	6	6	8	8	8	350
10	CA35-100V10uF(*)B	T3500B106(*)100(**)	(*)	100V10uF	B	1	6.0	6.0	10	10	10	260
15	CA35-100V15uF(*)C	T3500C156(*)100(**)	(*)	100V15uF	C	1.2	9.0	9.0	10	10	10	160
22	CA35-100V22uF(*)C	T3500C226(*)100(**)	(*)	100V22uF	C	1.8	13.2	13.2	10	10	10	110
33	CA35-100V33uF(*)D	T3500D336(*)100(**)	(*)	100V33uF	D	2.6	19.8	19.8	12	12	12	100
47	CA35-100V47uF(*)E	T3500E476(*)100(**)	(*)	100V47uF	E	3.8	28.2	28.2	12	12	12	65
68	CA35-100V68uF(*)F	T3500F686(*)100(**)	(*)	100V68uF	F	5.4	40.8	40.8	12	12	12	50
100	CA35-100V100uF(*)F	T3500F107(*)100(**)	(*)	100V100uF	F	8.0	60.0	60.0	12	12	12	40
<b>125 Volt 额定电压 +85°C时 ( 75 Volt 额定电压 +125°C时 )</b>												
1	CA35-125V1uF(*)A	T3500A105(*)125(**)	(*)	125V1uF	A	1	6	6	6	6	6	1800
1.5	CA35-125V1.5uF(*)A	T3500A155(*)125(**)	(*)	125V1.5uF	A	1	6	6	6	6	6	1400
2.2	CA35-125V2.2uF(*)A	T3500A225(*)125(**)	(*)	125V2.2uF	A	1	6	6	6	6	6	1100
3.3	CA35-125V3.3uF(*)A	T3500A335(*)125(**)	(*)	125V3.3uF	A	1	6	6	6	6	6	700
4.7	CA35-125V4.7uF(*)B	T3500B475(*)125(**)	(*)	125V4.7uF	B	1	6	6	6	6	6	500
6.8	CA35-125V6.8uF(*)B	T3500B685(*)125(**)	(*)	125V6.8uF	B	1	6	6	8	8	8	350
10	CA35-125V10uF(*)C	T3500C106(*)125(**)	(*)	125V10uF	C	1.0	7.5	7.5	9	9	9	260
15	CA35-125V15uF(*)C	T3500C156(*)125(**)	(*)	125V15uF	C	1.5	11.3	11.3	9	9	9	160
22	CA35-125V22uF(*)D	T3500D226(*)125(**)	(*)	125V22uF	D	2.2	16.5	16.5	9	9	9	130
33	CA35-125V33uF(*)E	T3500E336(*)125(**)	(*)	125V33uF	E	3.3	24.8	24.8	10	10	10	100
47	CA35-125V47uF(*)F	T3500F476(*)125(**)	(*)	125V47uF	F	4.7	35.3	35.3	10	10	10	70
68	CA35-125V68uF(*)F	T3500F686(*)125(**)	(*)	125V68uF	F	6.8	51.0	51.0	10	10	10	50

(\*)：电容量允许偏差：±10%，±20%

如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。