



CA35T 系列

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	漏电流 +125℃(uA)	损耗角正切 -55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
160 Volt 额定电压 +85℃时 (100 Volt 额定电压 +125℃时)												
0.47	CA35T-160V0.47uF(*)A	T350TA474(*)160(**)	(*)	160V0.47uF	A	1	8	8	40	6	6	6
0.68	CA35T-160V0.68uF(*)A	T350TA684(*)160(**)	(*)	160V0.68uF	A	1	8	8	40	6	6	6
1	CA35T-160V1uF(*)A	T350TA105(*)160(**)	(*)	160V1uF	A	1	8	8	40	7	7	7
1.5	CA35T-160V1.5uF(*)B	T350TB155(*)160(**)	(*)	160V1.5uF	B	1	8	8	40	8	8	8
2.2	CA35T-160V2.2uF(*)B	T350TB225(*)160(**)	(*)	160V2.2uF	B	1	8	8	40	8	8	8
3.3	CA35T-160V3.3uF(*)C	T350TC335(*)160(**)	(*)	160V3.3uF	C	1	8	8	72	10	10	10
4.7	CA35T-160V4.7uF(*)C	T350TC475(*)160(**)	(*)	160V4.7uF	C	1	8	8	84	10	10	10
6.8	CA35T-160V6.8uF(*)D	T350TD685(*)160(**)	(*)	160V6.8uF	D	1.1	8.7	8.7	84	10	10	10
10	CA35T-160V10uF(*)D	T350TD106(*)160(**)	(*)	160V10uF	D	1.6	12.8	12.8	120	12	12	12
15	CA35T-160V15uF(*)E	T350TE156(*)160(**)	(*)	160V15uF	E	2.4	19.2	19.2	120	12	12	12
22	CA35T-160V22uF(*)F	T350TF226(*)160(**)	(*)	160V22uF	F	3.5	28.2	28.2	140	15	15	15
33	CA35T-160V33uF(*)G	T350TG336(*)160(**)	(*)	160V33uF	G	5.3	42.2	42.2	160	15	15	15
47	CA35T-160V47uF(*)H	T350TH476(*)160(**)	(*)	160V47uF	H	7.5	60.2	60.2	180	15	15	15

(*)：电容量允许偏差：±10%，±20%
如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。