



CA71B-D6 系列

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +125℃(uA)	损耗角正切 - 55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
63 Volt 额定电压 +85℃时 (63 Volt 额定电压 +200℃时)											
0.68	CA71-D6-63V0.68uF(*)B	T71B6B684(*)063(**)	(*)	63V0.68uF	B	4.28	42.84	110	12	12	12
1	CA71-D6-63V1uF(*)B	T71B6B105(*)063(**)	(*)	63V1uF	B	6.30	63.00	110	12	12	12
1.5	CA71-D6-63V1.5uF(*)B	T71B6B155(*)063(**)	(*)	63V1.5uF	B	9.45	94.50	110	12	12	12
2.2	CA71-D6-63V2.2uF(*)C	T71B6C225(*)063(**)	(*)	63V2.2uF	C	13.86	138.60	110	12	12	12
3.3	CA71-D6-63V3.3uF(*)C	T71B6C335(*)063(**)	(*)	63V3.3uF	C	20.79	207.90	110	12	12	12
4.7	CA71-D6-63V4.7uF(*)D	T71B6D475(*)063(**)	(*)	63V4.7uF	D	29.61	296.10	110	12	12	12
6.8	CA71-D6-63V6.8uF(*)D	T71B6D685(*)063(**)	(*)	63V6.8uF	D	42.84	428.40	110	12	12	12
10	CA71-D6-63V10uF(*)E	T71B6E106(*)063(**)	(*)	63V10uF	E	63.00	630.00	110	12	12	12
100 Volt 额定电压 +85℃时 (100 Volt 额定电压 +200℃时)											
0.47	CA71-D6-100V0.47uF(*)B	T71B6B474(*)100(**)	(*)	100V0.47uF	B	4.70	47.00	110	12	12	12
0.68	CA71-D6-100V0.68uF(*)B	T71B6B684(*)100(**)	(*)	100V0.68uF	B	6.80	68.00	110	12	12	12
1	CA71-D6-100V1uF(*)B	T71B6B105(*)100(**)	(*)	100V1uF	B	10.00	100.00	110	12	12	12
1.5	CA71-D6-100V1.5uF(*)C	T71B6C155(*)100(**)	(*)	100V1.5uF	C	15.00	150.00	110	12	12	12
2.2	CA71-D6-100V2.2uF(*)C	T71B6C225(*)100(**)	(*)	100V2.2uF	C	22.00	220.00	110	12	12	12
3.3	CA71-D6-100V3.3uF(*)D	T71B6D335(*)100(**)	(*)	100V3.3uF	D	33.00	330.00	110	12	12	12
4.7	CA71-D6-100V4.7uF(*)D	T71B6D475(*)100(**)	(*)	100V4.7uF	D	47.00	470.00	110	12	12	12
6.8	CA71-D6-100V6.8uF(*)E	T71B6E685(*)100(**)	(*)	100V6.8uF	E	68.00	680.00	110	12	12	12
160 Volt 额定电压 +85℃时 (160 Volt 额定电压 +200℃时)											
0.33	CA71-D6-160V0.33uF(*)B	T71B6B334(*)160(**)	(*)	160V0.33uF	B	5.28	52.80	110	12	12	12
0.47	CA71-D6-160V0.47uF(*)B	T71B6B474(*)160(**)	(*)	160V0.47uF	B	7.52	75.20	110	12	12	12
0.68	CA71-D6-160V0.68uF(*)B	T71B6B684(*)160(**)	(*)	160V0.68uF	B	10.88	108.80	110	12	12	12
1	CA71-D6-160V1uF(*)C	T71B6C105(*)160(**)	(*)	160V1uF	C	16.00	160.00	110	12	12	12
1.5	CA71-D6-160V1.5uF(*)C	T71B6C155(*)160(**)	(*)	160V1.5uF	C	24.00	240.00	110	12	12	12
2.2	CA71-D6-160V2.2uF(*)D	T71B6D225(*)160(**)	(*)	160V2.2uF	D	35.20	352.00	110	12	12	12
3.3	CA71-D6-160V3.3uF(*)D	T71B6D335(*)160(**)	(*)	160V3.3uF	D	52.80	528.00	110	12	12	12
4.7	CA71-D6-160V4.7uF(*)E	T71B6E475(*)160(**)	(*)	160V4.7uF	E	75.20	752.00	110	12	12	12
250 Volt 额定电压 +85℃时 (250 Volt 额定电压 +200℃时)											
0.22	CA71-D6-250V0.22uF(*)B	T71B6B224(*)250(**)	(*)	250V0.22uF	B	5.50	55.00	110	12	12	12
0.33	CA71-D6-250V0.33uF(*)B	T71B6B334(*)250(**)	(*)	250V0.33uF	B	8.25	82.50	110	12	12	12
0.47	CA71-D6-250V0.47uF(*)B	T71B6B474(*)250(**)	(*)	250V0.47uF	B	11.75	117.50	110	12	12	12
0.68	CA71-D6-250V0.68uF(*)C	T71B6C684(*)250(**)	(*)	250V0.68uF	C	17.00	170.00	110	12	12	12
1	CA71-D6-250V1uF(*)C	T71B6C105(*)250(**)	(*)	250V1uF	C	25.00	250.00	110	12	12	12
1.5	CA71-D6-250V1.5uF(*)D	T71B6D155(*)250(**)	(*)	250V1.5uF	D	37.50	375.00	110	12	12	12
2.2	CA71-D6-250V2.2uF(*)D	T71B6D225(*)250(**)	(*)	250V2.2uF	D	55.00	550.00	110	12	12	12
3.3	CA71-D6-250V3.3uF(*)E	T71B6E335(*)250(**)	(*)	250V3.3uF	E	82.50	825.00	110	12	12	12

(*)：电容量允许偏差：±10%，±20%

如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。