

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25°C(uA)	漏电流 +85°C(uA)	漏电流 +125°C(uA)	损耗角正切 +25°C 120Hz(%)	损耗角正切 +85°C 120Hz(%)	损耗角正切 +125°C 120Hz(%)	ESR AT -55°C100Hz
6.3 Volt 额定电压 +85°C时 (4 Volt 额定电压 +125°C时)												
220	CA81-6V220uF(*)A	T8100A227(*)006(**)	(*)	6V220uF	A	50	50	50	2	9	9	36
820	CA81-6V820uF(*)B	T8100B827(*)006(**)	(*)	6V820uF	B	124	124	124	3	14	14	18
1500	CA81-6V1500uF(*)C	T8100C158(*)006(**)	(*)	6V1500uF	C	131	131	131	5	20	20	18
2200	CA81-6V2200uF(*)D	T8100D228(*)006(**)	(*)	6V2200uF	D	130	130	130	6	24	24	13
8 Volt 额定电压 +85°C时 (5 Volt 额定电压 +125°C时)												
180	CA81-8V180uF(*)A	T8100A187(*)008(**)	(*)	8V180uF	A	41	41	41	2	9	9	45
680	CA81-8V680uF(*)B	T8100B687(*)008(**)	(*)	8V680uF	B	104	104	104	3	14	14	22
1500	CA81-8V1500uF(*)C	T8100C158(*)008(**)	(*)	8V1500uF	C	130	130	130	5	20	20	18
1800	CA81-8V1800uF(*)D	T8100D188(*)008(**)	(*)	8V1800uF	D	104	104	104	7	25	25	14
10 Volt 额定电压 +85°C时 (7 Volt 额定电压 +125°C时)												
150	CA81-10V150uF(*)A	T8100A157(*)010(**)	(*)	10V150uF	A	34	34	34	2	9	9	54
560	CA81-10V560uF(*)B	T8100B567(*)010(**)	(*)	10V560uF	B	84	84	84	3	16	16	27
1200	CA81-10V1200uF(*)C	T8100C128(*)010(**)	(*)	10V1200uF	C	104	104	104	5	20	20	18
1500	CA81-10V1500uF(*)D	T8100D158(*)010(**)	(*)	10V1500uF	D	91	91	91	7	25	25	15
15 Volt 额定电压 +85°C时 (10 Volt 额定电压 +125°C时)												
100	CA81-15V100uF(*)A	T8100A107(*)015(**)	(*)	15V100uF	A	30	30	30	2	9	9	72
390	CA81-15V390uF(*)B	T8100B397(*)015(**)	(*)	15V390uF	B	74	74	74	3	16	16	31
820	CA81-15V820uF(*)C	T8100C827(*)015(**)	(*)	15V820uF	C	90	90	90	6	24	24	22
1000	CA81-15V1000uF(*)D	T8100D19(*)015(**)	(*)	15V1000uF	D	80	80	80	8	32	32	17
25 Volt 额定电压 +85°C时 (15 Volt 额定电压 +125°C时)												
68	CA81-25V68uF(*)A	T8100A686(*)025(**)	(*)	25V68uF	A	22	22	22	2	9	9	90
270	CA81-25V270uF(*)B	T8100B277(*)025(**)	(*)	25V270uF	B	55	55	55	3	16	16	33
560	CA81-25V560uF(*)C	T8100C567(*)025(**)	(*)	25V560uF	C	76	76	76	7	28	28	24
680	CA81-25V680uF(*)D	T8100D687(*)025(**)	(*)	25V680uF	D	63	63	63	8	32	32	19
30 Volt 额定电压 +85°C时 (20 Volt 额定电压 +125°C时)												
56	CA81-30V56uF(*)A	T8100A566(*)030(**)	(*)	30V56uF	A	22	22	22	2	9	9	100
220	CA81-30V220uF(*)B	T8100B227(*)030(**)	(*)	30V220uF	B	42	42	42	3	16	16	36
470	CA81-30V470uF(*)C	T8100C477(*)030(**)	(*)	30V470uF	C	64	64	64	8	32	32	25
560	CA81-30V560uF(*)D	T8100D567(*)030(**)	(*)	30V560uF	D	55	55	55	9	36	36	20
50 Volt 额定电压 +85°C时 (30 Volt 额定电压 +125°C时)												
33	CA81-50V33uF(*)A	T8100A336(*)050(**)	(*)	50V33uF	A	12.3	12.3	12.3	2	9	9	135
120	CA81-50V120uF(*)B	T8100B127(*)050(**)	(*)	50V120uF	B	22.5	22.5	22.5	4	24	24	49
270	CA81-50V270uF(*)C	T8100C277(*)050(**)	(*)	50V270uF	C	37	37	37	8	32	32	29
330	CA81-50V330uF(*)D	T8100D337(*)050(**)	(*)	50V330uF	D	38	38	38	9	36	36	22
60 Volt 额定电压 +85°C时 (40 Volt 额定电压 +125°C时)												
27	CA81-60V27uF(*)A	T8100A276(*)060(**)	(*)	60V27uF	A	10.2	10.2	10.2	3	12	12	144
100	CA81-60V100uF(*)B	T8100B107(*)060(**)	(*)	60V100uF	B	19	19	19	4	20	20	54
220	CA81-60V220uF(*)C	T8100C227(*)060(**)	(*)	60V220uF	C	30	30	30	8	32	32	29
270	CA81-60V270uF(*)D	T8100D277(*)060(**)	(*)	60V270uF	D	27	27	27	9	36	36	23
75 Volt 额定电压 +85°C时 (50 Volt 额定电压 +125°C时)												
22	CA81-75V22uF(*)A	T8100A226(*)075(**)	(*)	75V22uF	A	6.5	6.5	6.5	3	12	12	157
82	CA81-75V82uF(*)B	T8100B826(*)075(**)	(*)	75V82uF	B	15.2	15.2	15.2	4	24	24	63
180	CA81-75V180uF(*)C	T8100C187(*)075(**)	(*)	75V180uF	C	24.4	24.4	24.4	9	36	36	30
220	CA81-75V220uF(*)D	T8100D227(*)075(**)	(*)	75V220uF	D	37	37	37	10	40	40	24
100 Volt 额定电压 +85°C时 (65 Volt 额定电压 +125°C时)												
10	CA81-100V10uF(*)A	T8100A106(*)100(**)	(*)	100V10uF	A	4.5	4.5	4.5	3	12	12	200
39	CA81-100V39uF(*)B	T8100B396(*)100(**)	(*)	100V39uF	B	10.4	10.4	10.4	5	24	24	80
68	CA81-100V68uF(*)C	T8100C686(*)100(**)	(*)	100V68uF	C	11.3	11.3	11.3	10	40	40	40
120	CA81-100V120uF(*)D	T8100D127(*)100(**)	(*)	100V120uF	D	25	25	25	12	48	48	30
125 Volt 额定电压 +85°C时 (85 Volt 额定电压 +125°C时)												
6.8	CA81-125V6.8uF(*)A	T8100A685(*)125(**)	(*)	125V6.8uF	A	6	6	6	3	12	12	300
27	CA81-125V27uF(*)B	T8100B276(*)125(**)	(*)	125V27uF	B	7.2	7.2	7.2	5	24	24	90
47	CA81-125V47uF(*)C	T8100C476(*)125(**)	(*)	125V47uF	C	7.9	7.9	7.9	10	40	40	50
82	CA81-125V82uF(*)D	T8100D826(*)125(**)	(*)	125V82uF	D	17.4	17.4	17.4	12	48	48	32

(*)：电容量允许偏差：±10%，±20%

如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。