

容量	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	漏电流 +125℃ (uA)	损耗角正切 55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)	ESR AT -55℃ 100Hz
10 Volt Rating at +85℃ (6.3 Volt Rating at +125℃)													
33	CA82-10V33uF(*)A	T8200A336(*)010(**)	(*)	10V33uF	A	1.00	6.00	8.00		15	15	15	125
47	CA82-10V47uF(*)A	T8200A476(*)010(**)	(*)	10V47uF	A	1.00	6.00	9.40		15	15	15	100
68	CA82-10V68uF(*)B	T8200B686(*)010(**)	(*)	10V68uF	B	1.00	6.00	13.60		30	30	30	80
100	CA82-10V100uF(*)B	T8200B107(*)010(**)	(*)	10V100uF	B	1.00	6.00	20.00		20	20	20	60
150	CA82-10V150uF(*)C	T8200C157(*)010(**)	(*)	10V150uF	C	1.20	9.00	30.00		50	50	50	55
220	CA82-10V220uF(*)C	T8200C227(*)010(**)	(*)	10V220uF	C	1.76	13.20	44.00		45	45	45	45
330	CA82-10V330uF(*)D	T8200D337(*)010(**)	(*)	10V330uF	D	2.64	19.80	66.00		70	70	70	40
470	CA82-10V470uF(*)E	T8200E477(*)010(**)	(*)	10V470uF	E	3.76	28.20	94.00		75	75	75	35
680	CA82-10V680uF(*)F	T8200F687(*)010(**)	(*)	10V680uF	F	5.44	40.80	136.00		65	65	65	30
16 Volt Rating at +85℃ (10 Volt Rating at +125℃)													
22	CA82-16V22uF(*)A	T8200A226(*)016(**)	(*)	16V22uF	A	1.00	6.00	8.00		10	10	10	150
33	CA82-16V33uF(*)A	T8200A336(*)016(**)	(*)	16V33uF	A	1.00	6.00	10.56		12	12	12	130
47	CA82-16V47uF(*)B	T8200B476(*)016(**)	(*)	16V47uF	B	1.00	6.00	15.04		20	20	20	100
68	CA82-16V68uF(*)B	T8200B686(*)016(**)	(*)	16V68uF	B	1.00	6.53	21.76		20	20	20	80
100	CA82-16V100uF(*)C	T8200C107(*)016(**)	(*)	16V100uF	C	1.28	9.60	32.00		35	35	35	70
150	CA82-16V150uF(*)C	T8200C157(*)016(**)	(*)	16V150uF	C	1.92	14.40	48.00		35	35	35	60
220	CA82-16V220uF(*)D	T8200D227(*)016(**)	(*)	16V220uF	D	2.82	21.12	70.40		60	60	60	55
330	CA82-16V330uF(*)E	T8200E337(*)016(**)	(*)	16V330uF	E	4.22	31.68	105.60		70	70	70	45
470	CA82-16V470uF(*)F	T8200F477(*)016(**)	(*)	16V470uF	F	6.02	45.12	150.40		50	50	50	40
25 Volt Rating at +85℃ (16 Volt Rating at +125℃)													
15	CA82-25V15uF(*)A	T8200A156(*)025(**)	(*)	25V15uF	A	1.00	6.00	8.00		10	10	10	175
22	CA82-25V22uF(*)A	T8200A226(*)025(**)	(*)	25V22uF	A	1.00	6.00	11.00		10	10	10	150
33	CA82-25V33uF(*)B	T8200B336(*)025(**)	(*)	25V33uF	B	1.00	6.00	16.50		20	20	20	110
47	CA82-25V47uF(*)B	T8200B476(*)025(**)	(*)	25V47uF	B	1.00	7.05	23.50		15	15	15	80
68	CA82-25V68uF(*)C	T8200C686(*)025(**)	(*)	25V68uF	C	1.36	10.20	34.00		25	25	25	75
100	CA82-25V100uF(*)C	T8200C107(*)025(**)	(*)	25V100uF	C	2.00	15.00	50.00		25	25	25	70
150	CA82-25V150uF(*)D	T8200D157(*)025(**)	(*)	25V150uF	D	3.00	22.50	75.00		50	50	50	60
220	CA82-25V220uF(*)E	T8200E227(*)025(**)	(*)	25V220uF	E	4.40	33.00	110.00		50	50	50	55
330	CA82-25V330uF(*)F	T8200F337(*)025(**)	(*)	25V330uF	F	6.60	49.50	165.00		40	40	40	45
40 Volt Rating at +85℃ (25 Volt Rating at +125℃)													
10	CA82-40V10uF(*)A	T8200A106(*)040(**)	(*)	40V10uF	A	1.00	6.00	8.00		8	8	8	350
15	CA82-40V15uF(*)A	T8200A156(*)040(**)	(*)	40V15uF	A	1.00	6.00	12.00		10	10	10	210
22	CA82-40V22uF(*)B	T8200B226(*)040(**)	(*)	40V22uF	B	1.00	6.00	17.60		20	20	20	140
33	CA82-40V33uF(*)B	T8200B336(*)040(**)	(*)	40V33uF	B	1.06	7.92	26.40		20	20	20	110
47	CA82-40V47uF(*)C	T8200C476(*)040(**)	(*)	40V47uF	C	1.50	11.28	37.60		20	20	20	100
68	CA82-40V68uF(*)C	T8200C686(*)040(**)	(*)	40V68uF	C	2.18	16.32	54.40		20	20	20	75
100	CA82-40V100uF(*)D	T8200D106(*)040(**)	(*)	40V100uF	D	3.20	24.00	80.00		35	35	35	65
150	CA82-40V150uF(*)E	T8200E157(*)040(**)	(*)	40V150uF	E	4.80	36.00	120.00		35	35	35	50
220	CA82-40V220uF(*)F	T8200F227(*)040(**)	(*)	40V220uF	F	7.04	52.80	176.00		30	30	30	45
63 Volt Rating at +85℃ (40 Volt Rating at +125℃)													
4.7	CA82-63V4.7uF(*)A	T8200A475(*)063(**)	(*)	63V4.7uF	A	1.00	6.00	8.00		6	6	6	500
6.8	CA82-63V6.8uF(*)A	T8200A685(*)063(**)	(*)	63V6.8uF	A	1.00	6.00	8.57		8	8	8	350
10	CA82-63V10uF(*)B	T8200B106(*)063(**)	(*)	63V10uF	B	1.00	6.00	12.60		8	8	8	260
15	CA82-63V15uF(*)B	T8200B156(*)063(**)	(*)	63V15uF	B	1.00	6.00	18.90		10	10	10	175
22	CA82-63V22uF(*)C	T8200C226(*)063(**)	(*)	63V22uF	C	1.11	8.32	27.72		18	18	18	140
33	CA82-63V33uF(*)C	T8200C336(*)063(**)	(*)	63V33uF	C	1.66	12.47	41.58		18	18	18	100
47	CA82-63V47uF(*)D	T8200D476(*)063(**)	(*)	63V47uF	D	2.37	17.77	59.22		25	25	25	80
68	CA82-63V68uF(*)E	T8200E686(*)063(**)	(*)	63V68uF	E	3.43	25.70	85.68		25	25	25	65
100	CA82-63V100uF(*)F	T8200F107(*)063(**)	(*)	63V100uF	F	5.04	37.80	126.00		25	25	25	60
100 Volt Rating at +85℃ (63 Volt Rating at +125℃)													
3.3	CA82-100V3.3uF(*)A	T8200A335(*)100(**)	(*)	100V3.3uF	A	1.00	6.00	8.00		6	6	6	700
4.7	CA82-100V4.7uF(*)A	T8200A475(*)100(**)	(*)	100V4.7uF	A	1.00	6.00	9.40		6	6	6	500
6.8	CA82-100V6.8uF(*)B	T8200B685(*)100(**)	(*)	100V6.8uF	B	1.00	6.00	13.60		8	8	8	410
10	CA82-100V10uF(*)B	T8200B106(*)100(**)	(*)	100V10uF	B	1.00	6.00	20.00		10	10	10	260
15	CA82-100V15uF(*)C	T8200C156(*)100(**)	(*)	100V15uF	C	1.20	9.00	30.00		15	15	15	175
22	CA82-100V22uF(*)C	T8200C226(*)100(**)	(*)	100V22uF	C	1.76	13.20	44.00		15	15	15	150
33	CA82-100V33uF(*)D	T8200D336(*)100(**)	(*)	100V33uF	D	2.64	19.80	66.00		20	20	20	100
47	CA82-100V47uF(*)E	T8200E476(*)100(**)	(*)	100V47uF	E	3.76	28.20	94.00		25	25	25	70
68	CA82-100V68uF(*)F	T8200F686(*)100(**)	(*)	100V68uF	F	5.44	40.80	136.00		20	20	20	65
125 Volt Rating at +85℃ (75 Volt Rating at +125℃)													
2.2	CA82-125V2.2uF(*)A	T8200A225(*)125(**)	(*)	125V2.2uF	A	1.00	6.00	8.00		6	6	6	1100
3.3	CA82-125V3.3uF(*)A	T8200A335(*)125(**)	(*)	125V3.3uF	A	1.00	6.00	8.25		6	6	6	700
4.7	CA82-125V4.7uF(*)B	T8200B475(*)125(**)	(*)	125V4.7uF	B	1.00	6.00	11.75		6	6	6	500
6.8	CA82-125V6.8uF(*)B	T8200B685(*)125(**)	(*)	125V6.8uF	B	1.00	6.00	17.00		8	8	8	350
10	CA82-125V10uF(*)C	T8200C106(*)125(**)	(*)	125V10uF	C	1.00	7.50	25.00		15	15	15	260
15	CA82-125V15uF(*)C	T8200C156(*)125(**)	(*)	125V15uF	C	1.50	11.25	37.50		15	15	15	175
22	CA82-125V22uF(*)D	T8200D226(*)125(**)	(*)	125V22uF	D	2.20	16.50	55.00		20	20	20	150
33	CA82-125V33uF(*)E	T8200E336(*)125(**)	(*)	125V33uF	E	3.30	24.75	82.50		20	20	20	120
47	CA82-125V47uF(*)F	T8200F476(*)125(**)	(*)	125V47uF	F	4.70	35.25	117.50		20	20	20	90