

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流+25 ℃(uA)	漏电流+85 ℃(uA)	漏电流 +125℃ (uA)	损耗角正 切 -55℃ 120Hz(%)	损耗角正 切 +25℃ 120Hz(%)	损耗角正 切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
6.3 Volt 额定电压 +85℃时 (4 Volt 额定电压 +125℃时)												
0.47	CA70-6.3V0.47uF(*)A	T7000A474(*)006(**)	(*)	6.3V0.47uF	A	1	8.0	10.0	3	3	3	3
0.68	CA70-6.3V0.68uF(*)A	T7000A684(*)006(**)	(*)	6.3V0.68uF	A	1	8.0	10.0	5	5	5	5
1	CA70-6.3V1uF(*)A	T7000A105(*)006(**)	(*)	6.3V1uF	A	1	8.0	10.0	5	5	5	5
1.5	CA70-6.3V1.5uF(*)A	T7000A155(*)006(**)	(*)	6.3V1.5uF	A	1	8.0	10.0	5	5	5	5
2.2	CA70-6.3V2.2uF(*)A	T7000A225(*)006(**)	(*)	6.3V2.2uF	A	1	8.0	10.0	5	5	5	5
3.3	CA70-6.3V3.3uF(*)A	T7000A335(*)006(**)	(*)	6.3V3.3uF	A	1	8.0	10.0	5	5	5	5
4.7	CA70-6.3V4.7uF(*)A	T7000A475(*)006(**)	(*)	6.3V4.7uF	A	1	8.0	10.0	5	5	5	5
6.8	CA70-6.3V6.8uF(*)B	T7000B685(*)006(**)	(*)	6.3V6.8uF	B	1	8.0	10.0	5	5	5	5
10	CA70-6.3V10uF(*)B	T7000B106(*)006(**)	(*)	6.3V10uF	B	1.3	10.1	12.6	5	5	5	5
15	CA70-6.3V15uF(*)B	T7000B156(*)006(**)	(*)	6.3V15uF	B	1.9	15.1	18.9	5	5	5	5
22	CA70-6.3V22uF(*)B	T7000B226(*)006(**)	(*)	6.3V22uF	B	2.8	22.2	27.7	5	5	5	5
33	CA70-6.3V33uF(*)B	T7000B336(*)006(**)	(*)	6.3V33uF	B	4.2	33.3	41.6	5	5	5	5
47	CA70-6.3V47uF(*)C	T7000C476(*)006(**)	(*)	6.3V47uF	C	5.9	47.4	59.2	6	6	6	6
68	CA70-6.3V68uF(*)D	T7000D686(*)006(**)	(*)	6.3V68uF	D	8.6	68.5	85.7	6	6	6	6
100	CA70-6.3V100uF(*)D	T7000D107(*)006(**)	(*)	6.3V100uF	D	12.6	100.8	126.0	6	6	6	6
150	CA70-6.3V150uF(*)E	T7000E157(*)006(**)	(*)	6.3V150uF	E	18.9	151.2	189.0	6	6	6	6
220	CA70-6.3V220uF(*)E	T7000E227(*)006(**)	(*)	6.3V220uF	E	27.7	221.8	277.2	8	8	8	8
330	CA70-6.3V330uF(*)F	T7000F337(*)006(**)	(*)	6.3V330uF	F	41.6	332.6	415.8	8	8	8	8
470	CA70-6.3V470uF(*)F	T7000F477(*)006(**)	(*)	6.3V470uF	F	59.2	473.8	592.2	8	8	8	8
10 Volt 额定电压 +85℃时 (6.3 Volt 额定电压 +125℃时)												
0.33	CA70-10V0.33uF(*)A	T7000A334(*)010(**)	(*)	10V0.33uF	A	1	8.0	10.0	3	3	3	3
0.47	CA70-10V0.47uF(*)A	T7000A474(*)010(**)	(*)	10V0.47uF	A	1	8.0	10.0	3	3	3	3
0.68	CA70-10V0.68uF(*)A	T7000A684(*)010(**)	(*)	10V0.68uF	A	1	8.0	10.0	5	5	5	5
1	CA70-10V1uF(*)A	T7000A105(*)010(**)	(*)	10V1uF	A	1	8.0	10.0	5	5	5	5
1.5	CA70-10V1.5uF(*)A	T7000A155(*)010(**)	(*)	10V1.5uF	A	1	8.0	10.0	5	5	5	5
2.2	CA70-10V2.2uF(*)A	T7000A225(*)010(**)	(*)	10V2.2uF	A	1	8.0	10.0	5	5	5	5
3.3	CA70-10V3.3uF(*)A	T7000A335(*)010(**)	(*)	10V3.3uF	A	1	8.0	10.0	5	5	5	5
4.7	CA70-10V4.7uF(*)B	T7000B475(*)010(**)	(*)	10V4.7uF	B	1	8.0	10.0	5	5	5	5
6.8	CA70-10V6.8uF(*)B	T7000B685(*)010(**)	(*)	10V6.8uF	B	1.4	10.9	13.6	5	5	5	5
10	CA70-10V10uF(*)B	T7000B106(*)010(**)	(*)	10V10uF	B	2.0	16.0	20.0	5	5	5	5
15	CA70-10V15uF(*)B	T7000B156(*)010(**)	(*)	10V15uF	B	3.0	24.0	30.0	5	5	5	5
22	CA70-10V22uF(*)B	T7000B226(*)010(**)	(*)	10V22uF	B	4.4	35.2	44.0	5	5	5	5
33	CA70-10V33uF(*)C	T7000C336(*)010(**)	(*)	10V33uF	C	6.6	52.8	66.0	5	5	5	5
47	CA70-10V47uF(*)C	T7000C476(*)010(**)	(*)	10V47uF	C	9.4	75.2	94.0	6	6	6	6
68	CA70-10V68uF(*)D	T7000D686(*)010(**)	(*)	10V68uF	D	13.6	108.8	136.0	6	6	6	6
100	CA70-10V100uF(*)E	T7000E107(*)010(**)	(*)	10V100uF	E	20.0	160.0	200.0	6	6	6	6
150	CA70-10V150uF(*)E	T7000E157(*)010(**)	(*)	10V150uF	E	30.0	240.0	300.0	6	6	6	6
220	CA70-10V220uF(*)F	T7000F227(*)010(**)	(*)	10V220uF	F	44.0	352.0	440.0	8	8	8	8
330	CA70-10V330uF(*)F	T7000F337(*)010(**)	(*)	10V330uF	F	66.0	528.0	660.0	8	8	8	8
16 Volt 额定电压 +85℃时 (10 Volt 额定电压 +125℃时)												
0.15	CA70-16V0.15uF(*)A	T7000A154(*)016(**)	(*)	16V0.15uF	A	1	8.0	10.0	3	3	3	3
0.22	CA70-16V0.22uF(*)A	T7000A224(*)016(**)	(*)	16V0.22uF	A	1	8.0	10.0	3	3	3	3
0.33	CA70-16V0.33uF(*)A	T7000A334(*)016(**)	(*)	16V0.33uF	A	1	8.0	10.0	3	3	3	3
0.47	CA70-16V0.47uF(*)A	T7000A474(*)016(**)	(*)	16V0.47uF	A	1	8.0	10.0	3	3	3	3
0.68	CA70-16V0.68uF(*)A	T7000A684(*)016(**)	(*)	16V0.68uF	A	1	8.0	10.0	5	5	5	5
1	CA70-16V1uF(*)A	T7000A105(*)016(**)	(*)	16V1uF	A	1	8.0	10.0	5	5	5	5
1.5	CA70-16V1.5uF(*)A	T7000A155(*)016(**)	(*)	16V1.5uF	A	1	8.0	10.0	5	5	5	5
2.2	CA70-16V2.2uF(*)B	T7000B225(*)016(**)	(*)	16V2.2uF	B	1	8.0	10.0	5	5	5	5
3.3	CA70-16V3.3uF(*)B	T7000B335(*)016(**)	(*)	16V3.3uF	B	1.1	8.4	10.6	5	5	5	5
4.7	CA70-16V4.7uF(*)B	T7000B475(*)016(**)	(*)	16V4.7uF	B	1.5	12.0	15.0	5	5	5	5
6.8	CA70-16V6.8uF(*)B	T7000B685(*)016(**)	(*)	16V6.8uF	B	2.2	17.4	21.8	5	5	5	5
10	CA70-16V10uF(*)B	T7000B106(*)016(**)	(*)	16V10uF	B	3.2	25.6	32.0	5	5	5	5
15	CA70-16V15uF(*)B	T7000B156(*)016(**)	(*)	16V15uF	B	4.8	38.4	48.0	5	5	5	5
22	CA70-16V22uF(*)C	T7000C226(*)016(**)	(*)	16V22uF	C	7.0	56.3	70.4	5	5	5	5
33	CA70-16V33uF(*)C	T7000C336(*)016(**)	(*)	16V33uF	C	10.6	84.5	105.6	5	5	5	5
47	CA70-16V47uF(*)D	T7000D476(*)016(**)	(*)	16V47uF	D	15.0	120.3	150.4	6	6	6	6
68	CA70-16V68uF(*)E	T7000E686(*)016(**)	(*)	16V68uF	E	21.8	174.1	217.6	6	6	6	6
100	CA70-16V100uF(*)E	T7000E107(*)016(**)	(*)	16V100uF	E	32.0	256.0	320.0	6	6	6	6
150	CA70-16V150uF(*)F	T7000F157(*)016(**)	(*)	16V150uF	F	48.0	384.0	480.0	6	6	6	6
220	CA70-16V220uF(*)F	T7000F227(*)016(**)	(*)	16V220uF	F	70.4	563.2	704.0	8	8	8	8
25 Volt 额定电压 +85℃时 (16 Volt 额定电压 +125℃时)												

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流+25 ℃(uA)	漏电流+85 ℃(uA)	漏电流 +125℃ (uA)	损耗角正 切 -55℃ 120Hz(%)	损耗角正 切 +25℃ 120Hz(%)	损耗角正 切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
0.15	CA70-25V0.15uF(*)A	T7000A154(*)025(**)	(*)	25V0.15uF	A	1	8.0	10.0	3	3	3	3
0.22	CA70-25V0.22uF(*)A	T7000A224(*)025(**)	(*)	25V0.22uF	A	1	8.0	10.0	3	3	3	3
0.33	CA70-25V0.33uF(*)A	T7000A334(*)025(**)	(*)	25V0.33uF	A	1	8.0	10.0	3	3	3	3
0.47	CA70-25V0.47uF(*)A	T7000A474(*)025(**)	(*)	25V0.47uF	A	1	8.0	10.0	3	3	3	3
0.68	CA70-25V0.68uF(*)A	T7000A684(*)025(**)	(*)	25V0.68uF	A	1	8.0	10.0	5	5	5	5
1	CA70-25V1uF(*)A	T7000A105(*)025(**)	(*)	25V1uF	A	1	8.0	10.0	5	5	5	5
1.5	CA70-25V1.5uF(*)B	T7000B155(*)025(**)	(*)	25V1.5uF	B	1	8.0	10.0	5	5	5	5
2.2	CA70-25V2.2uF(*)B	T7000B225(*)025(**)	(*)	25V2.2uF	B	1.1	8.8	11.0	5	5	5	5
3.3	CA70-25V3.3uF(*)B	T7000B335(*)025(**)	(*)	25V3.3uF	B	1.7	13.2	16.5	5	5	5	5
4.7	CA70-25V4.7uF(*)B	T7000B475(*)025(**)	(*)	25V4.7uF	B	2.4	18.8	23.5	5	5	5	5
6.8	CA70-25V6.8uF(*)B	T7000B685(*)025(**)	(*)	25V6.8uF	B	3.4	27.2	34.0	5	5	5	5
10	CA70-25V10uF(*)C	T7000C106(*)025(**)	(*)	25V10uF	C	5.0	40.0	50.0	5	5	5	5
15	CA70-25V15uF(*)C	T7000C156(*)025(**)	(*)	25V15uF	C	7.5	60.0	75.0	5	5	5	5
22	CA70-25V22uF(*)D	T7000D226(*)025(**)	(*)	25V22uF	D	11.0	88.0	110.0	5	5	5	5
33	CA70-25V33uF(*)D	T7000D336(*)025(**)	(*)	25V33uF	D	16.5	132.0	165.0	5	5	5	5
47	CA70-25V47uF(*)E	T7000E476(*)025(**)	(*)	25V47uF	E	23.5	188.0	235.0	6	6	6	6
68	CA70-25V68uF(*)F	T7000F686(*)025(**)	(*)	25V68uF	F	34.0	272.0	340.0	6	6	6	6
100	CA70-25V100uF(*)F	T7000F107(*)025(**)	(*)	25V100uF	F	50.0	400.0	500.0	6	6	6	6
32 Volt 额定电压 +85℃时 (20 Volt 额定电压 +125℃时)												
0.1	CA70-32V0.1uF(*)A	T7000A104(*)032(**)	(*)	32V0.1uF	A	1	8.0	10.0	3	3	3	3
0.15	CA70-32V0.15uF(*)A	T7000A154(*)032(**)	(*)	32V0.15uF	A	1	8.0	10.0	3	3	3	3
0.22	CA70-32V0.22uF(*)A	T7000A224(*)032(**)	(*)	32V0.22uF	A	1	8.0	10.0	3	3	3	3
0.33	CA70-32V0.33uF(*)A	T7000A334(*)032(**)	(*)	32V0.33uF	A	1	8.0	10.0	3	3	3	3
0.47	CA70-32V0.47uF(*)A	T7000A474(*)032(**)	(*)	32V0.47uF	A	1	8.0	10.0	3	3	3	3
0.68	CA70-32V0.68uF(*)A	T7000A684(*)032(**)	(*)	32V0.68uF	A	1	8.0	10.0	5	5	5	5
1	CA70-32V1uF(*)B	T7000B105(*)032(**)	(*)	32V1uF	B	1	8.0	10.0	5	5	5	5
1.5	CA70-32V1.5uF(*)B	T7000B155(*)032(**)	(*)	32V1.5uF	B	1	8.0	10.0	5	5	5	5
2.2	CA70-32V2.2uF(*)B	T7000B225(*)032(**)	(*)	32V2.2uF	B	1.4	11.3	14.1	5	5	5	5
3.3	CA70-32V3.3uF(*)B	T7000B335(*)032(**)	(*)	32V3.3uF	B	2.1	16.9	21.1	5	5	5	5
4.7	CA70-32V4.7uF(*)B	T7000B475(*)032(**)	(*)	32V4.7uF	B	3.0	24.1	30.1	5	5	5	5
6.8	CA70-32V6.8uF(*)C	T7000C685(*)032(**)	(*)	32V6.8uF	C	4.4	34.8	43.5	5	5	5	5
10	CA70-32V10uF(*)D	T7000D106(*)032(**)	(*)	32V10uF	D	6.4	51.2	64.0	5	5	5	5
15	CA70-32V15uF(*)D	T7000D156(*)032(**)	(*)	32V15uF	D	9.6	76.8	96.0	5	5	5	5
22	CA70-32V22uF(*)E	T7000E226(*)032(**)	(*)	32V22uF	E	14.1	112.6	140.8	5	5	5	5
33	CA70-32V33uF(*)E	T7000E336(*)032(**)	(*)	32V33uF	E	21.1	169.0	211.2	5	5	5	5
47	CA70-32V47uF(*)F	T7000F476(*)032(**)	(*)	32V47uF	F	30.1	240.6	300.8	6	6	6	6
68	CA70-32V68uF(*)F	T7000F686(*)032(**)	(*)	32V68uF	F	43.5	348.2	435.2	6	6	6	6
40 Volt 额定电压 +85℃时 (25 Volt 额定电压 +125℃时)												
0.1	CA70-40V0.1uF(*)A	T7000A104(*)040(**)	(*)	40V0.1uF	A	1	8.0	10.0	3	3	3	3
0.15	CA70-40V0.15uF(*)A	T7000A154(*)040(**)	(*)	40V0.15uF	A	1	8.0	10.0	3	3	3	3
0.22	CA70-40V0.22uF(*)A	T7000A224(*)040(**)	(*)	40V0.22uF	A	1	8.0	10.0	3	3	3	3
0.33	CA70-40V0.33uF(*)A	T7000A334(*)040(**)	(*)	40V0.33uF	A	1	8.0	10.0	3	3	3	3
0.47	CA70-40V0.47uF(*)A	T7000A474(*)040(**)	(*)	40V0.47uF	A	1	8.0	10.0	3	3	3	3
0.68	CA70-40V0.68uF(*)B	T7000B684(*)040(**)	(*)	40V0.68uF	B	1	8.0	10.0	5	5	5	5
1	CA70-40V1uF(*)B	T7000B105(*)040(**)	(*)	40V1uF	B	1	8.0	10.0	5	5	5	5
1.5	CA70-40V1.5uF(*)B	T7000B155(*)040(**)	(*)	40V1.5uF	B	1.2	9.6	12.0	5	5	5	5
2.2	CA70-40V2.2uF(*)B	T7000B225(*)040(**)	(*)	40V2.2uF	B	1.8	14.1	17.6	5	5	5	5
3.3	CA70-40V3.3uF(*)B	T7000B335(*)040(**)	(*)	40V3.3uF	B	2.6	21.1	26.4	5	5	5	5
4.7	CA70-40V4.7uF(*)C	T7000C475(*)040(**)	(*)	40V4.7uF	C	3.8	30.1	37.6	5	5	5	5
6.8	CA70-40V6.8uF(*)C	T7000C685(*)040(**)	(*)	40V6.8uF	C	5.4	43.5	54.4	5	5	5	5
10	CA70-40V10uF(*)D	T7000D106(*)040(**)	(*)	40V10uF	D	8.0	64.0	80.0	5	5	5	5
15	CA70-40V15uF(*)D	T7000D156(*)040(**)	(*)	40V15uF	D	12.0	96.0	120.0	5	5	5	5
22	CA70-40V22uF(*)E	T7000E226(*)040(**)	(*)	40V22uF	E	17.6	140.8	176.0	5	5	5	5
33	CA70-40V33uF(*)F	T7000F336(*)040(**)	(*)	40V33uF	F	26.4	211.2	264.0	5	5	5	5
47	CA70-40V47uF(*)F	T7000F476(*)040(**)	(*)	40V47uF	F	37.6	300.8	376.0	6	6	6	6
63 Volt 额定电压 +85℃时 (40 Volt 额定电压 +125℃时)												
0.1	CA70-63V0.1uF(*)A	T7000A104(*)063(**)	(*)	63V0.1uF	A	1	8.0	10.0	3	3	3	3
0.15	CA70-63V0.15uF(*)A	T7000A154(*)063(**)	(*)	63V0.15uF	A	1	8.0	10.0	3	3	3	3
0.22	CA70-63V0.22uF(*)A	T7000A224(*)063(**)	(*)	63V0.22uF	A	1	8.0	10.0	3	3	3	3
0.33	CA70-63V0.33uF(*)B	T7000B334(*)063(**)	(*)	63V0.33uF	B	1	8.0	10.0	3	3	3	3
0.47	CA70-63V0.47uF(*)B	T7000B474(*)063(**)	(*)	63V0.47uF	B	1	8.0	10.0	3	3	3	3
0.68	CA70-63V0.68uF(*)B	T7000B684(*)063(**)	(*)	63V0.68uF	B	1	8.0	10.0	5	5	5	5

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流+25 ℃(uA)	漏电流+85 ℃(uA)	漏电流 +125℃ (uA)	损耗角正 切 -55℃ 120Hz(%)	损耗角正 切 +25℃ 120Hz(%)	损耗角正 切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
1	CA70-63V1uF(*)B	T7000B105(*)063(**)	(*)	63V1uF	B	1.3	10.1	12.6	5	5	5	5
1.5	CA70-63V1.5uF(*)B	T7000B155(*)063(**)	(*)	63V1.5uF	B	1.9	15.1	18.9	5	5	5	5
2.2	CA70-63V2.2uF(*)C	T7000C225(*)063(**)	(*)	63V2.2uF	C	2.8	22.2	27.7	5	5	5	5
3.3	CA70-63V3.3uF(*)D	T7000D335(*)063(**)	(*)	63V3.3uF	D	4.2	33.3	41.6	5	5	5	5
4.7	CA70-63V4.7uF(*)D	T7000D475(*)063(**)	(*)	63V4.7uF	D	5.9	47.4	59.2	5	5	5	5
6.8	CA70-63V6.8uF(*)E	T7000E685(*)063(**)	(*)	63V6.8uF	E	8.6	68.5	85.7	5	5	5	5
10	CA70-63V10uF(*)E	T7000E106(*)063(**)	(*)	63V10uF	E	12.6	100.8	126.0	5	5	5	5
15	CA70-63V15uF(*)F	T7000F156(*)063(**)	(*)	63V15uF	F	18.9	151.2	189.0	5	5	5	5
22	CA70-63V22uF(*)F	T7000F226(*)063(**)	(*)	63V22uF	F	27.7	221.8	277.2	5	5	5	5

(*): 电容量允许偏差: ±10%, ±20%

如电压、容量、电容量允许偏差等特殊要求, 请与上海聚电联系。