

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25°C (uA)	漏电流 +85°C (uA)	漏电流 +125°C (uA)	损耗角正切 -55°C 120Hz(%)	损耗角正切 +25°C 120Hz(%)	损耗角正切 +85°C 120Hz(%)	损耗角正切 +125°C 120Hz(%)
4 Volt 额定电压 +85°C时 (2.5 Volt 额定电压 +125°C时)												
4.7	CA42-4V4.7uF(*)A(**)	T4200A475(*)004(**)	(*)	4V4.7uF	A	0.5	4.0	5.0	6	6	8	8
6.8	CA42-4V6.8uF(*)A(**)	T4200A685(*)004(**)	(*)	4V6.8uF	A	0.5	4.0	5.0	6	6	8	8
10	CA42-4V10uF(*)A(**)	T4200A106(*)004(**)	(*)	4V10uF	A	0.5	4.0	5.0	8	8	10	10
15	CA42-4V15uF(*)A(**)	T4200A156(*)004(**)	(*)	4V15uF	A	0.6	4.8	6.0	8	8	10	10
22	CA42-4V22uF(*)B(**)	T4200B226(*)004(**)	(*)	4V22uF	B	0.9	7.0	8.8	8	8	10	10
33	CA42-4V33uF(*)B(**)	T4200B336(*)004(**)	(*)	4V33uF	B	1.3	10.6	13.2	8	8	10	10
47	CA42-4V47uF(*)C(**)	T4200C476(*)004(**)	(*)	4V47uF	C	1.9	15.0	18.8	8	8	10	10
68	CA42-4V68uF(*)D(**)	T4200D686(*)004(**)	(*)	4V68uF	D	2.7	21.8	27.2	8	8	10	10
100	CA42-4V100uF(*)D(**)	T4200D107(*)004(**)	(*)	4V100uF	D	4.0	32.0	40.0	10	10	12	12
150	CA42-4V150uF(*)E(**)	T4200E157(*)004(**)	(*)	4V150uF	E	6.0	48.0	60.0	10	10	12	12
220	CA42-4V220uF(*)F(**)	T4200F227(*)004(**)	(*)	4V220uF	F	8.8	70.4	88.0	10	10	12	12
330	CA42-4V330uF(*)F(**)	T4200F337(*)004(**)	(*)	4V330uF	F	13.2	105.6	132.0	10	10	12	12
6.3 Volt 额定电压 +85°C时 (4 Volt 额定电压 +125°C时)												
4.7	CA42-6.3V4.7uF(*)A(**)	T4200A475(*)006(**)	(*)	6.3V4.7uF	A	0.5	4.0	5.0	6	6	8	8
6.8	CA42-6.3V6.8uF(*)A(**)	T4200A685(*)006(**)	(*)	6.3V6.8uF	A	0.5	4.0	5.0	6	6	8	8
10	CA42-6.3V10uF(*)A(**)	T4200A106(*)006(**)	(*)	6.3V10uF	A	0.6	5.0	6.3	8	8	10	10
15	CA42-6.3V15uF(*)B(**)	T4200B156(*)006(**)	(*)	6.3V15uF	B	0.9	7.6	9.5	8	8	10	10
22	CA42-6.3V22uF(*)C(**)	T4200C226(*)006(**)	(*)	6.3V22uF	C	1.4	11.1	13.9	8	8	10	10
33	CA42-6.3V33uF(*)C(**)	T4200C336(*)006(**)	(*)	6.3V33uF	C	2.1	16.6	20.8	8	8	10	10
47	CA42-6.3V47uF(*)D(**)	T4200D476(*)006(**)	(*)	6.3V47uF	D	3.0	23.7	29.6	8	8	10	10
68	CA42-6.3V68uF(*)D(**)	T4200D686(*)006(**)	(*)	6.3V68uF	D	4.3	34.3	42.8	8	8	10	10
100	CA42-6.3V100uF(*)D(**)	T4200D107(*)006(**)	(*)	6.3V100uF	D	6.3	50.4	63.0	10	10	12	12
150	CA42-6.3V150uF(*)E(**)	T4200E157(*)006(**)	(*)	6.3V150uF	E	9.5	75.6	94.5	10	10	12	12
220	CA42-6.3V220uF(*)F(**)	T4200F227(*)006(**)	(*)	6.3V220uF	F	13.9	110.9	138.6	10	10	12	12
330	CA42-6.3V330uF(*)G(**)	T4200G337(*)006(**)	(*)	6.3V330uF	G	20.8	166.3	207.9	10	10	12	12
10 Volt 额定电压 +85°C时 (6.3 Volt 额定电压 +125°C时)												
3.3	CA42-10V3.3uF(*)A(**)	T4200A335(*)010(**)	(*)	10V3.3uF	A	0.5	4.0	5.0	6	6	8	8
4.7	CA42-10V4.7uF(*)A(**)	T4200A475(*)010(**)	(*)	10V4.7uF	A	0.5	3.8	4.7	6	6	8	8
6.8	CA42-10V6.8uF(*)B(**)	T4200B685(*)010(**)	(*)	10V6.8uF	B	0.7	5.4	6.8	6	6	8	8
10	CA42-10V10uF(*)B(**)	T4200B106(*)010(**)	(*)	10V10uF	B	1.0	8.0	10.0	8	8	10	10
15	CA42-10V15uF(*)C(**)	T4200C156(*)010(**)	(*)	10V15uF	C	1.5	12.0	15.0	8	8	10	10
22	CA42-10V22uF(*)C(**)	T4200C226(*)010(**)	(*)	10V22uF	C	2.2	17.6	22.0	8	8	10	10
33	CA42-10V33uF(*)D(**)	T4200D336(*)010(**)	(*)	10V33uF	D	3.3	26.4	33.0	8	8	10	10
47	CA42-10V47uF(*)D(**)	T4200D476(*)010(**)	(*)	10V47uF	D	4.7	37.6	47.0	8	8	10	10
68	CA42-10V68uF(*)D(**)	T4200D686(*)010(**)	(*)	10V68uF	D	6.8	54.4	68.0	8	8	10	10
100	CA42-10V100uF(*)E(**)	T4200E107(*)010(**)	(*)	10V100uF	E	10.0	80.0	100.0	10	10	12	12
150	CA42-10V150uF(*)F(**)	T4200F157(*)010(**)	(*)	10V150uF	F	15.0	120.0	150.0	10	10	12	12
220	CA42-10V220uF(*)G(**)	T4200G227(*)010(**)	(*)	10V220uF	G	22.0	176.0	220.0	10	10	12	12
16 Volt 额定电压 +85°C时 (10 Volt 额定电压 +125°C时)												
2.2	CA42-16V2.2uF(*)A(**)	T4200A225(*)016(**)	(*)	16V2.2uF	A	0.4	2.8	3.5	6	6	8	8
3.3	CA42-16V3.3uF(*)A(**)	T4200A335(*)016(**)	(*)	16V3.3uF	A	0.5	4.2	5.3	6	6	8	8
4.7	CA42-16V4.7uF(*)B(**)	T4200B475(*)016(**)	(*)	16V4.7uF	B	0.8	6.0	7.5	6	6	8	8
6.8	CA42-16V6.8uF(*)B(**)	T4200B685(*)016(**)	(*)	16V6.8uF	B	1.1	8.7	10.9	6	6	8	8
10	CA42-16V10uF(*)C(**)	T4200C106(*)016(**)	(*)	16V10uF	C	1.6	12.8	16.0	8	8	10	10
15	CA42-16V15uF(*)C(**)	T4200C156(*)016(**)	(*)	16V15uF	C	2.4	19.2	24.0	8	8	10	10
22	CA42-16V22uF(*)D(**)	T4200D226(*)016(**)	(*)	16V22uF	D	3.5	28.2	35.2	8	8	10	10
33	CA42-16V33uF(*)D(**)	T4200D336(*)016(**)	(*)	16V33uF	D	5.3	42.2	52.8	8	8	10	10
47	CA42-16V47uF(*)E(**)	T4200E476(*)016(**)	(*)	16V47uF	E	7.5	60.2	75.2	8	8	10	10
68	CA42-16V68uF(*)E(**)	T4200E686(*)016(**)	(*)	16V68uF	E	10.9	87.0	108.8	8	8	10	10
100	CA42-16V100uF(*)F(**)	T4200F107(*)016(**)	(*)	16V100uF	F	16.0	128.0	160.0	10	10	12	12
150	CA42-16V150uF(*)G(**)	T4200G157(*)016(**)	(*)	16V150uF	G	24.0	192.0	240.0	10	10	12	12
25 Volt 额定电压 +85°C时 (16 Volt 额定电压 +125°C时)												
1	CA42-25V1uF(*)A(**)	T4200A105(*)025(**)	(*)	25V1uF	A	0.5	4.0	5.0	4	4	6	6
1.5	CA42-25V1.5uF(*)A(**)	T4200A155(*)025(**)	(*)	25V1.5uF	A	0.5	4.0	5.0	6	6	8	8
2.2	CA42-25V2.2uF(*)A(**)	T4200A225(*)025(**)	(*)	25V2.2uF	A	0.6	4.4	5.5	6	6	8	8
3.3	CA42-25V3.3uF(*)B(**)	T4200B335(*)025(**)	(*)	25V3.3uF	B	0.8	6.6	8.3	6	6	8	8
4.7	CA42-25V4.7uF(*)B(**)	T4200B475(*)025(**)	(*)	25V4.7uF	B	1.2	9.4	11.8	6	6	8	8
6.8	CA42-25V6.8uF(*)C(**)	T4200C685(*)025(**)	(*)	25V6.8uF	C	1.7	13.6	17.0	6	6	8	8
10	CA42-25V10uF(*)C(**)	T4200C106(*)025(**)	(*)	25V10uF	C	2.5	20.0	25.0	8	8	10	10
15	CA42-25V15uF(*)D(**)	T4200D156(*)025(**)	(*)	25V15uF	D	3.8	30.0	37.5	8	8	10	10
22	CA42-25V22uF(*)D(**)	T4200D226(*)025(**)	(*)	25V22uF	D	5.5	44.0	55.0	8	8	10	10
33	CA42-25V33uF(*)E(**)	T4200E336(*)025(**)	(*)	25V33uF	E	8.3	66.0	82.5	8	8	10	10
47	CA42-25V47uF(*)F(**)	T4200F476(*)025(**)	(*)	25V47uF	F	11.8	94.0	117.5	8	8	10	10
68	CA42-25V68uF(*)G(**)	T4200G686(*)025(**)	(*)	25V68uF	G	17.0	136.0	170.0	8	8	10	10
35 Volt 额定电压 +85°C时 (20 Volt 额定电压 +125°C时)												
0.1	CA42-35V0.1uF(*)A(**)	T4200A104(*)035(**)	(*)	35V0.1uF	A	0.5	4.0	5.0	4	4	6	6
0.15	CA42-35V0.15uF(*)A(**)	T4200A154(*)035(**)	(*)	35V0.15uF	A	0.5	4.0	5.0	4	4	6	6
0.22	CA42-35V0.22uF(*)A(**)	T4200A224(*)035(**)	(*)	35V0.22uF	A	0.5	4.0	5.0	4	4	6	6
0.33	CA42-35V0.33uF(*)A(**)	T4200A334(*)035(**)	(*)	35V0.33uF	A	0.5	4.0	5.0	4	4	6	6
0.47	CA42-35V0.47uF(*)A(**)	T4200A474(*)035(**)	(*)	35V0.47uF	A	0.5	4.0	5.0	4	4	6	6
0.68	CA42-35V0.68uF(*)A(**)	T4200A684(*)035(**)	(*)	35V0.68uF	A	0.5	4.0	5.0	4	4	6	6
1	CA42-35V1uF(*)A(**)	T4200A105(*)035(**)	(*)	35V1uF	A	0.5	4.0	5.0	4	4	6	6
1.5	CA42-35V1.5uF(*)A(**)	T4200A155(*)035(**)	(*)	35V1.5uF	A	0.5	4.2	5.3	6	6	8	8
2.2	CA42-35V2.2uF(*)B(**)	T4200B225(*)035(**)	(*)	35V2.2uF	B	0.8	6.2	7.7	6	6	8	8

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25℃ (uA)	漏电流 +85℃ (uA)	漏电流 +125℃ (uA)	损耗角正切 -55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
3.3	CA42-35V3.3uF(*)B(**)	T4200B335(*)035(**)	(*)	35V3.3uF	B	1.2	9.2	11.6	6	6	8	8
4.7	CA42-35V4.7uF(*)C(**)	T4200C475(*)035(**)	(*)	35V4.7uF	C	1.6	13.2	16.5	6	6	8	8
6.8	CA42-35V6.8uF(*)D(**)	T4200D685(*)035(**)	(*)	35V6.8uF	D	2.4	19.0	23.8	6	6	8	8
10	CA42-35V10uF(*)D(**)	T4200D106(*)035(**)	(*)	35V10uF	D	3.5	28.0	35.0	8	8	10	10
15	CA42-35V15uF(*)E(**)	T4200E156(*)035(**)	(*)	35V15uF	E	5.3	42.0	52.5	8	8	10	10
22	CA42-35V22uF(*)F(**)	T4200F226(*)035(**)	(*)	35V22uF	F	7.7	61.6	77.0	8	8	10	10
33	CA42-35V33uF(*)G(**)	T4200G336(*)035(**)	(*)	35V33uF	G	11.6	92.4	115.5	8	8	10	10
47	CA42-35V47uF(*)G(**)	T4200G476(*)035(**)	(*)	35V47uF	G	16.5	131.6	164.5	8	8	10	10
40 Volt 额定电压 +85℃时 (25 Volt 额定电压 +125℃时)												
0.1	CA42-40V0.1uF(*)A(**)	T4200A104(*)040(**)	(*)	40V0.1uF	A	0.5	4.0	5.0	4	4	6	6
0.15	CA42-40V0.15uF(*)A(**)	T4200A154(*)040(**)	(*)	40V0.15uF	A	0.5	4.0	5.0	4	4	6	6
0.22	CA42-40V0.22uF(*)A(**)	T4200A224(*)040(**)	(*)	40V0.22uF	A	0.5	4.0	5.0	4	4	6	6
0.33	CA42-40V0.33uF(*)A(**)	T4200A334(*)040(**)	(*)	40V0.33uF	A	0.5	4.0	5.0	4	4	6	6
0.47	CA42-40V0.47uF(*)A(**)	T4200A474(*)040(**)	(*)	40V0.47uF	A	0.5	4.0	5.0	4	4	6	6
0.68	CA42-40V0.68uF(*)A(**)	T4200A684(*)040(**)	(*)	40V0.68uF	A	0.5	4.0	5.0	4	4	6	6
1	CA42-40V1.1uF(*)A(**)	T4200A105(*)040(**)	(*)	40V1.1uF	A	0.5	4.0	5.0	4	4	6	6
1.5	CA42-40V1.5uF(*)B(**)	T4200B155(*)040(**)	(*)	40V1.5uF	B	0.6	4.8	6.0	6	6	8	8
2.2	CA42-40V2.2uF(*)B(**)	T4200B225(*)040(**)	(*)	40V2.2uF	B	0.9	7.0	8.8	6	6	8	8
3.3	CA42-40V3.3uF(*)C(**)	T4200C335(*)040(**)	(*)	40V3.3uF	C	1.3	10.6	13.2	6	6	8	8
4.7	CA42-40V4.7uF(*)D(**)	T4200D475(*)040(**)	(*)	40V4.7uF	D	1.9	15.0	18.8	6	6	8	8
6.8	CA42-40V6.8uF(*)D(**)	T4200D685(*)040(**)	(*)	40V6.8uF	D	2.7	21.8	27.2	6	6	8	8
10	CA42-40V10uF(*)E(**)	T4200E106(*)040(**)	(*)	40V10uF	E	4.0	32.0	40.0	8	8	10	10
15	CA42-40V15uF(*)F(**)	T4200F156(*)040(**)	(*)	40V15uF	F	6.0	48.0	60.0	8	8	10	10
22	CA42-40V22uF(*)G(**)	T4200G226(*)040(**)	(*)	40V22uF	G	8.8	70.4	88.0	8	8	10	10
33	CA42-40V33uF(*)G(**)	T4200G336(*)040(**)	(*)	40V33uF	G	13.2	105.6	132.0	8	8	10	10
50 Volt 额定电压 +85℃时 (32 Volt 额定电压 +125℃时)												
0.1	CA42-50V0.1uF(*)A(**)	T4200A104(*)050(**)	(*)	50V0.1uF	A	0.5	4.0	5.0	4	4	6	6
0.15	CA42-50V0.15uF(*)A(**)	T4200A154(*)050(**)	(*)	50V0.15uF	A	0.5	4.0	5.0	4	4	6	6
0.22	CA42-50V0.22uF(*)A(**)	T4200A224(*)050(**)	(*)	50V0.22uF	A	0.5	4.0	5.0	4	4	6	6
0.33	CA42-50V0.33uF(*)A(**)	T4200A334(*)050(**)	(*)	50V0.33uF	A	0.5	4.0	5.0	4	4	6	6
0.47	CA42-50V0.47uF(*)A(**)	T4200A474(*)050(**)	(*)	50V0.47uF	A	0.5	4.0	5.0	4	4	6	6
0.68	CA42-50V0.68uF(*)A(**)	T4200A684(*)050(**)	(*)	50V0.68uF	A	0.5	4.0	5.0	4	4	6	6
1	CA42-50V1.1uF(*)B(**)	T4200B105(*)050(**)	(*)	50V1.1uF	B	0.5	4.0	5.0	4	4	6	6
1.5	CA42-50V1.5uF(*)C(**)	T4200C155(*)050(**)	(*)	50V1.5uF	C	0.8	6.0	7.5	6	6	8	8
2.2	CA42-50V2.2uF(*)C(**)	T4200C225(*)050(**)	(*)	50V2.2uF	C	1.1	8.8	11.0	6	6	8	8
3.3	CA42-50V3.3uF(*)D(**)	T4200D335(*)050(**)	(*)	50V3.3uF	D	1.7	13.2	16.5	6	6	8	8
4.7	CA42-50V4.7uF(*)D(**)	T4200D475(*)050(**)	(*)	50V4.7uF	D	2.4	18.8	23.5	6	6	8	8
6.8	CA42-50V6.8uF(*)E(**)	T4200E685(*)050(**)	(*)	50V6.8uF	E	3.4	27.2	34.0	6	6	8	8
10	CA42-50V10uF(*)F(**)	T4200F106(*)050(**)	(*)	50V10uF	F	5.0	40.0	50.0	8	8	10	10
15	CA42-50V15uF(*)G(**)	T4200G156(*)050(**)	(*)	50V15uF	G	7.5	60.0	75.0	8	8	10	10
22	CA42-50V22uF(*)G(**)	T4200G226(*)050(**)	(*)	50V22uF	G	11.0	88.0	110.0	8	8	10	10

(*): 电容量允许偏差: ±10%, ±20%

如电压、容量、电容量允许偏差等有特殊要求, 请与上海聚电联系。