

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	损耗角正切 -55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)
4 Volt 额定电压 +85℃时										
1.5	CA421-4V1.5uF(*)A(**)	T4210A155(*)004(**)	(*)	4V1.5uF	A	1	10.0	6	4	6
2.2	CA421-4V2.2uF(*)A(**)	T4210A225(*)004(**)	(*)	4V2.2uF	A	1	10.0	6	4	6
3.3	CA421-4V3.3uF(*)A(**)	T4210A335(*)004(**)	(*)	4V3.3uF	A	1	10.0	6	4	6
4.7	CA421-4V4.7uF(*)B(**)	T4210B475(*)004(**)	(*)	4V4.7uF	B	1	10.0	6	4	6
6.8	CA421-4V6.8uF(*)B(**)	T4210B685(*)004(**)	(*)	4V6.8uF	B	1	10.0	6	4	6
10	CA421-4V10uF(*)B(**)	T4210B106(*)004(**)	(*)	4V10uF	B	1	10.0	6	4	6
15	CA421-4V15uF(*)B(**)	T4210B156(*)004(**)	(*)	4V15uF	B	1.2	12.0	6	4	6
22	CA421-4V22uF(*)C(**)	T4210C226(*)004(**)	(*)	4V22uF	C	1.8	17.6	6	4	6
33	CA421-4V33uF(*)C(**)	T4210C336(*)004(**)	(*)	4V33uF	C	2.6	26.4	6	4	6
47	CA421-4V47uF(*)C(**)	T4210C476(*)004(**)	(*)	4V47uF	C	3.8	37.6	6	4	6
68	CA421-4V68uF(*)D(**)	T4210D686(*)004(**)	(*)	4V68uF	D	5.4	54.4	6	4	6
100	CA421-4V100uF(*)D(**)	T4210D107(*)006(**)	(*)	4V100uF	D	8.0	80.0	6	4	6
6.3 Volt 额定电压 +85℃时										
1	CA421-6.3V1uF(*)A(**)	T4210A105(*)006(**)	(*)	6.3V1uF	A	1	10.0	6	4	6
1.5	CA421-6.3V1.5uF(*)A(**)	T4210A155(*)006(**)	(*)	6.3V1.5uF	A	1	10.0	6	4	6
2.2	CA421-6.3V2.2uF(*)A(**)	T4210A225(*)006(**)	(*)	6.3V2.2uF	A	1	10.0	6	4	6
3.3	CA421-6.3V3.3uF(*)B(**)	T4210B335(*)006(**)	(*)	6.3V3.3uF	B	1	10.0	6	4	6
4.7	CA421-6.3V4.7uF(*)B(**)	T4210B475(*)006(**)	(*)	6.3V4.7uF	B	1	10.0	8	6	8
6.8	CA421-6.3V6.8uF(*)B(**)	T4210B685(*)006(**)	(*)	6.3V6.8uF	B	1	10.0	8	6	8
10	CA421-6.3V10uF(*)B(**)	T4210B106(*)006(**)	(*)	6.3V10uF	B	1.3	12.6	8	6	8
15	CA421-6.3V15uF(*)C(**)	T4210C156(*)006(**)	(*)	6.3V15uF	C	1.9	18.9	8	6	8
22	CA421-6.3V22uF(*)C(**)	T4210C226(*)006(**)	(*)	6.3V22uF	C	2.8	27.7	8	6	8
33	CA421-6.3V33uF(*)C(**)	T4210C336(*)006(**)	(*)	6.3V33uF	C	4.2	41.6	8	6	8
47	CA421-6.3V47uF(*)D(**)	T4210D476(*)006(**)	(*)	6.3V47uF	D	5.9	59.2	8	6	8
68	CA421-6.3V68uF(*)D(**)	T4210D686(*)010(**)	(*)	6.3V68uF	D	8.6	85.7	8	6	8
10 Volt 额定电压 +85℃时										
0.68	CA421-10V0.68uF(*)A(**)	T4210A684(*)010(**)	(*)	10V0.68uF	A	1	10.0	8	6	8
1	CA421-10V1uF(*)A(**)	T4210A105(*)010(**)	(*)	10V1uF	A	1	10.0	8	6	8
1.5	CA421-10V1.5uF(*)A(**)	T4210A155(*)010(**)	(*)	10V1.5uF	A	1	10.0	8	6	8
2.2	CA421-10V2.2uF(*)B(**)	T4210B225(*)010(**)	(*)	10V2.2uF	B	1	10.0	8	6	8
3.3	CA421-10V3.3uF(*)B(**)	T4210B335(*)010(**)	(*)	10V3.3uF	B	1	10.0	8	6	8
4.7	CA421-10V4.7uF(*)B(**)	T4210B475(*)010(**)	(*)	10V4.7uF	B	1	10.0	8	6	8
6.8	CA421-10V6.8uF(*)B(**)	T4210B685(*)010(**)	(*)	10V6.8uF	B	1.4	13.6	8	6	8
10	CA421-10V10uF(*)C(**)	T4210C106(*)010(**)	(*)	10V10uF	C	2.0	20.0	8	6	8
15	CA421-10V15uF(*)C(**)	T4210C156(*)010(**)	(*)	10V15uF	C	3.0	30.0	8	6	8
22	CA421-10V22uF(*)C(**)	T4210C226(*)010(**)	(*)	10V22uF	C	4.4	44.0	8	6	8
33	CA421-10V33uF(*)D(**)	T4210D336(*)010(**)	(*)	10V33uF	D	6.6	66.0	8	6	8
47	CA421-10V47uF(*)D(**)	T4210D476(*)016(**)	(*)	10V47uF	D	9.4	94.0	8	6	8
16 Volt 额定电压 +85℃时										
0.47	CA421-16V0.47uF(*)A(**)	T4210A474(*)016(**)	(*)	16V0.47uF	A	1	10.0	8	6	8
0.68	CA421-16V0.68uF(*)A(**)	T4210A684(*)016(**)	(*)	16V0.68uF	A	1	10.0	8	6	8
1	CA421-16V1uF(*)A(**)	T4210A105(*)016(**)	(*)	16V1uF	A	1	10.0	8	6	8
1.5	CA421-16V1.5uF(*)B(**)	T4210B155(*)016(**)	(*)	16V1.5uF	B	1	10.0	8	6	8
2.2	CA421-16V2.2uF(*)B(**)	T4210B225(*)016(**)	(*)	16V2.2uF	B	1	10.0	8	6	8
3.3	CA421-16V3.3uF(*)B(**)	T4210B335(*)016(**)	(*)	16V3.3uF	B	1.1	10.6	8	6	8
4.7	CA421-16V4.7uF(*)B(**)	T4210B475(*)016(**)	(*)	16V4.7uF	B	1.5	15.0	8	6	8
6.8	CA421-16V6.8uF(*)C(**)	T4210C685(*)016(**)	(*)	16V6.8uF	C	2.2	21.8	8	6	8
10	CA421-16V10uF(*)C(**)	T4210C106(*)016(**)	(*)	16V10uF	C	3.2	32.0	8	6	8
15	CA421-16V15uF(*)C(**)	T4210C156(*)016(**)	(*)	16V15uF	C	4.8	48.0	8	6	8
22	CA421-16V22uF(*)D(**)	T4210D226(*)016(**)	(*)	16V22uF	D	7.0	70.4	10	8	10
33	CA421-16V33uF(*)D(**)	T4210D336(*)025(**)	(*)	16V33uF	D	10.6	105.6	10	8	10
25 Volt 额定电压 +85℃时										
0.33	CA421-25V0.33uF(*)A(**)	T4210A334(*)025(**)	(*)	25V0.33uF	A	1	10.0	10	8	10
0.47	CA421-25V0.47uF(*)A(**)	T4210A474(*)025(**)	(*)	25V0.47uF	A	1	10.0	10	8	10
0.68	CA421-25V0.68uF(*)A(**)	T4210A684(*)025(**)	(*)	25V0.68uF	A	1	10.0	10	8	10
1	CA421-25V1uF(*)B(**)	T4210B105(*)025(**)	(*)	25V1uF	B	1	10.0	10	8	10
1.5	CA421-25V1.5uF(*)B(**)	T4210B155(*)025(**)	(*)	25V1.5uF	B	1	10.0	10	8	10
2.2	CA421-25V2.2uF(*)B(**)	T4210B225(*)025(**)	(*)	25V2.2uF	B	1.1	11.0	10	8	10
3.3	CA421-25V3.3uF(*)B(**)	T4210B335(*)025(**)	(*)	25V3.3uF	B	1.7	16.5	10	8	10
4.7	CA421-25V4.7uF(*)C(**)	T4210C475(*)025(**)	(*)	25V4.7uF	C	2.4	23.5	10	8	10
6.8	CA421-25V6.8uF(*)C(**)	T4210C685(*)025(**)	(*)	25V6.8uF	C	3.4	34.0	10	8	10
10	CA421-25V10uF(*)C(**)	T4210C106(*)025(**)	(*)	25V10uF	C	5.0	50.0	10	8	10
15	CA421-25V15uF(*)D(**)	T4210D156(*)025(**)	(*)	25V15uF	D	7.5	75.0	10	8	10

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	损耗角正切 -55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)
22	CA421-25V22uF(*)D(**)	T4210D226(*)032(**)	(*)	25V22uF	D	11.0	110.0	10	8	10
32 Volt 额定电压 +85℃时										
0.1	CA421-32V0.1uF(*)A(**)	T4210A104(*)032(**)	(*)	32V0.1uF	A	1	10.0	10	8	10
0.15	CA421-32V0.15uF(*)A(**)	T4210A154(*)032(**)	(*)	32V0.15uF	A	1	10.0	10	8	10
0.22	CA421-32V0.22uF(*)A(**)	T4210A224(*)032(**)	(*)	32V0.22uF	A	1	10.0	10	8	10
0.33	CA421-32V0.33uF(*)A(**)	T4210A334(*)032(**)	(*)	32V0.33uF	A	1	10.0	10	8	10
0.47	CA421-32V0.47uF(*)A(**)	T4210A474(*)032(**)	(*)	32V0.47uF	A	1	10.0	10	8	10
0.68	CA421-32V0.68uF(*)B(**)	T4210B684(*)032(**)	(*)	32V0.68uF	B	1	10.0	10	8	10
1	CA421-32V1uF(*)B(**)	T4210B105(*)032(**)	(*)	32V1uF	B	1	10.0	10	8	10
1.5	CA421-32V1.5uF(*)B(**)	T4210B155(*)032(**)	(*)	32V1.5uF	B	1	10.0	10	8	10
2.2	CA421-32V2.2uF(*)C(**)	T4210C225(*)032(**)	(*)	32V2.2uF	C	1.4	14.1	10	8	10
3.3	CA421-32V3.3uF(*)C(**)	T4210C335(*)032(**)	(*)	32V3.3uF	C	2.1	21.1	10	8	10
4.7	CA421-32V4.7uF(*)C(**)	T4210C475(*)032(**)	(*)	32V4.7uF	C	3.0	30.1	10	8	10
6.8	CA421-32V6.8uF(*)D(**)	T4210D685(*)032(**)	(*)	32V6.8uF	D	4.4	43.5	12	10	12
10	CA421-32V10uF(*)D(**)	T4210D106(*)004(**)	(*)	32V10uF	D	6.4	64.0	6	4	6

(*)：电容量允许偏差：±10%，±20%

如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。