

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25°C (uA)	漏电流 +85°C (uA)	漏电流 +125°C (uA)	损耗角正切 -55°C 120Hz(%)	损耗角正切 +25°C 120Hz(%)	损耗角正切 +85°C 120Hz(%)	损耗角正切 +125°C 120Hz(%)
6.8	CA42B-25V6.8uF(*)C(**)	T42B0C685(*)025(**)	(*)	25V6.8uF	C	1.7	17.0	25.5	6	6	8	8
10	CA42B-25V10uF(*)D(**)	T42B0D106(*)025(**)	(*)	25V10uF	D	2.5	25.0	37.5	8	8	10	10
15	CA42B-25V15uF(*)E(**)	T42B0E156(*)025(**)	(*)	25V15uF	E	3.8	37.5	56.3	8	8	10	10
22	CA42B-25V22uF(*)F(**)	T42B0F226(*)025(**)	(*)	25V22uF	F	5.5	55.0	82.5	8	8	10	10
33	CA42B-25V33uF(*)G(**)	T42B0G336(*)025(**)	(*)	25V33uF	G	8.3	82.5	123.8	8	8	10	10
47	CA42B-25V47uF(*)H(**)	T42B0H476(*)025(**)	(*)	25V47uF	H	11.8	117.5	176.3	8	8	10	10
68	CA42B-25V68uF(*)I(**)	T42B0I686(*)025(**)	(*)	25V68uF	I	17.0	170.0	255.0	8	8	10	10
100	CA42B-25V100uF(*)J(**)	T42B0J107(*)025(**)	(*)	25V100uF	J	25.0	250.0	375.0	10	10	12	12
35 Volt 额定电压 +85°C时 (20 Volt 额定电压 +125°C时)												
0.1	CA42B-35V0.1uF(*)A(**)	T42B0A104(*)035(**)	(*)	35V0.1uF	A	0.5	5.0	7.5	4	4	6	6
0.15	CA42B-35V0.15uF(*)A(**)	T42B0A154(*)035(**)	(*)	35V0.15uF	A	0.5	5.0	7.5	4	4	6	6
0.22	CA42B-35V0.22uF(*)A(**)	T42B0A224(*)035(**)	(*)	35V0.22uF	A	0.5	5.0	7.5	4	4	6	6
0.33	CA42B-35V0.33uF(*)B(**)	T42B0B334(*)035(**)	(*)	35V0.33uF	B	0.5	5.0	7.5	4	4	6	6
0.47	CA42B-35V0.47uF(*)B(**)	T42B0B474(*)035(**)	(*)	35V0.47uF	B	0.5	5.0	7.5	4	4	6	6
0.68	CA42B-35V0.68uF(*)B(**)	T42B0B684(*)035(**)	(*)	35V0.68uF	B	0.5	5.0	7.5	4	4	6	6
1	CA42B-35V1uF(*)B(**)	T42B0B105(*)035(**)	(*)	35V1uF	B	0.5	5.0	7.5	4	4	6	6
1.5	CA42B-35V1.5uF(*)B(**)	T42B0B155(*)035(**)	(*)	35V1.5uF	B	0.5	5.3	7.9	6	6	8	8
2.2	CA42B-35V2.2uF(*)B(**)	T42B0B225(*)035(**)	(*)	35V2.2uF	B	0.8	7.7	11.6	6	6	8	8
3.3	CA42B-35V3.3uF(*)B(**)	T42B0B335(*)035(**)	(*)	35V3.3uF	B	1.2	11.6	17.3	6	6	8	8
4.7	CA42B-35V4.7uF(*)C(**)	T42B0C475(*)035(**)	(*)	35V4.7uF	C	1.6	16.5	24.7	6	6	8	8
6.8	CA42B-35V6.8uF(*)C(**)	T42B0C685(*)035(**)	(*)	35V6.8uF	C	2.4	23.8	35.7	6	6	8	8
10	CA42B-35V10uF(*)D(**)	T42B0D106(*)035(**)	(*)	35V10uF	D	3.5	35.0	52.5	8	8	10	10
15	CA42B-35V15uF(*)E(**)	T42B0E156(*)035(**)	(*)	35V15uF	E	5.3	52.5	78.8	8	8	10	10
22	CA42B-35V22uF(*)F(**)	T42B0F226(*)035(**)	(*)	35V22uF	F	7.7	77.0	115.5	8	8	10	10
33	CA42B-35V33uF(*)G(**)	T42B0G336(*)035(**)	(*)	35V33uF	G	11.6	115.5	173.3	8	8	10	10
47	CA42B-35V47uF(*)G(**)	T42B0G476(*)035(**)	(*)	35V47uF	G	16.5	164.5	246.8	8	8	10	10
68	CA42B-35V68uF(*)H(**)	T42B0H686(*)035(**)	(*)	35V68uF	H	23.8	238.0	357.0	8	8	10	10
40 Volt 额定电压 +85°C时 (25 Volt 额定电压 +125°C时)												
0.1	CA42B-40V0.1uF(*)A(**)	T42B0A104(*)040(**)	(*)	40V0.1uF	A	0.5	5.0	7.5	4	4	6	6
0.15	CA42B-40V0.15uF(*)A(**)	T42B0A154(*)040(**)	(*)	40V0.15uF	A	0.5	5.0	7.5	4	4	6	6
0.22	CA42B-40V0.22uF(*)A(**)	T42B0A224(*)040(**)	(*)	40V0.22uF	A	0.5	5.0	7.5	4	4	6	6
0.33	CA42B-40V0.33uF(*)B(**)	T42B0B334(*)040(**)	(*)	40V0.33uF	B	0.5	5.0	7.5	4	4	6	6
0.47	CA42B-40V0.47uF(*)B(**)	T42B0B474(*)040(**)	(*)	40V0.47uF	B	0.5	5.0	7.5	4	4	6	6
0.68	CA42B-40V0.68uF(*)B(**)	T42B0B684(*)040(**)	(*)	40V0.68uF	B	0.5	5.0	7.5	4	4	6	6
1	CA42B-40V1uF(*)B(**)	T42B0B105(*)040(**)	(*)	40V1uF	B	0.5	5.0	7.5	4	4	6	6
1.5	CA42B-40V1.5uF(*)B(**)	T42B0B155(*)040(**)	(*)	40V1.5uF	B	0.6	6.0	9.0	6	6	8	8
2.2	CA42B-40V2.2uF(*)B(**)	T42B0B225(*)040(**)	(*)	40V2.2uF	B	0.9	8.8	13.2	6	6	8	8
3.3	CA42B-40V3.3uF(*)C(**)	T42B0C335(*)040(**)	(*)	40V3.3uF	C	1.3	13.2	19.8	6	6	8	8
4.7	CA42B-40V4.7uF(*)D(**)	T42B0D475(*)040(**)	(*)	40V4.7uF	D	1.9	18.8	28.2	6	6	8	8
6.8	CA42B-40V6.8uF(*)E(**)	T42B0E685(*)040(**)	(*)	40V6.8uF	E	2.7	27.2	40.8	6	6	8	8
10	CA42B-40V10uF(*)E(**)	T42B0E106(*)040(**)	(*)	40V10uF	E	4.0	40.0	60.0	8	8	10	10
15	CA42B-40V15uF(*)F(**)	T42B0F156(*)040(**)	(*)	40V15uF	F	6.0	60.0	90.0	8	8	10	10
22	CA42B-40V22uF(*)G(**)	T42B0G226(*)040(**)	(*)	40V22uF	G	8.8	88.0	132.0	8	8	10	10
33	CA42B-40V33uF(*)G(**)	T42B0G336(*)040(**)	(*)	40V33uF	G	13.2	132.0	198.0	8	8	10	10
47	CA42B-40V47uF(*)H(**)	T42B0H476(*)040(**)	(*)	40V47uF	H	18.8	188.0	282.0	8	8	10	10
50 Volt 额定电压 +85°C时 (32 Volt 额定电压 +125°C时)												
0.1	CA42B-50V0.1uF(*)A(**)	T42B0A104(*)050(**)	(*)	50V0.1uF	A	0.5	5.0	7.5	4	4	6	6
0.15	CA42B-50V0.15uF(*)A(**)	T42B0A154(*)050(**)	(*)	50V0.15uF	A	0.5	5.0	7.5	4	4	6	6
0.22	CA42B-50V0.22uF(*)A(**)	T42B0A224(*)050(**)	(*)	50V0.22uF	A	0.5	5.0	7.5	4	4	6	6
0.33	CA42B-50V0.33uF(*)B(**)	T42B0B334(*)050(**)	(*)	50V0.33uF	B	0.5	5.0	7.5	4	4	6	6
0.47	CA42B-50V0.47uF(*)B(**)	T42B0B474(*)050(**)	(*)	50V0.47uF	B	0.5	5.0	7.5	4	4	6	6
0.68	CA42B-50V0.68uF(*)B(**)	T42B0B684(*)050(**)	(*)	50V0.68uF	B	0.5	5.0	7.5	4	4	6	6
1	CA42B-50V1uF(*)C(**)	T42B0C105(*)050(**)	(*)	50V1uF	C	0.5	5.0	7.5	4	4	6	6
1.5	CA42B-50V1.5uF(*)D(**)	T42B0D155(*)050(**)	(*)	50V1.5uF	D	0.8	7.5	11.3	6	6	8	8
2.2	CA42B-50V2.2uF(*)D(**)	T42B0D225(*)050(**)	(*)	50V2.2uF	D	1.1	11.0	16.5	6	6	8	8
3.3	CA42B-50V3.3uF(*)D(**)	T42B0D335(*)050(**)	(*)	50V3.3uF	D	1.7	16.5	24.8	6	6	8	8
4.7	CA42B-50V4.7uF(*)E(**)	T42B0E475(*)050(**)	(*)	50V4.7uF	E	2.4	23.5	35.3	6	6	8	8
6.8	CA42B-50V6.8uF(*)E(**)	T42B0E685(*)050(**)	(*)	50V6.8uF	E	3.4	34.0	51.0	6	6	8	8
10	CA42B-50V10uF(*)F(**)	T42B0F106(*)050(**)	(*)	50V10uF	F	5.0	50.0	75.0	8	8	10	10
15	CA42B-50V15uF(*)G(**)	T42B0G156(*)050(**)	(*)	50V15uF	G	7.5	75.0	112.5	8	8	10	10
22	CA42B-50V22uF(*)G(**)	T42B0G226(*)050(**)	(*)	50V22uF	G	11.0	110.0	165.0	8	8	10	10
33	CA42B-50V33uF(*)H(**)	T42B0H336(*)050(**)	(*)	50V33uF	H	16.5	165.0	247.5	8	8	10	10

(*)：电容量允许偏差：±10%，±20%
如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。