

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25 °C(uA)	漏电流 +85°(uA)	漏电流 +125°(uA)	损耗角正切 55° 120Hz(%)	损耗角正切 +25° 120Hz(%)	损耗角正切 +85° 120Hz(%)	损耗角正切 +125° 120Hz(%)
6.3 Volt 额定电压 +85°时 (4 Volt 额定电压 +125°时)												
2.2	CA41-6.3V2.2uF(*)B	T4100B225(*)006(**)	(*)	6.3V2.2uF	B	0.50	4.00	5.00	7	5	6	7
3.3	CA41-6.3V3.3uF(*)B	T4100B335(*)006(**)	(*)	6.3V3.3uF	B	0.50	4.00	5.00	7	5	6	7
4.7	CA41-6.3V4.7uF(*)B	T4100B475(*)006(**)	(*)	6.3V4.7uF	B	0.50	4.00	5.00	7	5	6	7
6.8	CA41-6.3V6.8uF(*)C	T4100C685(*)006(**)	(*)	6.3V6.8uF	C	0.50	4.00	5.00	7	5	6	7
6.8	CA41-6.3V6.8uF(*)B	T4100B685(*)006(**)	(*)	6.3V6.8uF	B	0.50	4.00	5.00	7	5	6	7
10	CA41-6.3V10uF(*)C	T4100C106(*)006(**)	(*)	6.3V10uF	C	0.63	5.04	6.30	7	5	6	7
10	CA41-6.3V10uF(*)B	T4100B106(*)006(**)	(*)	6.3V10uF	B	0.63	5.04	6.30	7	5	6	7
15	CA41-6.3V15uF(*)C	T4100C156(*)006(**)	(*)	6.3V15uF	C	0.95	7.56	9.45	7	5	6	7
15	CA41-6.3V15uF(*)B	T4100B156(*)006(**)	(*)	6.3V15uF	B	0.95	7.56	9.45	7	5	6	7
22	CA41-6.3V22uF(*)D	T4100D226(*)006(**)	(*)	6.3V22uF	D	1.39	11.09	13.86	7	5	6	7
22	CA41-6.3V22uF(*)C	T4100C226(*)006(**)	(*)	6.3V22uF	C	1.39	11.09	13.86	7	5	6	7
33	CA41-6.3V33uF(*)D	T4100D336(*)006(**)	(*)	6.3V33uF	D	2.08	16.63	20.79	7	5	6	7
33	CA41-6.3V33uF(*)C	T4100C336(*)006(**)	(*)	6.3V33uF	C	2.08	16.63	20.79	7	5	6	7
47	CA41-6.3V47uF(*)E	T4100E476(*)006(**)	(*)	6.3V47uF	E	2.96	23.69	29.61	7	5	6	7
47	CA41-6.3V47uF(*)D	T4100D476(*)006(**)	(*)	6.3V47uF	D	2.96	23.69	29.61	7	5	6	7
68	CA41-6.3V68uF(*)E	T4100E686(*)006(**)	(*)	6.3V68uF	E	4.28	34.27	42.84	7	5	6	7
68	CA41-6.3V68uF(*)D	T4100D686(*)006(**)	(*)	6.3V68uF	D	4.28	34.27	42.84	7	5	6	7
100	CA41-6.3V100uF(*)E	T4100E107(*)006(**)	(*)	6.3V100uF	E	6.30	50.40	63.00	8	7	7	8
100	CA41-6.3V100uF(*)D	T4100D107(*)006(**)	(*)	6.3V100uF	D	6.30	50.40	63.00	8	7	7	8
150	CA41-6.3V150uF(*)E	T4100E157(*)006(**)	(*)	6.3V150uF	E	9.45	75.60	94.50	8	7	7	8
150	CA41-6.3V150uF(*)D	T4100D157(*)006(**)	(*)	6.3V150uF	D	9.45	75.60	94.50	8	7	7	8
220	CA41-6.3V220uF(*)F	T4100F227(*)006(**)	(*)	6.3V220uF	F	13.86	110.88	138.60	8	7	7	8
220	CA41-6.3V220uF(*)E	T4100E227(*)006(**)	(*)	6.3V220uF	E	13.86	110.88	138.60	8	7	7	8
330	CA41-6.3V330uF(*)F	T4100F337(*)006(**)	(*)	6.3V330uF	F	20.79	166.32	207.90	10	10	10	10
330	CA41-6.3V330uF(*)E	T4100E337(*)006(**)	(*)	6.3V330uF	E	20.79	166.32	207.90	10	10	10	10
470	CA41-6.3V470uF(*)F	T4100F477(*)006(**)	(*)	6.3V470uF	F	29.61	236.88	296.10	10	10	10	10
470	CA41-6.3V470uF(*)E	T4100E477(*)006(**)	(*)	6.3V470uF	E	29.61	236.88	296.10	10	10	10	10
680	CA41-6.3V680uF(*)F	T4100F687(*)006(**)	(*)	6.3V680uF	F	42.84	342.72	428.40	15	12	15	15
1000	CA41-6.3V1000uF(*)F	T4100F108(*)006(**)	(*)	6.3V1000uF	F	63.00	504.00	630.00	15	12	15	15
10 Volt 额定电压 +85°时 (6.3 Volt 额定电压 +125°时)												
1.5	CA41-10V1.5uF(*)B	T4100B155(*)010(**)	(*)	10V1.5uF	B	0.50	4.00	5.00	7	5	6	7
2.2	CA41-10V2.2uF(*)B	T4100B225(*)010(**)	(*)	10V2.2uF	B	0.50	4.00	5.00	7	5	6	7
3.3	CA41-10V3.3uF(*)B	T4100B335(*)010(**)	(*)	10V3.3uF	B	0.50	4.00	5.00	7	5	6	7
4.7	CA41-10V4.7uF(*)C	T4100C475(*)010(**)	(*)	10V4.7uF	C	0.50	4.00	5.00	7	5	6	7
4.7	CA41-10V4.7uF(*)B	T4100B475(*)010(**)	(*)	10V4.7uF	B	0.50	4.00	5.00	7	5	6	7
6.8	CA41-10V6.8uF(*)C	T4100C685(*)010(**)	(*)	10V6.8uF	C	0.68	5.44	6.80	7	5	6	7
6.8	CA41-10V6.8uF(*)B	T4100B685(*)010(**)	(*)	10V6.8uF	B	0.68	5.44	6.80	7	5	6	7
10	CA41-10V10uF(*)C	T4100C106(*)010(**)	(*)	10V10uF	C	1.00	8.00	10.00	7	5	6	7
10	CA41-10V10uF(*)B	T4100B106(*)010(**)	(*)	10V10uF	B	1.00	8.00	10.00	7	5	6	7
15	CA41-10V15uF(*)D	T4100D156(*)010(**)	(*)	10V15uF	D	1.50	12.00	15.00	7	5	6	7
15	CA41-10V15uF(*)C	T4100C156(*)010(**)	(*)	10V15uF	C	1.50	12.00	15.00	7	5	6	7
22	CA41-10V22uF(*)D	T4100D226(*)010(**)	(*)	10V22uF	D	2.20	17.60	22.00	7	5	6	7
22	CA41-10V22uF(*)C	T4100C226(*)010(**)	(*)	10V22uF	C	2.20	17.60	22.00	7	5	6	7
33	CA41-10V33uF(*)E	T4100E336(*)010(**)	(*)	10V33uF	E	3.30	26.40	33.00	7	5	6	7
33	CA41-10V33uF(*)D	T4100D336(*)010(**)	(*)	10V33uF	D	3.30	26.40	33.00	7	5	6	7
47	CA41-10V47uF(*)E	T4100E476(*)010(**)	(*)	10V47uF	E	4.70	37.60	47.00	7	5	6	7
47	CA41-10V47uF(*)D	T4100D476(*)010(**)	(*)	10V47uF	D	4.70	37.60	47.00	7	5	6	7
68	CA41-10V68uF(*)E	T4100E686(*)010(**)	(*)	10V68uF	E	6.80	54.40	68.00	7	5	6	7
68	CA41-10V68uF(*)D	T4100D686(*)010(**)	(*)	10V68uF	D	6.80	54.40	68.00	7	5	6	7
100	CA41-10V100uF(*)E	T4100E107(*)010(**)	(*)	10V100uF	E	10.00	80.00	100.00	8	7	7	8
100	CA41-10V100uF(*)D	T4100D107(*)010(**)	(*)	10V100uF	D	10.00	80.00	100.00	8	7	7	8
150	CA41-10V150uF(*)F	T4100F157(*)010(**)	(*)	10V150uF	F	15.00	120.00	150.00	8	7	7	8
150	CA41-10V150uF(*)E	T4100E157(*)010(**)	(*)	10V150uF	E	15.00	120.00	150.00	8	7	7	8
220	CA41-10V220uF(*)F	T4100F227(*)010(**)	(*)	10V220uF	F	22.00	176.00	220.00	8	7	7	8
220	CA41-10V220uF(*)E	T4100E227(*)010(**)	(*)	10V220uF	E	22.00	176.00	220.00	8	7	7	8
330	CA41-10V330uF(*)F	T4100F337(*)010(**)	(*)	10V330uF	F	33.00	264.00	330.00	10	10	10	10
330	CA41-10V330uF(*)E	T4100E337(*)010(**)	(*)	10V330uF	E	33.00	264.00	330.00	10	10	10	10
470	CA41-10V470uF(*)F	T4100F477(*)010(**)	(*)	10V470uF	F	47.00	376.00	470.00	10	10	10	10
680	CA41-10V680uF(*)F	T4100F687(*)010(**)	(*)	10V680uF	F	68.00	544.00	680.00	15	12	15	15
16 Volt 额定电压 +85°时 (10 Volt 额定电压 +125°时)												
1	CA41-16V1uF(*)B	T4100B105(*)016(**)	(*)	16V1uF	B	0.50	4.00	5.00	6	3	5	6
1.5	CA41-16V1.5uF(*)B	T4100B155(*)016(**)	(*)	16V1.5uF	B	0.50	4.00	5.00	7	5	6	7
2.2	CA41-16V2.2uF(*)B	T4100B225(*)016(**)	(*)	16V2.2uF	B	0.50	4.00	5.00	7	5	6	7
3.3	CA41-16V3.3uF(*)C	T4100C335(*)016(**)	(*)	16V3.3uF	C	0.53	4.22	5.28	7	5	6	7
3.3	CA41-16V3.3uF(*)B	T4100B335(*)016(**)	(*)	16V3.3uF	B	0.53	4.22	5.28	7	5	6	7
4.7	CA41-16V4.7uF(*)C	T4100C475(*)016(**)	(*)	16V4.7uF	C	0.75	6.02	7.52	7	5	6	7
4.7	CA41-16V4.7uF(*)B	T4100B475(*)016(**)	(*)	16V4.7uF	B	0.75	6.02	7.52	7	5	6	7
6.8	CA41-16V6.8uF(*)C	T4100C685(*)016(**)	(*)	16V6.8uF	C	1.09	8.70	10.88	7	5	6	7
6.8	CA41-16V6.8uF(*)B	T4100B685(*)016(**)	(*)	16V6.8uF	B	1.09	8.70	10.88	7	5	6	7
10	CA41-16V10uF(*)D	T4100D106(*)016(**)	(*)	16V10uF	D	1.60	12.80	16.00	7	5	6	7
10	CA41-16V10uF(*)C	T4100C106(*)016(**)	(*)	16V10uF	C	1.60	12.80	16.00	7	5	6	7
15	CA41-16V15uF(*)D	T4100D156(*)016(**)	(*)	16V15uF	D	2.40	19.20	24.00	7	5	6	7
15	CA41-16V15uF(*)C	T4100C156(*)016(**)	(*)	16V15uF	C	2.40	19.20	24.00	7	5	6	7
22	CA41-16V22uF(*)E	T4100E226(*)016(**)	(*)	16V22uF	E	3.52	28.16	35.20	7	5	6	7
22	CA41-16V22uF(*)D	T4100D226(*)016(**)	(*)	16V22uF	D	3.52	28.16	35.20	7	5	6	7
33	CA41-16V33uF(*)E	T4100E336(*)016(**)	(*)	16V33uF	E	5.28	42.24	52.80	7	5	6	7
33	CA41-16V33uF(*)D	T4100D336(*)016(**)	(*)	16V33uF	D	5.28	42.24	52.80	7	5	6	7

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25℃ (uA)	漏电流 +85℃ (uA)	漏电流 +125℃ (uA)	损耗角正切 55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
47	CA41-16V47uF(*)E	T4100E476(*)016(**)	(*)	16V47uF	E	7.52	60.16	75.20	7	5	6	7
47	CA41-16V47uF(*)D	T4100D476(*)016(**)	(*)	16V47uF	D	7.52	60.16	75.20	7	5	6	7
68	CA41-16V68uF(*)E	T4100E686(*)016(**)	(*)	16V68uF	E	10.88	87.04	108.80	7	5	6	7
68	CA41-16V68uF(*)D	T4100D686(*)016(**)	(*)	16V68uF	D	10.88	87.04	108.80	7	5	6	7
100	CA41-16V100uF(*)F	T4100F107(*)016(**)	(*)	16V100uF	F	16.00	128.00	160.00	8	7	7	8
100	CA41-16V100uF(*)E	T4100E107(*)016(**)	(*)	16V100uF	E	16.00	128.00	160.00	8	7	7	8
150	CA41-16V150uF(*)F	T4100F157(*)016(**)	(*)	16V150uF	F	24.00	192.00	240.00	8	7	7	8
150	CA41-16V150uF(*)E	T4100E157(*)016(**)	(*)	16V150uF	E	24.00	192.00	240.00	8	7	7	8
220	CA41-16V220uF(*)F	T4100F227(*)016(**)	(*)	16V220uF	F	35.20	281.60	352.00	8	7	7	8
330	CA41-16V330uF(*)F	T4100F337(*)016(**)	(*)	16V330uF	F	52.80	422.40	528.00	10	10	10	10
25 Volt 额定电压 +85℃时 (16 Volt 额定电压 +125℃时)												
0.47	CA41-25V0.47uF(*)B	T4100B474(*)025(**)	(*)	25V0.47uF	B	0.50	4.00	5.00	6	3	5	6
0.68	CA41-25V0.68uF(*)B	T4100B684(*)025(**)	(*)	25V0.68uF	B	0.50	4.00	5.00	6	3	5	6
1	CA41-25V1uF(*)B	T4100B105(*)025(**)	(*)	25V1uF	B	0.50	4.00	5.00	6	3	5	6
1.5	CA41-25V1.5uF(*)C	T4100C155(*)025(**)	(*)	25V1.5uF	C	0.50	4.00	5.00	7	5	6	7
1.5	CA41-25V1.5uF(*)B	T4100B155(*)025(**)	(*)	25V1.5uF	B	0.50	4.00	5.00	7	5	6	7
2.2	CA41-25V2.2uF(*)C	T4100C225(*)025(**)	(*)	25V2.2uF	C	0.55	4.40	5.50	7	5	6	7
2.2	CA41-25V2.2uF(*)B	T4100B225(*)025(**)	(*)	25V2.2uF	B	0.55	4.40	5.50	7	5	6	7
3.3	CA41-25V3.3uF(*)C	T4100C335(*)025(**)	(*)	25V3.3uF	C	0.83	6.60	8.25	7	5	6	7
3.3	CA41-25V3.3uF(*)B	T4100B335(*)025(**)	(*)	25V3.3uF	B	0.83	6.60	8.25	7	5	6	7
4.7	CA41-25V4.7uF(*)D	T4100D475(*)025(**)	(*)	25V4.7uF	D	1.18	9.40	11.75	7	5	6	7
4.7	CA41-25V4.7uF(*)C	T4100C475(*)025(**)	(*)	25V4.7uF	C	1.18	9.40	11.75	7	5	6	7
6.8	CA41-25V6.8uF(*)D	T4100D685(*)025(**)	(*)	25V6.8uF	D	1.70	13.60	17.00	7	5	6	7
10	CA41-25V10uF(*)D	T4100D106(*)025(**)	(*)	25V10uF	D	2.50	20.00	25.00	7	5	6	7
15	CA41-25V15uF(*)E	T4100E156(*)025(**)	(*)	25V15uF	E	3.75	30.00	37.50	7	5	6	7
15	CA41-25V15uF(*)D	T4100D156(*)025(**)	(*)	25V15uF	D	3.75	30.00	37.50	7	5	6	7
22	CA41-25V22uF(*)E	T4100E226(*)025(**)	(*)	25V22uF	E	5.50	44.00	55.00	7	5	6	7
22	CA41-25V22uF(*)D	T4100D226(*)025(**)	(*)	25V22uF	D	5.50	44.00	55.00	7	5	6	7
33	CA41-25V33uF(*)E	T4100E336(*)025(**)	(*)	25V33uF	E	8.25	66.00	82.50	7	5	6	7
33	CA41-25V33uF(*)D	T4100D336(*)025(**)	(*)	25V33uF	D	8.25	66.00	82.50	7	5	6	7
47	CA41-25V47uF(*)E	T4100E476(*)025(**)	(*)	25V47uF	E	11.75	94.00	117.50	7	5	6	7
68	CA41-25V68uF(*)F	T4100F686(*)025(**)	(*)	25V68uF	F	17.00	136.00	170.00	7	5	6	7
68	CA41-25V68uF(*)E	T4100E686(*)025(**)	(*)	25V68uF	E	17.00	136.00	170.00	7	5	6	7
100	CA41-25V100uF(*)F	T4100F107(*)025(**)	(*)	25V100uF	F	25.00	200.00	250.00	8	7	7	8
150	CA41-25V150uF(*)F	T4100F157(*)025(**)	(*)	25V150uF	F	37.50	300.00	375.00	8	7	7	8
35 Volt 额定电压 +85℃时 (20 Volt 额定电压 +125℃时)												
0.1	CA41-35V0.1uF(*)B	T4100B104(*)035(**)	(*)	35V0.1uF	B	0.50	4.00	5.00	6	3	5	6
0.15	CA41-35V0.15uF(*)B	T4100B154(*)035(**)	(*)	35V0.15uF	B	0.50	4.00	5.00	6	3	5	6
0.22	CA41-35V0.22uF(*)B	T4100B224(*)035(**)	(*)	35V0.22uF	B	0.50	4.00	5.00	6	3	5	6
0.33	CA41-35V0.33uF(*)B	T4100B334(*)035(**)	(*)	35V0.33uF	B	0.50	4.00	5.00	6	3	5	6
0.47	CA41-35V0.47uF(*)B	T4100B474(*)035(**)	(*)	35V0.47uF	B	0.50	4.00	5.00	6	3	5	6
0.68	CA41-35V0.68uF(*)C	T4100C684(*)035(**)	(*)	35V0.68uF	C	0.50	4.00	5.00	6	3	5	6
0.68	CA41-35V0.68uF(*)B	T4100B684(*)035(**)	(*)	35V0.68uF	B	0.50	4.00	5.00	6	3	5	6
1	CA41-35V1uF(*)C	T4100C105(*)035(**)	(*)	35V1uF	C	0.50	4.00	5.00	6	3	5	6
1	CA41-35V1uF(*)B	T4100B105(*)035(**)	(*)	35V1uF	B	0.50	4.00	5.00	6	3	5	6
1.5	CA41-35V1.5uF(*)C	T4100C155(*)035(**)	(*)	35V1.5uF	C	0.53	4.20	5.25	7	5	6	7
2.2	CA41-35V2.2uF(*)D	T4100D225(*)035(**)	(*)	35V2.2uF	D	0.77	6.16	7.70	7	5	6	7
2.2	CA41-35V2.2uF(*)C	T4100C225(*)035(**)	(*)	35V2.2uF	C	0.77	6.16	7.70	7	5	6	7
3.3	CA41-35V3.3uF(*)D	T4100D335(*)035(**)	(*)	35V3.3uF	D	1.16	9.24	11.55	7	5	6	7
3.3	CA41-35V3.3uF(*)C	T4100C335(*)035(**)	(*)	35V3.3uF	C	1.16	9.24	11.55	7	5	6	7
4.7	CA41-35V4.7uF(*)D	T4100D475(*)035(**)	(*)	35V4.7uF	D	1.65	13.16	16.45	7	5	6	7
6.8	CA41-35V6.8uF(*)D	T4100D685(*)035(**)	(*)	35V6.8uF	D	2.38	19.04	23.80	7	5	6	7
10	CA41-35V10uF(*)E	T4100E106(*)035(**)	(*)	35V10uF	E	3.50	28.00	35.00	7	5	6	7
10	CA41-35V10uF(*)D	T4100D106(*)035(**)	(*)	35V10uF	D	3.50	28.00	35.00	7	5	6	7
15	CA41-35V15uF(*)E	T4100E156(*)035(**)	(*)	35V15uF	E	5.25	42.00	52.50	7	5	6	7
22	CA41-35V22uF(*)E	T4100E226(*)035(**)	(*)	35V22uF	E	7.70	61.60	77.00	7	5	6	7
33	CA41-35V33uF(*)F	T4100F336(*)035(**)	(*)	35V33uF	F	11.55	92.40	115.50	7	5	6	7
47	CA41-35V47uF(*)F	T4100F476(*)035(**)	(*)	35V47uF	F	16.45	131.60	164.50	7	5	6	7
68	CA41-35V68uF(*)F	T4100F686(*)035(**)	(*)	35V68uF	F	23.80	190.40	238.00	7	5	6	7
40 Volt 额定电压 +85℃时 (25 Volt 额定电压 +125℃时)												
0.1	CA41-40V0.1uF(*)B	T4100B104(*)040(**)	(*)	40V0.1uF	B	0.50	4.00	5.00	6	3	5	6
0.15	CA41-40V0.15uF(*)B	T4100B154(*)040(**)	(*)	40V0.15uF	B	0.50	4.00	5.00	6	3	5	6
0.22	CA41-40V0.22uF(*)B	T4100B224(*)040(**)	(*)	40V0.22uF	B	0.50	4.00	5.00	6	3	5	6
0.33	CA41-40V0.33uF(*)B	T4100B334(*)040(**)	(*)	40V0.33uF	B	0.50	4.00	5.00	6	3	5	6
0.47	CA41-40V0.47uF(*)B	T4100B474(*)040(**)	(*)	40V0.47uF	B	0.50	4.00	5.00	6	3	5	6
0.68	CA41-40V0.68uF(*)C	T4100C684(*)040(**)	(*)	40V0.68uF	C	0.50	4.00	5.00	6	3	5	6
0.68	CA41-40V0.68uF(*)B	T4100B684(*)040(**)	(*)	40V0.68uF	B	0.50	4.00	5.00	6	3	5	6
1	CA41-40V1uF(*)C	T4100C105(*)040(**)	(*)	40V1uF	C	0.50	4.00	5.00	6	3	5	6
1	CA41-40V1uF(*)B	T4100B105(*)040(**)	(*)	40V1uF	B	0.50	4.00	5.00	6	3	5	6
1.5	CA41-40V1.5uF(*)C	T4100C155(*)040(**)	(*)	40V1.5uF	C	0.60	4.80	6.00	7	5	6	7
2.2	CA41-40V2.2uF(*)D	T4100D225(*)040(**)	(*)	40V2.2uF	D	0.88	7.04	8.80	7	5	6	7
2.2	CA41-40V2.2uF(*)C	T4100C225(*)040(**)	(*)	40V2.2uF	C	0.88	7.04	8.80	7	5	6	7
3.3	CA41-40V3.3uF(*)D	T4100D335(*)040(**)	(*)	40V3.3uF	D	1.32	10.56	13.20	7	5	6	7
4.7	CA41-40V4.7uF(*)E	T4100E475(*)040(**)	(*)	40V4.7uF	E	1.88	15.04	18.80	7	5	6	7
4.7	CA41-40V4.7uF(*)D	T4100D475(*)040(**)	(*)	40V4.7uF	D	1.88	15.04	18.80	7	5	6	7
6.8	CA41-40V6.8uF(*)E	T4100E685(*)040(**)	(*)	40V6.8uF	E	2.72	21.76	27.20	7	5	6	7
6.8	CA41-40V6.8uF(*)D	T4100D685(*)040(**)	(*)	40V6.8uF	D	2.72	21.76	27.20	7	5	6	7
10	CA41-40V10uF(*)E	T4100E106(*)040(**)	(*)	40V10uF	E	4.00	32.00	40.00	7	5	6	7

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25℃ (uA)	漏电流 +85℃ (uA)	漏电流 +125℃ (uA)	损耗角正切 55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
15	CA41-40V15uF(*)E	T4100E156(*)040(**)	(*)	40V15uF	E	6.00	48.00	60.00	7	5	6	7
22	CA41-40V22uF(*)F	T4100F226(*)040(**)	(*)	40V22uF	F	8.80	70.40	88.00	7	5	6	7
33	CA41-40V33uF(*)F	T4100F336(*)040(**)	(*)	40V33uF	F	13.20	105.60	132.00	7	5	6	7
47	CA41-40V47uF(*)F	T4100F476(*)040(**)	(*)	40V47uF	F	18.80	150.40	188.00	7	5	6	7
50 Volt 额定电压 +85℃时 (32 Volt 额定电压 +125℃时)												
0.015	CA41-50V0.015uF(*)B	T4100B153(*)050(**)	(*)	50V0.015uF	B	0.50	4.00	5.00	6	3	5	6
0.022	CA41-50V0.022uF(*)B	T4100B223(*)050(**)	(*)	50V0.022uF	B	0.50	4.00	5.00	6	3	5	6
0.033	CA41-50V0.033uF(*)B	T4100B333(*)050(**)	(*)	50V0.033uF	B	0.50	4.00	5.00	6	3	5	6
0.047	CA41-50V0.047uF(*)B	T4100B473(*)050(**)	(*)	50V0.047uF	B	0.50	4.00	5.00	6	3	5	6
0.068	CA41-50V0.068uF(*)B	T4100B683(*)050(**)	(*)	50V0.068uF	B	0.50	4.00	5.00	6	3	5	6
0.1	CA41-50V0.1uF(*)B	T4100B15(*)050(**)	(*)	50V0.1uF	B	0.50	4.00	5.00	6	3	5	6
0.15	CA41-50V0.15uF(*)B	T4100B154(*)050(**)	(*)	50V0.15uF	B	0.50	4.00	5.00	6	3	5	6
0.22	CA41-50V0.22uF(*)B	T4100B224(*)050(**)	(*)	50V0.22uF	B	0.50	4.00	5.00	6	3	5	6
0.33	CA41-50V0.33uF(*)C	T4100C334(*)050(**)	(*)	50V0.33uF	C	0.50	4.00	5.00	6	3	5	6
0.33	CA41-50V0.33uF(*)B	T4100B334(*)050(**)	(*)	50V0.33uF	B	0.50	4.00	5.00	6	3	5	6
0.47	CA41-50V0.47uF(*)C	T4100C474(*)050(**)	(*)	50V0.47uF	C	0.50	4.00	5.00	6	3	5	6
0.68	CA41-50V0.68uF(*)D	T4100D684(*)050(**)	(*)	50V0.68uF	D	0.50	4.00	5.00	6	3	5	6
0.68	CA41-50V0.68uF(*)C	T4100C684(*)050(**)	(*)	50V0.68uF	C	0.50	4.00	5.00	6	3	5	6
1	CA41-50V1uF(*)D	T4100D105(*)050(**)	(*)	50V1uF	D	0.50	4.00	5.00	6	3	5	6
1	CA41-50V1uF(*)C	T4100C105(*)050(**)	(*)	50V1uF	C	0.50	4.00	5.00	6	3	5	6
1.5	CA41-50V1.5uF(*)D	T4100D155(*)050(**)	(*)	50V1.5uF	D	0.75	6.00	7.50	7	5	6	7
2.2	CA41-50V2.2uF(*)D	T4100D225(*)050(**)	(*)	50V2.2uF	D	1.10	8.80	11.00	7	5	6	7
3.3	CA41-50V3.3uF(*)E	T4100E335(*)050(**)	(*)	50V3.3uF	E	1.65	13.20	16.50	7	5	6	7
3.3	CA41-50V3.3uF(*)D	T4100D335(*)050(**)	(*)	50V3.3uF	D	1.65	13.20	16.50	7	5	6	7
4.7	CA41-50V4.7uF(*)E	T4100E475(*)050(**)	(*)	50V4.7uF	E	2.35	18.80	23.50	7	5	6	7
4.7	CA41-50V4.7uF(*)D	T4100D475(*)050(**)	(*)	50V4.7uF	D	2.35	18.80	23.50	7	5	6	7
6.8	CA41-50V6.8uF(*)E	T4100E685(*)050(**)	(*)	50V6.8uF	E	3.40	27.20	34.00	7	5	6	7
10	CA41-50V10uF(*)E	T4100E106(*)050(**)	(*)	50V10uF	E	5.00	40.00	50.00	7	5	6	7
15	CA41-50V15uF(*)E	T4100E156(*)050(**)	(*)	50V15uF	E	7.50	60.00	75.00	7	5	6	7
22	CA41-50V22uF(*)F	T4100F226(*)050(**)	(*)	50V22uF	F	11.00	88.00	110.00	7	5	6	7
33	CA41-50V33uF(*)F	T4100F336(*)050(**)	(*)	50V33uF	F	16.50	132.00	165.00	7	5	6	7
63 Volt 额定电压 +85℃时 (40 Volt 额定电压 +125℃时)												
0.015	CA41-63V0.015uF(*)B	T4100B153(*)063(**)	(*)	63V0.015uF	B	0.50	4.00	5.00	6	3	5	6
0.022	CA41-63V0.022uF(*)B	T4100B223(*)063(**)	(*)	63V0.022uF	B	0.50	4.00	5.00	6	3	5	6
0.033	CA41-63V0.033uF(*)B	T4100B333(*)063(**)	(*)	63V0.033uF	B	0.50	4.00	5.00	6	3	5	6
0.047	CA41-63V0.047uF(*)B	T4100B473(*)063(**)	(*)	63V0.047uF	B	0.50	4.00	5.00	6	3	5	6
0.068	CA41-63V0.068uF(*)B	T4100B683(*)063(**)	(*)	63V0.068uF	B	0.50	4.00	5.00	6	3	5	6
0.1	CA41-63V0.1uF(*)B	T4100B104(*)063(**)	(*)	63V0.1uF	B	0.06	0.50	0.63	6	3	5	6
0.15	CA41-63V0.15uF(*)B	T4100B154(*)063(**)	(*)	63V0.15uF	B	0.09	0.76	0.95	6	3	5	6
0.22	CA41-63V0.22uF(*)C	T4100C224(*)063(**)	(*)	63V0.22uF	C	0.14	1.11	1.39	6	3	5	6
0.22	CA41-63V0.22uF(*)B	T4100B224(*)063(**)	(*)	63V0.22uF	B	0.14	1.11	1.39	6	3	5	6
0.33	CA41-63V0.33uF(*)C	T4100C334(*)063(**)	(*)	63V0.33uF	C	0.21	1.66	2.08	6	3	5	6
0.47	CA41-63V0.47uF(*)D	T4100D474(*)063(**)	(*)	63V0.47uF	D	0.30	2.37	2.96	6	3	5	6
0.47	CA41-63V0.47uF(*)C	T4100C474(*)063(**)	(*)	63V0.47uF	C	0.30	2.37	2.96	6	3	5	6
0.68	CA41-63V0.68uF(*)D	T4100D684(*)063(**)	(*)	63V0.68uF	D	0.43	3.43	4.28	6	3	5	6
0.68	CA41-63V0.68uF(*)C	T4100C684(*)063(**)	(*)	63V0.68uF	C	0.43	3.43	4.28	6	3	5	6
1	CA41-63V1uF(*)D	T4100D105(*)063(**)	(*)	63V1uF	D	0.63	5.04	6.30	6	3	5	6
1.5	CA41-63V1.5uF(*)E	T4100E155(*)063(**)	(*)	63V1.5uF	E	0.95	7.56	9.45	7	5	6	7
1.5	CA41-63V1.5uF(*)D	T4100D155(*)063(**)	(*)	63V1.5uF	D	0.95	7.56	9.45	7	5	6	7
2.2	CA41-63V2.2uF(*)E	T4100E225(*)063(**)	(*)	63V2.2uF	E	1.39	11.09	13.86	7	5	6	7
2.2	CA41-63V2.2uF(*)D	T4100D225(*)063(**)	(*)	63V2.2uF	D	1.39	11.09	13.86	7	5	6	7
3.3	CA41-63V3.3uF(*)E	T4100E335(*)063(**)	(*)	63V3.3uF	E	2.08	16.63	20.79	7	5	6	7
4.7	CA41-63V4.7uF(*)E	T4100E475(*)063(**)	(*)	63V4.7uF	E	2.96	23.69	29.61	7	5	6	7
6.8	CA41-63V6.8uF(*)E	T4100E685(*)063(**)	(*)	63V6.8uF	E	4.28	34.27	42.84	7	5	6	7
10	CA41-63V10uF(*)F	T4100F106(*)063(**)	(*)	63V10uF	F	6.30	50.40	63.00	7	5	6	7
10	CA41-63V10uF(*)E	T4100E106(*)063(**)	(*)	63V10uF	E	6.30	50.40	63.00	7	5	6	7
15	CA41-63V15uF(*)F	T4100F156(*)063(**)	(*)	63V15uF	F	9.45	75.60	94.50	7	5	6	7
22	CA41-63V22uF(*)F	T4100F226(*)063(**)	(*)	63V22uF	F	13.86	110.88	138.60	7	5	6	7

(*)：电容量允许偏差：±10%，±20%

如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。