

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25°C(uA)	漏电流 +85°C(uA)	漏电流 +125°C(uA)	损耗角正切 -55°C 120Hz(%)	损耗角正切 +25°C 120Hz(%)	损耗角正切 +85°C 120Hz(%)	损耗角正切 +125°C 120Hz(%)
6.3 Volt 额定电压 +85°C时 (4 Volt 额定电压 +125°C时)												
2.2	CA41S-6.3V2.2uF(*)B	T41S0B225(*)006(**)	(*)	6.3V2.2uF	B	0.50	4.00	5.00	7	5	6	7
3.3	CA41S-6.3V3.3uF(*)B	T41S0B335(*)006(**)	(*)	6.3V3.3uF	B	0.50	4.00	5.00	7	5	6	7
4.7	CA41S-6.3V4.7uF(*)B	T41S0B475(*)006(**)	(*)	6.3V4.7uF	B	0.50	4.00	5.00	7	5	6	7
6.8	CA41S-6.3V6.8uF(*)B	T41S0B685(*)006(**)	(*)	6.3V6.8uF	B	0.50	4.00	5.00	7	5	6	7
10	CA41S-6.3V10uF(*)B	T41S0B106(*)006(**)	(*)	6.3V10uF	B	0.63	5.04	6.30	7	5	6	7
15	CA41S-6.3V15uF(*)B	T41S0B156(*)006(**)	(*)	6.3V15uF	B	0.95	7.56	9.45	7	5	6	7
22	CA41S-6.3V22uF(*)C	T41S0C226(*)006(**)	(*)	6.3V22uF	C	1.39	11.09	13.86	7	5	6	7
33	CA41S-6.3V33uF(*)C	T41S0C336(*)006(**)	(*)	6.3V33uF	C	2.08	16.63	20.79	7	5	6	7
47	CA41S-6.3V47uF(*)D	T41S0D476(*)006(**)	(*)	6.3V47uF	D	2.96	23.69	29.61	7	5	6	7
68	CA41S-6.3V68uF(*)D	T41S0D686(*)006(**)	(*)	6.3V68uF	D	4.28	34.27	42.84	7	5	6	7
100	CA41S-6.3V100uF(*)D	T41S0D107(*)006(**)	(*)	6.3V100uF	D	6.30	50.40	63.00	8	7	7	8
150	CA41S-6.3V150uF(*)E	T41S0E157(*)006(**)	(*)	6.3V150uF	E	9.45	75.60	94.50	8	7	7	8
220	CA41S-6.3V220uF(*)E	T41S0E227(*)006(**)	(*)	6.3V220uF	E	13.86	110.88	138.60	8	7	7	8
330	CA41S-6.3V330uF(*)E	T41S0E337(*)006(**)	(*)	6.3V330uF	E	20.79	166.32	207.90	10	10	10	10
470	CA41S-6.3V470uF(*)F	T41S0F477(*)006(**)	(*)	6.3V470uF	F	29.61	236.88	296.10	10	10	10	10
10 Volt 额定电压 +85°C时 (6.3 Volt 额定电压 +125°C时)												
1.5	CA41S-10V1.5uF(*)B	T41S0B155(*)010(**)	(*)	10V1.5uF	B	0.50	4.00	5.00	7	5	6	7
2.2	CA41S-10V2.2uF(*)B	T41S0B225(*)010(**)	(*)	10V2.2uF	B	0.50	4.00	5.00	7	5	6	7
3.3	CA41S-10V3.3uF(*)B	T41S0B335(*)010(**)	(*)	10V3.3uF	B	0.50	4.00	5.00	7	5	6	7
4.7	CA41S-10V4.7uF(*)B	T41S0B475(*)010(**)	(*)	10V4.7uF	B	0.50	4.00	5.00	7	5	6	7
6.8	CA41S-10V6.8uF(*)B	T41S0B685(*)010(**)	(*)	10V6.8uF	B	0.68	5.44	6.80	7	5	6	7
10	CA41S-10V10uF(*)B	T41S0B106(*)010(**)	(*)	10V10uF	B	1.00	8.00	10.00	7	5	6	7
15	CA41S-10V15uF(*)C	T41S0C156(*)010(**)	(*)	10V15uF	C	1.50	12.00	15.00	7	5	6	7
22	CA41S-10V22uF(*)C	T41S0C226(*)010(**)	(*)	10V22uF	C	2.20	17.60	22.00	7	5	6	7
33	CA41S-10V33uF(*)D	T41S0D336(*)010(**)	(*)	10V33uF	D	3.30	26.40	33.00	7	5	6	7
47	CA41S-10V47uF(*)D	T41S0D476(*)010(**)	(*)	10V47uF	D	4.70	37.60	47.00	7	5	6	7
68	CA41S-10V68uF(*)D	T41S0D686(*)010(**)	(*)	10V68uF	D	6.80	54.40	68.00	7	5	6	7
100	CA41S-10V100uF(*)E	T41S0E107(*)010(**)	(*)	10V100uF	E	10.00	80.00	100.00	8	7	7	8
150	CA41S-10V150uF(*)E	T41S0E157(*)010(**)	(*)	10V150uF	E	15.00	120.00	150.00	8	7	7	8
220	CA41S-10V220uF(*)E	T41S0E227(*)010(**)	(*)	10V220uF	E	22.00	176.00	220.00	8	7	7	8
330	CA41S-10V330uF(*)F	T41S0F337(*)010(**)	(*)	10V330uF	F	33.00	264.00	330.00	10	10	10	10
16 Volt 额定电压 +85°C时 (10 Volt 额定电压 +125°C时)												
1	CA41S-16V1uF(*)B	T41S0B105(*)016(**)	(*)	16V1uF	B	0.50	4.00	5.00	6	3	5	6
1.5	CA41S-16V1.5uF(*)B	T41S0B155(*)016(**)	(*)	16V1.5uF	B	0.50	4.00	5.00	7	5	6	7
2.2	CA41S-16V2.2uF(*)B	T41S0B225(*)016(**)	(*)	16V2.2uF	B	0.50	4.00	5.00	7	5	6	7
3.3	CA41S-16V3.3uF(*)B	T41S0B335(*)016(**)	(*)	16V3.3uF	B	0.50	4.00	5.00	7	5	6	7
4.7	CA41S-16V4.7uF(*)B	T41S0B475(*)016(**)	(*)	16V4.7uF	B	0.75	6.02	7.52	7	5	6	7
6.8	CA41S-16V6.8uF(*)C	T41S0C685(*)016(**)	(*)	16V6.8uF	C	1.09	8.70	10.88	7	5	6	7
10	CA41S-16V10uF(*)C	T41S0C106(*)016(**)	(*)	16V10uF	C	1.60	12.80	16.00	7	5	6	7
15	CA41S-16V15uF(*)C	T41S0C156(*)016(**)	(*)	16V15uF	C	2.40	19.20	24.00	7	5	6	7
22	CA41S-16V22uF(*)D	T41S0D226(*)016(**)	(*)	16V22uF	D	3.52	28.16	35.20	7	5	6	7
33	CA41S-16V33uF(*)D	T41S0D336(*)016(**)	(*)	16V33uF	D	5.28	42.24	52.80	7	5	6	7
47	CA41S-16V47uF(*)D	T41S0D476(*)016(**)	(*)	16V47uF	D	7.52	60.16	75.20	7	5	6	7
68	CA41S-16V68uF(*)E	T41S0E686(*)016(**)	(*)	16V68uF	E	10.88	87.04	108.80	7	5	6	7
100	CA41S-16V100uF(*)E	T41S0E107(*)016(**)	(*)	16V100uF	E	16.00	128.00	160.00	8	7	7	8
150	CA41S-16V150uF(*)E	T41S0E157(*)016(**)	(*)	16V150uF	E	24.00	192.00	240.00	8	7	7	8
220	CA41S-16V220uF(*)F	T41S0F227(*)016(**)	(*)	16V220uF	F	35.20	281.60	352.00	8	7	7	8
25 Volt 额定电压 +85°C时 (16 Volt 额定电压 +125°C时)												
0.47	CA41S-25V0.47uF(*)B	T41S0B474(*)025(**)	(*)	25V0.47uF	B	0.50	4.00	5.00	6	3	5	6
0.68	CA41S-25V0.68uF(*)B	T41S0B684(*)025(**)	(*)	25V0.68uF	B	0.50	4.00	5.00	6	3	5	6
1	CA41S-25V1uF(*)B	T41S0B105(*)025(**)	(*)	25V1uF	B	0.50	4.00	5.00	6	3	5	6
1.5	CA41S-25V1.5uF(*)B	T41S0B155(*)025(**)	(*)	25V1.5uF	B	0.50	4.00	5.00	7	5	6	7
2.2	CA41S-25V2.2uF(*)B	T41S0B225(*)025(**)	(*)	25V2.2uF	B	0.55	4.40	5.50	7	5	6	7
3.3	CA41S-25V3.3uF(*)B	T41S0B335(*)025(**)	(*)	25V3.3uF	B	0.83	6.60	8.25	7	5	6	7
4.7	CA41S-25V4.7uF(*)C	T41S0C475(*)025(**)	(*)	25V4.7uF	C	1.18	9.40	11.75	7	5	6	7
6.8	CA41S-25V6.8uF(*)C	T41S0C685(*)025(**)	(*)	25V6.8uF	C	1.70	13.60	17.00	7	5	6	7
10	CA41S-25V10uF(*)C	T41S0C106(*)025(**)	(*)	25V10uF	C	2.50	20.00	25.00	7	5	6	7
15	CA41S-25V15uF(*)D	T41S0D156(*)025(**)	(*)	25V15uF	D	3.75	30.00	37.50	7	5	6	7
22	CA41S-25V22uF(*)D	T41S0D226(*)025(**)	(*)	25V22uF	D	5.50	44.00	55.00	7	5	6	7
33	CA41S-25V33uF(*)D	T41S0D336(*)025(**)	(*)	25V33uF	D	8.25	66.00	82.50	7	5	6	7
47	CA41S-25V47uF(*)E	T41S0E476(*)025(**)	(*)	25V47uF	E	11.75	94.00	117.50	7	5	6	7
68	CA41S-25V68uF(*)E	T41S0E686(*)025(**)	(*)	25V68uF	E	17.00	136.00	170.00	7	5	6	7
100	CA41S-25V100uF(*)F	T41S0F107(*)025(**)	(*)	25V100uF	F	25.00	200.00	250.00	8	7	7	8
35 Volt 额定电压 +85°C时 (20 Volt 额定电压 +125°C时)												
0.1	CA41S-35V0.1uF(*)B	T41S0B104(*)035(**)	(*)	35V0.1uF	B	0.50	4.00	5.00	6	3	5	6
0.15	CA41S-35V0.15uF(*)B	T41S0B154(*)035(**)	(*)	35V0.15uF	B	0.50	4.00	5.00	6	3	5	6
0.22	CA41S-35V0.22uF(*)B	T41S0B224(*)035(**)	(*)	35V0.22uF	B	0.50	4.00	5.00	6	3	5	6
0.33	CA41S-35V0.33uF(*)B	T41S0B334(*)035(**)	(*)	35V0.33uF	B	0.50	4.00	5.00	6	3	5	6
0.47	CA41S-35V0.47uF(*)B	T41S0B474(*)035(**)	(*)	35V0.47uF	B	0.50	4.00	5.00	6	3	5	6
0.68	CA41S-35V0.68uF(*)B	T41S0B684(*)035(**)	(*)	35V0.68uF	B	0.50	4.00	5.00	6	3	5	6
1	CA41S-35V1uF(*)B	T41S0B105(*)035(**)	(*)	35V1uF	B	0.50	4.00	5.00	6	3	5	6

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25°C (uA)	漏电流 +85°C (uA)	漏电流 +125°C (uA)	损耗角正切 -55°C 120Hz (%)	损耗角正切 +25°C 120Hz (%)	损耗角正切 +85°C 120Hz (%)	损耗角正切 +125°C 120Hz (%)
1.5	CA41S-35V1.5uF(*)C	T41S0C155(*)035(**)	(*)	35V1.5uF	C	0.50	4.00	5.00	7	5	6	7
2.2	CA41S-35V2.2uF(*)C	T41S0C225(*)035(**)	(*)	35V2.2uF	C	0.77	6.16	7.70	7	5	6	7
3.3	CA41S-35V3.3uF(*)C	T41S0C335(*)035(**)	(*)	35V3.3uF	C	1.16	9.24	11.55	7	5	6	7
4.7	CA41S-35V4.7uF(*)D	T41S0D475(*)035(**)	(*)	35V4.7uF	D	1.65	13.16	16.45	7	5	6	7
6.8	CA41S-35V6.8uF(*)D	T41S0D685(*)035(**)	(*)	35V6.8uF	D	2.38	19.04	23.80	7	5	6	7
10	CA41S-35V10uF(*)D	T41S0D106(*)035(**)	(*)	35V10uF	D	3.50	28.00	35.00	7	5	6	7
15	CA41S-35V15uF(*)E	T41S0E156(*)035(**)	(*)	35V15uF	E	5.25	42.00	52.50	7	5	6	7
22	CA41S-35V22uF(*)E	T41S0E226(*)035(**)	(*)	35V22uF	E	7.70	61.60	77.00	7	5	6	7
33	CA41S-35V33uF(*)F	T41S0F336(*)035(**)	(*)	35V33uF	F	11.55	92.40	115.50	7	5	6	7
47	CA41S-35V47uF(*)F	T41S0F476(*)035(**)	(*)	35V47uF	F	16.45	131.60	164.50	7	5	6	7
40 Volt 额定电压 +85°C时 (25 Volt 额定电压 +125°C时)												
0.1	CA41S-40V0.1uF(*)B	T41S0B104(*)040(**)	(*)	40V0.1uF	B	0.50	4.00	5.00	6	3	5	6
0.15	CA41S-40V0.15uF(*)B	T41S0B154(*)040(**)	(*)	40V0.15uF	B	0.50	4.00	5.00	6	3	5	6
0.22	CA41S-40V0.22uF(*)B	T41S0B224(*)040(**)	(*)	40V0.22uF	B	0.50	4.00	5.00	6	3	5	6
0.33	CA41S-40V0.33uF(*)B	T41S0B334(*)040(**)	(*)	40V0.33uF	B	0.50	4.00	5.00	6	3	5	6
0.47	CA41S-40V0.47uF(*)B	T41S0B474(*)040(**)	(*)	40V0.47uF	B	0.50	4.00	5.00	6	3	5	6
0.68	CA41S-40V0.68uF(*)B	T41S0B684(*)040(**)	(*)	40V0.68uF	B	0.50	4.00	5.00	6	3	5	6
1	CA41S-40V1uF(*)C	T41S0C105(*)040(**)	(*)	40V1uF	C	0.50	4.00	5.00	6	3	5	6
1.5	CA41S-40V1.5uF(*)C	T41S0C155(*)040(**)	(*)	40V1.5uF	C	0.50	4.00	5.00	7	5	6	7
2.2	CA41S-40V2.2uF(*)C	T41S0C225(*)040(**)	(*)	40V2.2uF	C	0.88	7.04	8.80	7	5	6	7
3.3	CA41S-40V3.3uF(*)D	T41S0D335(*)040(**)	(*)	40V3.3uF	D	1.32	10.56	13.20	7	5	6	7
4.7	CA41S-40V4.7uF(*)D	T41S0D475(*)040(**)	(*)	40V4.7uF	D	1.88	15.04	18.80	7	5	6	7
6.8	CA41S-40V6.8uF(*)E	T41S0E685(*)040(**)	(*)	40V6.8uF	E	2.72	21.76	27.20	7	5	6	7
10	CA41S-40V10uF(*)E	T41S0E106(*)040(**)	(*)	40V10uF	E	4.00	32.00	40.00	7	5	6	7
15	CA41S-40V15uF(*)E	T41S0E156(*)040(**)	(*)	40V15uF	E	6.00	48.00	60.00	7	5	6	7
22	CA41S-40V22uF(*)F	T41S0F226(*)040(**)	(*)	40V22uF	F	8.80	70.40	88.00	7	5	6	7
33	CA41S-40V33uF(*)F	T41S0F336(*)040(**)	(*)	40V33uF	F	13.20	105.60	132.00	7	5	6	7
50 Volt 额定电压 +85°C时 (32 Volt 额定电压 +125°C时)												
0.015	CA41S-50V0.015uF(*)B	T41S0B153(*)050(**)	(*)	50V0.015uF	B	0.50	4.00	5.00	6	3	5	6
0.022	CA41S-50V0.022uF(*)B	T41S0B223(*)050(**)	(*)	50V0.022uF	B	0.50	4.00	5.00	6	3	5	6
0.033	CA41S-50V0.033uF(*)B	T41S0B333(*)050(**)	(*)	50V0.033uF	B	0.50	4.00	5.00	6	3	5	6
0.047	CA41S-50V0.047uF(*)B	T41S0B473(*)050(**)	(*)	50V0.047uF	B	0.50	4.00	5.00	6	3	5	6
0.068	CA41S-50V0.068uF(*)B	T41S0B683(*)050(**)	(*)	50V0.068uF	B	0.50	4.00	5.00	6	3	5	6
0.1	CA41S-50V0.1uF(*)B	T41S0B104(*)050(**)	(*)	50V0.1uF	B	0.50	4.00	5.00	6	3	5	6
0.15	CA41S-50V0.15uF(*)B	T41S0B154(*)050(**)	(*)	50V0.15uF	B	0.50	4.00	5.00	6	3	5	6
0.22	CA41S-50V0.22uF(*)B	T41S0B224(*)050(**)	(*)	50V0.22uF	B	0.50	4.00	5.00	6	3	5	6
0.33	CA41S-50V0.33uF(*)B	T41S0B334(*)050(**)	(*)	50V0.33uF	B	0.50	4.00	5.00	6	3	5	6
0.47	CA41S-50V0.47uF(*)C	T41S0C474(*)050(**)	(*)	50V0.47uF	C	0.50	4.00	5.00	6	3	5	6
0.68	CA41S-50V0.68uF(*)C	T41S0C684(*)050(**)	(*)	50V0.68uF	C	0.50	4.00	5.00	6	3	5	6
1	CA41S-50V1uF(*)C	T41S0C105(*)050(**)	(*)	50V1uF	C	0.50	4.00	5.00	6	3	5	6
1.5	CA41S-50V1.5uF(*)D	T41S0D155(*)050(**)	(*)	50V1.5uF	D	0.50	4.00	5.00	7	5	6	7
2.2	CA41S-50V2.2uF(*)D	T41S0D225(*)050(**)	(*)	50V2.2uF	D	1.10	8.80	11.00	7	5	6	7
3.3	CA41S-50V3.3uF(*)D	T41S0D335(*)050(**)	(*)	50V3.3uF	D	1.65	13.20	16.50	7	5	6	7
4.7	CA41S-50V4.7uF(*)E	T41S0E475(*)050(**)	(*)	50V4.7uF	E	2.35	18.80	23.50	7	5	6	7
6.8	CA41S-50V6.8uF(*)E	T41S0E685(*)050(**)	(*)	50V6.8uF	E	3.40	27.20	34.00	7	5	6	7
10	CA41S-50V10uF(*)E	T41S0E106(*)050(**)	(*)	50V10uF	E	5.00	40.00	50.00	7	5	6	7
15	CA41S-50V15uF(*)F	T41S0F156(*)050(**)	(*)	50V15uF	F	7.50	60.00	75.00	7	5	6	7
22	CA41S-50V22uF(*)F	T41S0F226(*)050(**)	(*)	50V22uF	F	11.00	88.00	110.00	7	5	6	7
63 Volt 额定电压 +85°C时 (40 Volt 额定电压 +125°C时)												
0.015	CA41S-63V0.015uF(*)B	T41S0B153(*)063(**)	(*)	63V0.015uF	B	0.50	4.00	5.00	6	3	5	6
0.022	CA41S-63V0.022uF(*)B	T41S0B223(*)063(**)	(*)	63V0.022uF	B	0.50	4.00	5.00	6	3	5	6
0.033	CA41S-63V0.033uF(*)B	T41S0B333(*)063(**)	(*)	63V0.033uF	B	0.50	4.00	5.00	6	3	5	6
0.047	CA41S-63V0.047uF(*)B	T41S0B473(*)063(**)	(*)	63V0.047uF	B	0.50	4.00	5.00	6	3	5	6
0.068	CA41S-63V0.068uF(*)B	T41S0B683(*)063(**)	(*)	63V0.068uF	B	0.50	4.00	5.00	6	3	5	6
0.1	CA41S-63V0.1uF(*)B	T41S0B104(*)063(**)	(*)	63V0.1uF	B	0.50	4.00	5.00	6	3	5	6
0.15	CA41S-63V0.15uF(*)B	T41S0B154(*)063(**)	(*)	63V0.15uF	B	0.50	4.00	5.00	6	3	5	6
0.22	CA41S-63V0.22uF(*)B	T41S0B224(*)063(**)	(*)	63V0.22uF	B	0.50	4.00	5.00	6	3	5	6
0.33	CA41S-63V0.33uF(*)C	T41S0C334(*)063(**)	(*)	63V0.33uF	C	0.50	4.00	5.00	6	3	5	6
0.47	CA41S-63V0.47uF(*)C	T41S0C474(*)063(**)	(*)	63V0.47uF	C	0.50	4.00	5.00	6	3	5	6
0.68	CA41S-63V0.68uF(*)C	T41S0C684(*)063(**)	(*)	63V0.68uF	C	0.50	4.00	5.00	6	3	5	6
1	CA41S-63V1uF(*)D	T41S0D105(*)063(**)	(*)	63V1uF	D	0.63	5.04	6.30	6	3	5	6
1.5	CA41S-63V1.5uF(*)D	T41S0D155(*)063(**)	(*)	63V1.5uF	D	0.50	4.00	5.00	7	5	6	7
2.2	CA41S-63V2.2uF(*)D	T41S0D225(*)063(**)	(*)	63V2.2uF	D	1.39	11.09	13.86	7	5	6	7
3.3	CA41S-63V3.3uF(*)E	T41S0E335(*)063(**)	(*)	63V3.3uF	E	2.08	16.63	20.79	7	5	6	7
4.7	CA41S-63V4.7uF(*)E	T41S0E475(*)063(**)	(*)	63V4.7uF	E	2.96	23.69	29.61	7	5	6	7
6.8	CA41S-63V6.8uF(*)E	T41S0E685(*)063(**)	(*)	63V6.8uF	E	4.28	34.27	42.84	7	5	6	7
10	CA41S-63V10uF(*)E	T41S0E106(*)063(**)	(*)	63V10uF	E	6.30	50.40	63.00	7	5	6	7
15	CA41S-63V15uF(*)F	T41S0F156(*)063(**)	(*)	63V15uF	F	9.45	75.60	94.50	7	5	6	7

(*)：电容量允许偏差：±10%，±20%

如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。