

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	漏电流 +125℃(uA)	损耗角正切 -55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
4 Volt 额定电压 +85℃时 (2.5 Volt 额定电压 +125℃时)												
3.3	CA43-4V3.3uF(*)B	T4300B335(*)004(**)	(*)	4V3.3uF	B	0.5	4.0	5.0	6	3	3	4
4.7	CA43-4V4.7uF(*)B	T4300B475(*)004(**)	(*)	4V4.7uF	B	0.5	4.0	5.0	8	4	5	6
6.8	CA43-4V6.8uF(*)B	T4300B685(*)004(**)	(*)	4V6.8uF	B	0.5	4.0	5.0	8	4	5	6
10	CA43-4V10uF(*)C	T4300C106(*)004(**)	(*)	4V10uF	C	0.5	4.0	5.0	8	4	5	6
10	CA43-4V10uF(*)B	T4300B106(*)004(**)	(*)	4V10uF	B	0.5	4.0	5.0	8	4	5	6
15	CA43-4V15uF(*)C	T4300C156(*)004(**)	(*)	4V15uF	C	0.6	4.8	6.0	8	4	5	6
15	CA43-4V15uF(*)B	T4300B156(*)004(**)	(*)	4V15uF	B	0.6	4.8	6.0	8	4	5	6
22	CA43-4V22uF(*)C	T4300C226(*)004(**)	(*)	4V22uF	C	0.9	7.0	8.8	8	4	5	6
22	CA43-4V22uF(*)B	T4300B226(*)004(**)	(*)	4V22uF	B	0.9	7.0	8.8	8	4	5	6
33	CA43-4V33uF(*)D	T4300D336(*)004(**)	(*)	4V33uF	D	1.3	10.6	13.2	8	4	5	6
33	CA43-4V33uF(*)C	T4300C336(*)004(**)	(*)	4V33uF	C	1.3	10.6	13.2	8	4	5	6
47	CA43-4V47uF(*)D	T4300D476(*)004(**)	(*)	4V47uF	D	1.9	15.0	18.8	8	5	7	8
47	CA43-4V47uF(*)C	T4300C476(*)004(**)	(*)	4V47uF	C	1.9	15.0	18.8	8	5	7	8
68	CA43-4V68uF(*)E	T4300E686(*)004(**)	(*)	4V68uF	E	2.7	21.8	27.2	8	5	7	8
68	CA43-4V68uF(*)D	T4300D686(*)004(**)	(*)	4V68uF	D	2.7	21.8	27.2	8	5	7	8
100	CA43-4V100uF(*)F	T4300F107(*)004(**)	(*)	4V100uF	F	4.0	32.0	40.0	10	7	9	10
100	CA43-4V100uF(*)E	T4300E107(*)004(**)	(*)	4V100uF	E	4.0	32.0	40.0	10	7	9	10
100	CA43-4V100uF(*)D	T4300D107(*)004(**)	(*)	4V100uF	D	4.0	32.0	40.0	10	7	9	10
150	CA43-4V150uF(*)F	T4300F157(*)004(**)	(*)	4V150uF	F	6.0	48.0	60.0	10	7	9	10
150	CA43-4V150uF(*)E	T4300E157(*)004(**)	(*)	4V150uF	E	6.0	48.0	60.0	10	7	9	10
150	CA43-4V150uF(*)D	T4300D157(*)004(**)	(*)	4V150uF	D	6.0	48.0	60.0	10	7	9	10
220	CA43-4V220uF(*)F	T4300F227(*)004(**)	(*)	4V220uF	F	8.8	70.4	88.0	10	7	9	10
220	CA43-4V220uF(*)E	T4300E227(*)004(**)	(*)	4V220uF	E	8.8	70.4	88.0	10	7	9	10
220	CA43-4V220uF(*)D	T4300D227(*)004(**)	(*)	4V220uF	D	8.8	70.4	88.0	10	7	9	10
330	CA43-4V330uF(*)F	T4300F337(*)004(**)	(*)	4V330uF	F	13.2	105.6	132.0	12	10	12	12
330	CA43-4V330uF(*)E	T4300E337(*)004(**)	(*)	4V330uF	E	13.2	105.6	132.0	12	10	12	12
470	CA43-4V470uF(*)F	T4300F477(*)004(**)	(*)	4V470uF	F	18.8	150.4	188.0	12	10	12	12
680	CA43-4V680uF(*)F	T4300F687(*)004(**)	(*)	4V680uF	F	27.2	217.6	272.0	12	10	12	12
6.3 Volt 额定电压 +85℃时 (4 Volt 额定电压 +125℃时)												
2.2	CA43-6.3V2.2uF(*)B	T4300B225(*)006(**)	(*)	6.3V2.2uF	B	0.5	4.0	5.0	6	3	3	4
3.3	CA43-6.3V3.3uF(*)B	T4300B335(*)006(**)	(*)	6.3V3.3uF	B	0.5	4.0	5.0	6	3	3	4
4.7	CA43-6.3V4.7uF(*)B	T4300B475(*)006(**)	(*)	6.3V4.7uF	B	0.5	4.0	5.0	8	4	5	6
6.8	CA43-6.3V6.8uF(*)C	T4300C685(*)006(**)	(*)	6.3V6.8uF	C	0.5	4.0	5.0	8	4	5	6
6.8	CA43-6.3V6.8uF(*)B	T4300B685(*)006(**)	(*)	6.3V6.8uF	B	0.5	4.0	5.0	8	4	5	6
10	CA43-6.3V10uF(*)C	T4300C106(*)006(**)	(*)	6.3V10uF	C	0.6	5.0	6.3	8	4	5	6
10	CA43-6.3V10uF(*)B	T4300B106(*)006(**)	(*)	6.3V10uF	B	0.6	5.0	6.3	8	4	5	6
15	CA43-6.3V15uF(*)C	T4300C156(*)006(**)	(*)	6.3V15uF	C	0.9	7.6	9.5	8	4	5	6
15	CA43-6.3V15uF(*)B	T4300B156(*)006(**)	(*)	6.3V15uF	B	0.9	7.6	9.5	8	4	5	6
22	CA43-6.3V22uF(*)D	T4300D226(*)006(**)	(*)	6.3V22uF	D	1.4	11.1	13.9	8	4	5	6
22	CA43-6.3V22uF(*)C	T4300C226(*)006(**)	(*)	6.3V22uF	C	1.4	11.1	13.9	8	4	5	6
33	CA43-6.3V33uF(*)D	T4300D336(*)006(**)	(*)	6.3V33uF	D	2.1	16.6	20.8	8	4	5	6
33	CA43-6.3V33uF(*)C	T4300C336(*)006(**)	(*)	6.3V33uF	C	2.1	16.6	20.8	8	4	5	6
47	CA43-6.3V47uF(*)E	T4300E476(*)006(**)	(*)	6.3V47uF	E	3.0	23.7	29.6	8	5	7	8
47	CA43-6.3V47uF(*)D	T4300D476(*)006(**)	(*)	6.3V47uF	D	3.0	23.7	29.6	8	5	7	8
68	CA43-6.3V68uF(*)E	T4300E686(*)006(**)	(*)	6.3V68uF	E	4.3	34.3	42.8	8	5	7	8
68	CA43-6.3V68uF(*)D	T4300D686(*)006(**)	(*)	6.3V68uF	D	4.3	34.3	42.8	8	5	7	8
100	CA43-6.3V100uF(*)F	T4300F107(*)006(**)	(*)	6.3V100uF	F	6.3	50.4	63.0	10	7	9	10
100	CA43-6.3V100uF(*)E	T4300E107(*)006(**)	(*)	6.3V100uF	E	6.3	50.4	63.0	10	7	9	10
100	CA43-6.3V100uF(*)D	T4300D107(*)006(**)	(*)	6.3V100uF	D	6.3	50.4	63.0	10	7	9	10
150	CA43-6.3V150uF(*)F	T4300F157(*)006(**)	(*)	6.3V150uF	F	9.5	75.6	94.5	10	7	9	10
150	CA43-6.3V150uF(*)E	T4300E157(*)006(**)	(*)	6.3V150uF	E	9.5	75.6	94.5	10	7	9	10
150	CA43-6.3V150uF(*)D	T4300D157(*)006(**)	(*)	6.3V150uF	D	9.5	75.6	94.5	10	7	9	10
220	CA43-6.3V220uF(*)F	T4300F227(*)006(**)	(*)	6.3V220uF	F	13.9	110.9	138.6	10	7	9	10
220	CA43-6.3V220uF(*)E	T4300E227(*)006(**)	(*)	6.3V220uF	E	13.9	110.9	138.6	10	7	9	10
330	CA43-6.3V330uF(*)F	T4300F337(*)006(**)	(*)	6.3V330uF	F	20.8	166.3	207.9	12	10	12	12
330	CA43-6.3V330uF(*)E	T4300E337(*)006(**)	(*)	6.3V330uF	E	20.8	166.3	207.9	12	10	12	12
470	CA43-6.3V470uF(*)F	T4300F477(*)006(**)	(*)	6.3V470uF	F	29.6	236.9	296.1	12	10	12	12
10 Volt 额定电压 +85℃时 (6.3 Volt 额定电压 +125℃时)												
1.5	CA43-10V1.5uF(*)B	T4300B155(*)010(**)	(*)	10V1.5uF	B	0.5	4.0	5.0	6	3	3	4
2.2	CA43-10V2.2uF(*)B	T4300B225(*)010(**)	(*)	10V2.2uF	B	0.5	4.0	5.0	6	3	3	4
3.3	CA43-10V3.3uF(*)B	T4300B335(*)010(**)	(*)	10V3.3uF	B	0.5	4.0	5.0	6	3	3	4
4.7	CA43-10V4.7uF(*)C	T4300C475(*)010(**)	(*)	10V4.7uF	C	0.5	4.0	5.0	8	4	5	6
4.7	CA43-10V4.7uF(*)B	T4300B475(*)010(**)	(*)	10V4.7uF	B	0.5	4.0	5.0	8	4	5	6
6.8	CA43-10V6.8uF(*)C	T4300C685(*)010(**)	(*)	10V6.8uF	C	0.7	5.4	6.8	8	4	5	6
6.8	CA43-10V6.8uF(*)B	T4300B685(*)010(**)	(*)	10V6.8uF	B	0.7	5.4	6.8	8	4	5	6
10	CA43-10V10uF(*)C	T4300C106(*)010(**)	(*)	10V10uF	C	1.0	8.0	10.0	8	4	5	6
10	CA43-10V10uF(*)B	T4300B106(*)010(**)	(*)	10V10uF	B	1.0	8.0	10.0	8	4	5	6
15	CA43-10V15uF(*)D	T4300D156(*)010(**)	(*)	10V15uF	D	1.5	12.0	15.0	8	4	5	6
15	CA43-10V15uF(*)C	T4300C156(*)010(**)	(*)	10V15uF	C	1.5	12.0	15.0	8	4	5	6
22	CA43-10V22uF(*)D	T4300D226(*)010(**)	(*)	10V22uF	D	2.2	17.6	22.0	8	4	5	6
22	CA43-10V22uF(*)C	T4300C226(*)010(**)	(*)	10V22uF	C	2.2	17.6	22.0	8	4	5	6
33	CA43-10V33uF(*)E	T4300E336(*)010(**)	(*)	10V33uF	E	3.3	26.4	33.0	8	4	5	6

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	漏电流 +125℃(uA)	损耗角正切 -55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
33	CA43-10V33uF(*)D	T4300D336(*)010(**)	(*)	10V33uF	D	3.3	26.4	33.0	8	4	5	6
47	CA43-10V47uF(*)E	T4300E476(*)010(**)	(*)	10V47uF	E	4.7	37.6	47.0	8	5	7	8
47	CA43-10V47uF(*)D	T4300D476(*)010(**)	(*)	10V47uF	D	4.7	37.6	47.0	8	5	7	8
68	CA43-10V68uF(*)F	T4300F686(*)010(**)	(*)	10V68uF	F	6.8	54.4	68.0	8	5	7	8
68	CA43-10V68uF(*)E	T4300E686(*)010(**)	(*)	10V68uF	E	6.8	54.4	68.0	8	5	7	8
68	CA43-10V68uF(*)D	T4300D686(*)010(**)	(*)	10V68uF	D	6.8	54.4	68.0	8	5	7	8
100	CA43-10V100uF(*)F	T4300F107(*)010(**)	(*)	10V100uF	F	10.0	80.0	100.0	10	7	9	10
100	CA43-10V100uF(*)E	T4300E107(*)010(**)	(*)	10V100uF	E	10.0	80.0	100.0	10	7	9	10
100	CA43-10V100uF(*)D	T4300D107(*)010(**)	(*)	10V100uF	D	10.0	80.0	100.0	10	7	9	10
150	CA43-10V150uF(*)F	T4300F157(*)010(**)	(*)	10V150uF	F	15.0	120.0	150.0	10	7	9	10
150	CA43-10V150uF(*)E	T4300E157(*)010(**)	(*)	10V150uF	E	15.0	120.0	150.0	10	7	9	10
150	CA43-10V150uF(*)D	T4300D157(*)010(**)	(*)	10V150uF	D	15.0	120.0	150.0	10	7	9	10
220	CA43-10V220uF(*)F	T4300F227(*)010(**)	(*)	10V220uF	F	22.0	176.0	220.0	10	7	9	10
220	CA43-10V220uF(*)E	T4300E227(*)010(**)	(*)	10V220uF	E	22.0	176.0	220.0	10	7	9	10
330	CA43-10V330uF(*)F	T4300F337(*)010(**)	(*)	10V330uF	F	33.0	264.0	330.0	12	10	12	12
16 Volt 额定电压 +85℃时 (10 Volt 额定电压 +125℃时)												
1	CA43-16V1uF(*)B	T4300B105(*)016(**)	(*)	16V1uF	B	0.5	4.0	5.0	6	3	3	4
1.5	CA43-16V1.5uF(*)B	T4300B155(*)016(**)	(*)	16V1.5uF	B	0.5	4.0	5.0	6	3	3	4
2.2	CA43-16V2.2uF(*)B	T4300B225(*)016(**)	(*)	16V2.2uF	B	0.5	4.0	5.0	6	3	3	4
3.3	CA43-16V3.3uF(*)C	T4300C335(*)016(**)	(*)	16V3.3uF	C	0.5	4.2	5.3	6	3	3	4
3.3	CA43-16V3.3uF(*)B	T4300B335(*)016(**)	(*)	16V3.3uF	B	0.5	4.2	5.3	6	3	3	4
4.7	CA43-16V4.7uF(*)C	T4300C475(*)016(**)	(*)	16V4.7uF	C	0.8	6.0	7.5	8	4	5	6
4.7	CA43-16V4.7uF(*)B	T4300B475(*)016(**)	(*)	16V4.7uF	B	0.8	6.0	7.5	8	4	5	6
6.8	CA43-16V6.8uF(*)C	T4300C685(*)016(**)	(*)	16V6.8uF	C	1.1	8.7	10.9	8	4	5	6
6.8	CA43-16V6.8uF(*)B	T4300B685(*)016(**)	(*)	16V6.8uF	B	1.1	8.7	10.9	8	4	5	6
10	CA43-16V10uF(*)D	T4300D106(*)016(**)	(*)	16V10uF	D	1.6	12.8	16.0	8	4	5	6
10	CA43-16V10uF(*)C	T4300C106(*)016(**)	(*)	16V10uF	C	1.6	12.8	16.0	8	4	5	6
15	CA43-16V15uF(*)D	T4300D156(*)016(**)	(*)	16V15uF	D	2.4	19.2	24.0	8	4	5	6
22	CA43-16V22uF(*)E	T4300E226(*)016(**)	(*)	16V22uF	E	3.5	28.2	35.2	8	4	5	6
22	CA43-16V22uF(*)D	T4300D226(*)016(**)	(*)	16V22uF	D	3.5	28.2	35.2	8	4	5	6
33	CA43-16V33uF(*)E	T4300E336(*)016(**)	(*)	16V33uF	E	5.3	42.2	52.8	8	4	5	6
33	CA43-16V33uF(*)D	T4300D336(*)016(**)	(*)	16V33uF	D	5.3	42.2	52.8	8	4	5	6
47	CA43-16V47uF(*)F	T4300F476(*)016(**)	(*)	16V47uF	F	7.5	60.2	75.2	8	5	7	8
47	CA43-16V47uF(*)E	T4300E476(*)016(**)	(*)	16V47uF	E	7.5	60.2	75.2	8	5	7	8
47	CA43-16V47uF(*)D	T4300D476(*)016(**)	(*)	16V47uF	D	7.5	60.2	75.2	8	5	7	8
68	CA43-16V68uF(*)F	T4300F686(*)016(**)	(*)	16V68uF	F	10.9	87.0	108.8	8	5	7	8
68	CA43-16V68uF(*)E	T4300E686(*)016(**)	(*)	16V68uF	E	10.9	87.0	108.8	8	5	7	8
68	CA43-16V68uF(*)D	T4300D686(*)016(**)	(*)	16V68uF	D	10.9	87.0	108.8	8	5	7	8
100	CA43-16V100uF(*)F	T4300F107(*)016(**)	(*)	16V100uF	F	16.0	128.0	160.0	10	7	9	10
100	CA43-16V100uF(*)E	T4300E107(*)016(**)	(*)	16V100uF	E	16.0	128.0	160.0	10	7	9	10
150	CA43-16V150uF(*)F	T4300F157(*)016(**)	(*)	16V150uF	F	24.0	192.0	240.0	10	7	9	10
220	CA43-16V220uF(*)F	T4300F227(*)016(**)	(*)	16V220uF	F	35.2	281.6	352.0	10	7	9	10
20 Volt 额定电压 +85℃时 (13 Volt 额定电压 +125℃时)												
0.47	CA43-20V0.47uF(*)B	T4300B474(*)020(**)	(*)	20V0.47uF	B	0.5	4.0	5.0	6	3	3	4
0.68	CA43-20V0.68uF(*)B	T4300B684(*)020(**)	(*)	20V0.68uF	B	0.5	4.0	5.0	6	3	3	4
1	CA43-20V1uF(*)B	T4300B105(*)020(**)	(*)	20V1uF	B	0.5	4.0	5.0	6	3	3	4
1.5	CA43-20V1.5uF(*)B	T4300B155(*)020(**)	(*)	20V1.5uF	B	0.5	4.0	5.0	6	3	3	4
2.2	CA43-20V2.2uF(*)C	T4300C225(*)020(**)	(*)	20V2.2uF	C	0.5	4.0	5.0	6	3	3	4
2.2	CA43-20V2.2uF(*)B	T4300B225(*)020(**)	(*)	20V2.2uF	B	0.5	4.0	5.0	6	3	3	4
3.3	CA43-20V3.3uF(*)C	T4300C335(*)020(**)	(*)	20V3.3uF	C	0.7	5.3	6.6	6	3	3	4
3.3	CA43-20V3.3uF(*)B	T4300B335(*)020(**)	(*)	20V3.3uF	B	0.7	5.3	6.6	6	3	3	4
4.7	CA43-20V4.7uF(*)C	T4300C475(*)020(**)	(*)	20V4.7uF	C	0.9	7.5	9.4	8	4	5	6
4.7	CA43-20V4.7uF(*)B	T4300B475(*)020(**)	(*)	20V4.7uF	B	0.9	7.5	9.4	8	4	5	6
6.8	CA43-20V6.8uF(*)D	T4300D685(*)020(**)	(*)	20V6.8uF	D	1.4	10.9	13.6	8	4	5	6
6.8	CA43-20V6.8uF(*)C	T4300C685(*)020(**)	(*)	20V6.8uF	C	1.4	10.9	13.6	8	4	5	6
10	CA43-20V10uF(*)D	T4300D106(*)020(**)	(*)	20V10uF	D	2.0	16.0	20.0	8	4	5	6
10	CA43-20V10uF(*)C	T4300C106(*)020(**)	(*)	20V10uF	C	2.0	16.0	20.0	8	4	5	6
15	CA43-20V15uF(*)E	T4300E156(*)020(**)	(*)	20V15uF	E	3.0	24.0	30.0	8	4	5	6
15	CA43-20V15uF(*)D	T4300D156(*)020(**)	(*)	20V15uF	D	3.0	24.0	30.0	8	4	5	6
22	CA43-20V22uF(*)E	T4300E226(*)020(**)	(*)	20V22uF	E	4.4	35.2	44.0	8	4	5	6
22	CA43-20V22uF(*)D	T4300D226(*)020(**)	(*)	20V22uF	D	4.4	35.2	44.0	8	4	5	6
33	CA43-20V33uF(*)F	T4300F336(*)020(**)	(*)	20V33uF	F	6.6	52.8	66.0	8	4	5	6
33	CA43-20V33uF(*)E	T4300E336(*)020(**)	(*)	20V33uF	E	6.6	52.8	66.0	8	4	5	6
33	CA43-20V33uF(*)D	T4300D336(*)020(**)	(*)	20V33uF	D	6.6	52.8	66.0	8	4	5	6
47	CA43-20V47uF(*)F	T4300F476(*)020(**)	(*)	20V47uF	F	9.4	75.2	94.0	8	5	7	8
47	CA43-20V47uF(*)E	T4300E476(*)020(**)	(*)	20V47uF	E	9.4	75.2	94.0	8	5	7	8
47	CA43-20V47uF(*)D	T4300D476(*)020(**)	(*)	20V47uF	D	9.4	75.2	94.0	8	5	7	8
68	CA43-20V68uF(*)F	T4300F686(*)020(**)	(*)	20V68uF	F	13.6	108.8	136.0	8	5	7	8
68	CA43-20V68uF(*)E	T4300E686(*)020(**)	(*)	20V68uF	E	13.6	108.8	136.0	8	5	7	8
100	CA43-20V100uF(*)F	T4300F107(*)020(**)	(*)	20V100uF	F	20.0	160.0	200.0	10	7	9	10
100	CA43-20V100uF(*)E	T4300E107(*)020(**)	(*)	20V100uF	E	20.0	160.0	200.0	10	7	9	10
150	CA43-20V150uF(*)F	T4300F157(*)020(**)	(*)	20V150uF	F	30.0	240.0	300.0	10	7	9	10
25 Volt 额定电压 +85℃时 (16 Volt 额定电压 +125℃时)												

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	漏电流 +125℃(uA)	损耗角正切 -55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
0.33	CA43-25V0.33uF(*)B	T4300B334(*)025(**)	(*)	25V0.33uF	B	0.5	4.0	5.0	6	3	3	4
0.47	CA43-25V0.47uF(*)B	T4300B474(*)025(**)	(*)	25V0.47uF	B	0.5	4.0	5.0	6	3	3	4
0.68	CA43-25V0.68uF(*)B	T4300B684(*)025(**)	(*)	25V0.68uF	B	0.5	4.0	5.0	6	3	3	4
1	CA43-25V1uF(*)B	T4300B105(*)025(**)	(*)	25V1uF	B	0.5	4.0	5.0	6	3	3	4
1.5	CA43-25V1.5uF(*)C	T4300C155(*)025(**)	(*)	25V1.5uF	C	0.5	4.0	5.0	6	3	3	4
1.5	CA43-25V1.5uF(*)B	T4300B155(*)025(**)	(*)	25V1.5uF	B	0.5	4.0	5.0	6	3	3	4
2.2	CA43-25V2.2uF(*)C	T4300C225(*)025(**)	(*)	25V2.2uF	C	0.6	4.4	5.5	6	3	3	4
2.2	CA43-25V2.2uF(*)B	T4300B225(*)025(**)	(*)	25V2.2uF	B	0.6	4.4	5.5	6	3	3	4
3.3	CA43-25V3.3uF(*)C	T4300C335(*)025(**)	(*)	25V3.3uF	C	0.8	6.6	8.3	6	3	3	4
4.7	CA43-25V4.7uF(*)D	T4300D475(*)025(**)	(*)	25V4.7uF	D	1.2	9.4	11.8	8	4	5	6
4.7	CA43-25V4.7uF(*)C	T4300C475(*)025(**)	(*)	25V4.7uF	C	1.2	9.4	11.8	8	4	5	6
6.8	CA43-25V6.8uF(*)D	T4300D685(*)025(**)	(*)	25V6.8uF	D	1.7	13.6	17.0	8	4	5	6
10	CA43-25V10uF(*)D	T4300D106(*)025(**)	(*)	25V10uF	D	2.5	20.0	25.0	8	4	5	6
15	CA43-25V15uF(*)E	T4300E156(*)025(**)	(*)	25V15uF	E	3.8	30.0	37.5	8	4	5	6
15	CA43-25V15uF(*)D	T4300D156(*)025(**)	(*)	25V15uF	D	3.8	30.0	37.5	8	4	5	6
22	CA43-25V22uF(*)E	T4300E226(*)025(**)	(*)	25V22uF	E	5.5	44.0	55.0	8	4	5	6
22	CA43-25V22uF(*)D	T4300D226(*)025(**)	(*)	25V22uF	D	5.5	44.0	55.0	8	4	5	6
33	CA43-25V33uF(*)F	T4300F336(*)025(**)	(*)	25V33uF	F	8.3	66.0	82.5	8	4	5	6
33	CA43-25V33uF(*)E	T4300E336(*)025(**)	(*)	25V33uF	E	8.3	66.0	82.5	8	4	5	6
33	CA43-25V33uF(*)D	T4300D336(*)025(**)	(*)	25V33uF	D	8.3	66.0	82.5	8	4	5	6
47	CA43-25V47uF(*)F	T4300F476(*)025(**)	(*)	25V47uF	F	11.8	94.0	117.5	8	5	7	8
47	CA43-25V47uF(*)E	T4300E476(*)025(**)	(*)	25V47uF	E	11.8	94.0	117.5	8	5	7	8
68	CA43-25V68uF(*)F	T4300F686(*)025(**)	(*)	25V68uF	F	17.0	136.0	170.0	8	5	7	8
100	CA43-25V100uF(*)F	T4300F107(*)025(**)	(*)	25V100uF	F	25.0	200.0	250.0	10	7	9	10
35 Volt 额定电压 +85℃时 (20 Volt 额定电压 +125℃时)												
0.1	CA43-35V0.1uF(*)B	T4300B104(*)035(**)	(*)	35V0.1uF	B	0.5	4.0	5.0	6	3	3	4
0.15	CA43-35V0.15uF(*)B	T4300B154(*)035(**)	(*)	35V0.15uF	B	0.5	4.0	5.0	6	3	3	4
0.22	CA43-35V0.22uF(*)B	T4300B224(*)035(**)	(*)	35V0.22uF	B	0.5	4.0	5.0	6	3	3	4
0.33	CA43-35V0.33uF(*)B	T4300B334(*)035(**)	(*)	35V0.33uF	B	0.5	4.0	5.0	6	3	3	4
0.47	CA43-35V0.47uF(*)B	T4300B474(*)035(**)	(*)	35V0.47uF	B	0.5	4.0	5.0	6	3	3	4
0.68	CA43-35V0.68uF(*)C	T4300C684(*)035(**)	(*)	35V0.68uF	C	0.5	4.0	5.0	6	3	3	4
0.68	CA43-35V0.68uF(*)B	T4300B684(*)035(**)	(*)	35V0.68uF	B	0.5	4.0	5.0	6	3	3	4
1	CA43-35V1uF(*)C	T4300C105(*)035(**)	(*)	35V1uF	C	0.5	4.0	5.0	6	3	3	4
1	CA43-35V1uF(*)B	T4300B105(*)035(**)	(*)	35V1uF	B	0.5	4.0	5.0	6	3	3	4
1.5	CA43-35V1.5uF(*)C	T4300C155(*)035(**)	(*)	35V1.5uF	C	0.5	4.2	5.3	6	3	3	4
1.5	CA43-35V1.5uF(*)B	T4300B155(*)035(**)	(*)	35V1.5uF	B	0.5	4.2	5.3	6	3	3	4
2.2	CA43-35V2.2uF(*)D	T4300D225(*)035(**)	(*)	35V2.2uF	D	0.8	6.2	7.7	6	3	3	4
2.2	CA43-35V2.2uF(*)C	T4300C225(*)035(**)	(*)	35V2.2uF	C	0.8	6.2	7.7	6	3	3	4
3.3	CA43-35V3.3uF(*)D	T4300D335(*)035(**)	(*)	35V3.3uF	D	1.2	9.2	11.6	6	3	3	4
4.7	CA43-35V4.7uF(*)D	T4300D475(*)035(**)	(*)	35V4.7uF	D	1.6	13.2	16.5	8	4	5	6
6.8	CA43-35V6.8uF(*)E	T4300E685(*)035(**)	(*)	35V6.8uF	E	2.4	19.0	23.8	8	4	5	6
6.8	CA43-35V6.8uF(*)D	T4300D685(*)035(**)	(*)	35V6.8uF	D	2.4	19.0	23.8	8	4	5	6
10	CA43-35V10uF(*)E	T4300E106(*)035(**)	(*)	35V10uF	E	3.5	28.0	35.0	8	4	5	6
10	CA43-35V10uF(*)D	T4300D106(*)035(**)	(*)	35V10uF	D	3.5	28.0	35.0	8	4	5	6
15	CA43-35V15uF(*)F	T4300F156(*)035(**)	(*)	35V15uF	F	5.3	42.0	52.5	8	4	5	6
15	CA43-35V15uF(*)E	T4300E156(*)035(**)	(*)	35V15uF	E	5.3	42.0	52.5	8	4	5	6
22	CA43-35V22uF(*)F	T4300F226(*)035(**)	(*)	35V22uF	F	7.7	61.6	77.0	8	4	5	6
33	CA43-35V33uF(*)F	T4300F336(*)035(**)	(*)	35V33uF	F	11.6	92.4	115.5	8	4	5	6
47	CA43-35V47uF(*)F	T4300F476(*)035(**)	(*)	35V47uF	F	16.5	131.6	164.5	8	5	7	8
50 Volt 额定电压 +85℃时 (32 Volt 额定电压 +125℃时)												
0.1	CA43-50V0.1uF(*)B	T4300B104(*)050(**)	(*)	50V0.1uF	B	0.5	4.0	5.0	6	3	3	4
0.15	CA43-50V0.15uF(*)B	T4300B154(*)050(**)	(*)	50V0.15uF	B	0.5	4.0	5.0	6	3	3	4
0.22	CA43-50V0.22uF(*)B	T4300B224(*)050(**)	(*)	50V0.22uF	B	0.5	4.0	5.0	6	3	3	4
0.33	CA43-50V0.33uF(*)C	T4300C334(*)050(**)	(*)	50V0.33uF	C	0.5	4.0	5.0	6	3	3	4
0.33	CA43-50V0.33uF(*)B	T4300B334(*)050(**)	(*)	50V0.33uF	B	0.5	4.0	5.0	6	3	3	4
0.47	CA43-50V0.47uF(*)C	T4300C474(*)050(**)	(*)	50V0.47uF	C	0.5	4.0	5.0	6	3	3	4
0.47	CA43-50V0.47uF(*)B	T4300B474(*)050(**)	(*)	50V0.47uF	B	0.5	4.0	5.0	6	3	3	4
0.68	CA43-50V0.68uF(*)D	T4300D684(*)050(**)	(*)	50V0.68uF	D	0.5	4.0	5.0	6	3	3	4
0.68	CA43-50V0.68uF(*)C	T4300C684(*)050(**)	(*)	50V0.68uF	C	0.5	4.0	5.0	6	3	3	4
1	CA43-50V1uF(*)D	T4300D105(*)050(**)	(*)	50V1uF	D	0.5	4.0	5.0	6	3	3	4
1.5	CA43-50V1.5uF(*)D	T4300D155(*)050(**)	(*)	50V1.5uF	D	0.8	6.0	7.5	6	3	3	4
2.2	CA43-50V2.2uF(*)D	T4300D225(*)050(**)	(*)	50V2.2uF	D	1.1	8.8	11.0	6	3	3	4
3.3	CA43-50V3.3uF(*)E	T4300E335(*)050(**)	(*)	50V3.3uF	E	1.7	13.2	16.5	6	3	3	4
3.3	CA43-50V3.3uF(*)D	T4300D335(*)050(**)	(*)	50V3.3uF	D	1.7	13.2	16.5	6	3	3	4
4.7	CA43-50V4.7uF(*)E	T4300E475(*)050(**)	(*)	50V4.7uF	E	2.4	18.8	23.5	8	4	5	6
6.8	CA43-50V6.8uF(*)F	T4300F685(*)050(**)	(*)	50V6.8uF	F	3.4	27.2	34.0	8	4	5	6
10	CA43-50V10uF(*)F	T4300F106(*)050(**)	(*)	50V10uF	F	5.0	40.0	50.0	8	4	5	6
15	CA43-50V15uF(*)F	T4300F156(*)050(**)	(*)	50V15uF	F	7.5	60.0	75.0	8	4	5	6

(*)：电容量允许偏差：±10%，±20%

如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。